



SIT1602ACE8-33S Information



For Reference Only

Part Number SIT1602ACE8-33S

Manufacturer SiTIME

Category Crystals, Oscillators, Resonators

Programmable Oscillators

Description OSC PROG LVCMOS 3.3V STBY SMD

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SIT1602ACE8-33S Specifications

Manufacturer Part Number SIT1602ACE8-33S Manufacturer SiTIME Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series SiT1602 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 3.75MHz ~ 77.76MHz Function Standby Output HCMOS, LVCMOS Voltage - Supply 3.3V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)		
Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series SiT1602 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 3.75MHz ~ 77.76MHz Function Standby Output HCMOS, LVCMOS Voltage - Supply 3.3V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Manufacturer Part Number	SIT1602ACE8-33S
Package 4-SMD, No Lead Series SiT1602 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 3.75MHz ~ 77.76MHz Function Standby Output HCMOS, LVCMOS Voltage - Supply - Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Manufacturer	SiTIME
Package 4-SMD, No Lead Series SiT1602 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 3.75MHz ~ 77.76MHz Function Standby Output HCMOS, LVCMOS Voltage - Supply 3.3V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Category	Crystals, Oscillators, Resonators
Series SiT1602 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 3.75MHz ~ 77.76MHz Function Standby Output HCMOS, LVCMOS Voltage - Supply 3.3V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)		Programmable Oscillators
TypeMEMS (Silicon)Programmable TypeProgrammed as RequestAvailable Frequency Range3.75MHz ~ 77.76MHzFunctionStandbyOutputHCMOS, LVCMOSVoltage - Supply3.3VFrequency Stability-Frequency Stability (Total)±20ppm, ±25ppm, ±50ppmOperating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)4.5mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.276" L x 0.197" W (7.00mm x 5.00mm)Height0.039" (1.00mm)	Package	4-SMD, No Lead
Programmable Type Programmed as Request Available Frequency Range 3.75MHz ~ 77.76MHz Function Standby Output HCMOS, LVCMOS Voltage - Supply 3.3V Frequency Stability Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.00000000000000000000000000000000000	Series	SiT1602
Available Frequency Range 3.75MHz ~ 77.76MHz Function Standby Output HCMOS, LVCMOS Voltage - Supply 3.3V Frequency Stability - Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height	Туре	MEMS (Silicon)
Function Standby Output HCMOS, LVCMOS Voltage - Supply 3.3V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.009" (1.00mm)	Programmable Type	Programmed as Request
Output HCMOS, LVCMOS Voltage - Supply 3.3V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.009" (1.00mm)	Available Frequency Range	3.75MHz ~ 77.76MHz
Voltage - Supply Frequency Stability Frequency Stability (Total) Operating Temperature Spread Spectrum Bandwidth - Current - Supply (Max) Ratings Mounting Type Surface Mount Package / Case Size / Dimension Height 3.3V 3.3V 3.3V 5.3V 5.3V 5.30 5.40 5.40 5.40 5.40 5.40 5.40 5.40 5.40 5.40 5.40 5.40 5.40 5.40 5.40 5.40 5.40 6.4	Function	Standby
Frequency Stability (Total) Frequency Stability (Total) Departing Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case Size / Dimension D.276" L x 0.197" W (7.00mm x 5.00mm) Height - - - - - - - - - - - - -	Output	HCMOS, LVCMOS
Frequency Stability (Total) ± 20 ppm, ± 25 ppm, ± 50 ppm Operating Temperature -20° C $\sim 70^{\circ}$ C Spread Spectrum Bandwidth $-$ Current - Supply (Max) 4.5 mA Ratings $-$ Mounting Type Surface Mount Package / Case $4-$ SMD, No Lead Size / Dimension 0.276° L x 0.197° W $(7.00$ mm x 5.00 mm) Height 0.039° $(1.00$ mm)	Voltage - Supply	3.3V
Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Frequency Stability	-
Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Frequency Stability (Total)	±20ppm, ±25ppm, ±50ppm
Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Operating Temperature	-20°C ~ 70°C
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Current - Supply (Max)	4.5mA
Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Ratings	-
Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Mounting Type	Surface Mount
Height 0.039" (1.00mm)	Package / Case	4-SMD, No Lead
	Size / Dimension	0.276" L x 0.197" W (7.00mm x 5.00mm)
Report errors?	Height	0.039" (1.00mm)
		Report errors?

SIT1602ACE8-33S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SIT1602ACE8-33S Payment Methods



















SIT1602ACE8-33S Shipping Methods













If you have any question about SIT1602ACE8-33S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com