



SIT1602AIR3-XXE Information



For Reference Only

Part Number SIT1602AIR3-XXE

Manufacturer SiTIME

Category Crystals, Oscillators, Resonators

Programmable Oscillators

Description OSC PROG LVCMOS 2.25-3.63V EN/DS

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SIT1602AIR3-XXE Specifications

Manufacturer Part Number SIT1602AIR3-XXE Manufacturer SiTIME Category Crystals, Oscillators, Resonators Programmable Oscillators Programmable Oscillators Package 4-SMD, No Lead Series SiT1602 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 3.75MHz ~ 77.76MHz Function Enable/Disable Output HCMOS, LVCMOS Voltage - Supply 2.25 V ~ 3.63 V Frequency Stability ±0ppm, ±25ppm, ±50ppm Operating Temperature 40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)		
Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series SiT1602 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 3.75MHz ~ 77.76MHz Function Enable/Disable Output HCMOS, LVCMOS Voltage - Supply 2.25 V ~ 3.63 V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature 40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Manufacturer Part Number	SIT1602AIR3-XXE
Package 4-SMD, No Lead Series SiT1602 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 3.75MHz ~ 77.76MHz Function Enable/Disable Output HCMOS, LVCMOS Voltage - Supply - 2.25 V ~ 3.63 V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Manufacturer	SiTIME
Package 4-SMD, No Lead Series SiT1602 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 3.75MHz ~ 77.76MHz Function Enable/Disable Output HCMOS, LVCMOS Voltage - Supply 2.25 V ~ 3.63 V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Category	Crystals, Oscillators, Resonators
Series SiT1602 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 3.75MHz ~ 77.76MHz Function Enable/Disable Output HCMOS, LVCMOS Voltage - Supply 2.25 V ~ 3.63 V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)		Programmable Oscillators
Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 3.75MHz ~ 77.76MHz Function Enable/Disable Output HCMOS, LVCMOS Voltage - Supply 2.25 V ~ 3.63 V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature 40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Package	4-SMD, No Lead
Programmable Type Programmed as Request Available Frequency Range 3.75MHz ~ 77.76MHz Function Enable/Disable Output HCMOS, LVCMOS Voltage - Supply 2.25 V ~ 3.63 V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.00000000000000000000000000000000000	Series	SiT1602
Available Frequency Range 3.75MHz ~ 77.76MHz Function Enable/Disable Output HCMOS, LVCMOS Voltage - Supply 2.25 V ~ 3.63 V Frequency Stability Frequency Stability (Total) Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.031" (0.79mm)	Туре	MEMS (Silicon)
Function Enable/Disable Output HCMOS, LVCMOS Voltage - Supply 2.25 V ~ 3.63 V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Programmable Type	Programmed as Request
Output HCMOS, LVCMOS Voltage - Supply 2.25 V ~ 3.63 V Frequency Stability - Frequency Stability (Total) ± 20 ppm, ± 25 ppm, ± 50 ppm Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.0031" (0.79mm)	Available Frequency Range	3.75MHz ~ 77.76MHz
Voltage - Supply Frequency Stability Frequency Stability (Total) Operating Temperature Spread Spectrum Bandwidth - Current - Supply (Max) Ratings Mounting Type Surface Mount Package / Case Size / Dimension Height 2.25 V ~ 3.63 V 2.26 V ~ 3.63 V 2.27 V ~ 3.63 V 2.28 V ~ 3.63 V 2.29 pm, ±50ppm 4.50ppm 4.50ppm 4.50ppm 4.5mA Surface Mount 0.197" L x 0.126" W (5.00mm x 3.20mm) 0.031" (0.79mm)	Function	Enable/Disable
Frequency Stability (Total) Frequency Stability (Total) Departing Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case Size / Dimension D.197" L x 0.126" W (5.00mm x 3.20mm) Height - - - - - - - - - - - - -	Output	HCMOS, LVCMOS
Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Voltage - Supply	2.25 V ~ 3.63 V
Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Frequency Stability	-
Spread Spectrum Bandwidth Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Frequency Stability (Total)	±20ppm, ±25ppm, ±50ppm
Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Operating Temperature	-40°C ~ 85°C
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Current - Supply (Max)	4.5mA
Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Ratings	-
Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Mounting Type	Surface Mount
Height 0.031" (0.79mm)	Package / Case	4-SMD, No Lead
-	Size / Dimension	0.197" L x 0.126" W (5.00mm x 3.20mm)
Report errors?	Height	0.031" (0.79mm)
		Report errors?

SIT1602AIR3-XXE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SIT1602AIR3-XXE Payment Methods



















SIT1602AIR3-XXE Shipping Methods













If you have any question about SIT1602AIR3-XXE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com