



# SIT1602AIT3-33E Information



For Reference Only

Part Number SIT1602AIT3-33E

**Manufacturer** SiTIME

Category Crystals, Oscillators, Resonators

**Programmable Oscillators** 

**Description** OSC PROG LVCMOS 3.3V EN/DS SMD

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **SIT1602AIT3-33E Specifications**

Manufacturer Part Number         SIT1602AIT3-33E           Manufacturer         SiTIME           Category         Crystals, Oscillators, Resonators           Package         4-SMD, No Lead           Series         SiT1602           Type         MEMS (Silicon)           Programmable Type         Programmed as Request           Available Frequency Range         3.75MHz ~ 77.76MHz           Function         Enable/Disable           Output         HCMOS, LVCMOS           Voltage - Supply         3.3V           Frequency Stability         -           Frequency Stability (Total)         ±20ppm, ±25ppm, ±50ppm           Operating Temperature         +40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         4.5mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.197" L x 0.126" W (5.00mm x 3.20mm)           Height         0.031" (0.79mm)		
Category         Crystals, Oscillators, Resonators           Package         4-SMD, No Lead           Series         SiT1602           Type         MEMS (Silicon)           Programmable Type         Programmed as Request           Available Frequency Range         3.75MHz ~ 77.76MHz           Function         Enable/Disable           Output         HCMOS, LVCMOS           Voltage - Supply         3.3V           Frequency Stability         -           Frequency Stability (Total)         ±20ppm, ±25ppm, ±50ppm           Operating Temperature         -40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         4.5mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.197" L x 0.126" W (5.00mm x 3.20mm)           Height         0.031" (0.79mm)	Manufacturer Part Number	SIT1602AIT3-33E
Package         4-SMD, No Lead           Series         SiT1602           Type         MEMS (Silicon)           Programmable Type         Programmed as Request           Available Frequency Range         3.75MHz ~ 77.76MHz           Function         Enable/Disable           Output         HCMOS, LVCMOS           Voltage - Supply         3.3V           Frequency Stability         -           Frequency Stability (Total)         ±20ppm, ±25ppm, ±50ppm           Operating Temperature         -40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         4.5mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.197" L x 0.126" W (5.00mm x 3.20mm)           Height         0.031" (0.79mm)	Manufacturer	SiTIME
Package         4-SMD, No Lead           Series         SiT1602           Type         MEMS (Silicon)           Programmable Type         Programmed as Request           Available Frequency Range         3.75MHz ~ 77.76MHz           Function         Enable/Disable           Output         HCMOS, LVCMOS           Voltage - Supply         3.3V           Frequency Stability         -           Frequency Stability (Total)         ±20ppm, ±25ppm, ±50ppm           Operating Temperature         -40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         4.5mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.197" L x 0.126" W (5.00mm x 3.20mm)           Height         0.031" (0.79mm)	Category	Crystals, Oscillators, Resonators
Series         SiT1602           Type         MEMS (Silicon)           Programmable Type         Programmed as Request           Available Frequency Range         3.75MHz ~ 77.76MHz           Function         Enable/Disable           Output         HCMOS, LVCMOS           Voltage - Supply         3.3V           Frequency Stability         -           Frequency Stability (Total)         ±20ppm, ±25ppm, ±50ppm           Operating Temperature         -40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         4.5mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.197" L x 0.126" W (5.00mm x 3.20mm)           Height         0.031" (0.79mm)		Programmable Oscillators
TypeMEMS (Silicon)Programmable TypeProgrammed as RequestAvailable Frequency Range3.75MHz ~ 77.76MHzFunctionEnable/DisableOutputHCMOS, LVCMOSVoltage - Supply3.3VFrequency Stability-Frequency Stability (Total)±20ppm, ±25ppm, ±50ppmOperating Temperature-40°C ~ 85°CSpread Spectrum Bandwidth-Current - Supply (Max)4.5mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height0.031" (0.79mm)	Package	4-SMD, No Lead
Programmable Type Programmed as Request  Available Frequency Range 3.75MHz ~ 77.76MHz  Function Enable/Disable  Output HCMOS, LVCMOS  Voltage - Supply 3.3V  Frequency Stability Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm  Operating Temperature 40°C ~ 85°C  Spread Spectrum Bandwidth Current - Supply (Max) 4.5mA  Ratings Mounting Type Surface Mount  Package / Case 4-SMD, No Lead  Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm)  Height 0.00000000000000000000000000000000000	Series	SiT1602
Available Frequency Range  Supply  Function  Enable/Disable  Output  HCMOS, LVCMOS  Voltage - Supply  3.3V  Frequency Stability  - Frequency Stability (Total)  Operating Temperature  -40°C ~ 85°C  Spread Spectrum Bandwidth  - Current - Supply (Max)  Ratings  - Mounting Type  Surface Mount  Package / Case  Size / Dimension  0.197" L x 0.126" W (5.00mm x 3.20mm)  Height	Туре	MEMS (Silicon)
Function Enable/Disable Output HCMOS, LVCMOS  Voltage - Supply 3.3V  Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -40°C ~ 85°C  Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA  Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.0031" (0.79mm)	Programmable Type	Programmed as Request
Output HCMOS, LVCMOS  Voltage - Supply 3.3V  Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -40°C ~ 85°C  Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA  Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.0031" (0.79mm)	Available Frequency Range	3.75MHz ~ 77.76MHz
Voltage - Supply Frequency Stability - Frequency Stability (Total)  Operating Temperature  Spread Spectrum Bandwidth - Current - Supply (Max)  Ratings - Mounting Type Surface Mount Package / Case Size / Dimension  Height  3.3V  3.3V  3.3V  4.5m  - Supply (Max)  4.50ppm, ±25ppm, ±50ppm  -40°C ~ 85°C  5.00pm  4.5mA  5.00pm  4.5mA  8.0pm  5.0pm  6.0197" L x 0.126" W (5.00mm x 3.20mm)  6.0031" (0.79mm)	Function	Enable/Disable
Frequency Stability (Total)  Frequency Stability (Total)  Departing Temperature  -40°C ~ 85°C  Spread Spectrum Bandwidth  - Current - Supply (Max)  Ratings  - Mounting Type  Surface Mount  Package / Case  Size / Dimension  D.197" L x 0.126" W (5.00mm x 3.20mm)  Height  -  -  -  -  -  -  -  -  -  -  -  -  -	Output	HCMOS, LVCMOS
Frequency Stability (Total) $\pm 20$ ppm, $\pm 25$ ppm, $\pm 50$ ppm  Operating Temperature $-40^{\circ}$ C $\sim 85^{\circ}$ C  Spread Spectrum Bandwidth $-$ Current - Supply (Max) $4.5$ mA  Ratings $-$ Mounting Type Surface Mount  Package / Case $4-$ SMD, No Lead  Size / Dimension $0.197''$ L x $0.126''$ W ( $5.00$ mm x $3.20$ mm)  Height $0.031''$ ( $0.79$ mm)	Voltage - Supply	3.3V
Operating Temperature -40°C ~ 85°C  Spread Spectrum Bandwidth -  Current - Supply (Max) 4.5mA  Ratings -  Mounting Type Surface Mount  Package / Case 4-SMD, No Lead  Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm)  Height 0.031" (0.79mm)	Frequency Stability	-
Spread Spectrum Bandwidth  Current - Supply (Max)  Ratings  - Mounting Type Surface Mount  Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm)  Height 0.031" (0.79mm)	Frequency Stability (Total)	±20ppm, ±25ppm, ±50ppm
Current - Supply (Max)       4.5mA         Ratings       -         Mounting Type       Surface Mount         Package / Case       4-SMD, No Lead         Size / Dimension       0.197" L x 0.126" W (5.00mm x 3.20mm)         Height       0.031" (0.79mm)	Operating Temperature	-40°C ~ 85°C
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount  Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm)  Height 0.031" (0.79mm)	Current - Supply (Max)	4.5mA
Package / Case       4-SMD, No Lead         Size / Dimension       0.197" L x 0.126" W (5.00mm x 3.20mm)         Height       0.031" (0.79mm)	Ratings	-
Size / Dimension       0.197" L x 0.126" W (5.00mm x 3.20mm)         Height       0.031" (0.79mm)	Mounting Type	Surface Mount
Height 0.031" (0.79mm)	Package / Case	4-SMD, No Lead
-	Size / Dimension	0.197" L x 0.126" W (5.00mm x 3.20mm)
Report errors?	Height	0.031" (0.79mm)
		Report errors?

#### **SIT1602AIT3-33E Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **SIT1602AIT3-33E Payment Methods**



















### SIT1602AIT3-33E Shipping Methods













If you have any question about SIT1602AIT3-33E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com