

SIT1602BCE7-XXS

uote

SIT1602BCE7-XXS Information

For Reference Only	Part Number Manufacturer Category Description	SIT1602BCE7-XXS SiTIME Crystals, Oscillators, Resonators Programmable Oscillators OSC PROG LVCMOS 2.25V-3.63V STBY	
	Package	4-SMD, No Lead For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com	回診療者
		E-mail: salesdept@heisener.com	Request a Qu

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SIT1602BCE7-XXS Specifications

ManufacturerSiTIMECategoryCrystals, Oscillators, ResonatorsPogrammable OscillatorsPackage4-SMD, No LeadSeriesSiT1602TypeMEMS (Silicon)Programmable TypeProgrammed as RequestAvailable Frequency RangeSirMHz ~ 77.76MHzPoutputStordby Power Down)OutputLVCMOSVoltage - Supply-Frequency Stability (Total)-Prequency Stability (Total)-Operating Temperature-Output-Sprad Spectrum Bandwidth-Current - Supply (Max)-Ratings-Anating TypeSufface MountMunting TypeSufface MountPackage / CaseSufface MountSpread Spectrum SpectrumSufface MountSpread Spectrum Spectrum-Sufface MountSufface MountSpread Spectrum SpectrumSufface MountSpread Spectrum Spectrum-Spread Spectrum-Spread Spectrum- <th></th> <th></th>		
CategoryCrystals, Oscillators, ResonatorsProgrammable OscillatorsPackage4-SMD, No LeadSeriesSiT1602TypeMEMS (Silicon)Programmable TypeProgrammed as RequestAvailable Frequency RangeSorMHz ~ 77.76MHzPoutputLVCMOSOutputLVCMOSVoltage - Supply-Frequency Stability (Total)-Prequency Stability (Total)-Operating Temperature-0°C ~ 7°CSpread Spectrum Bandwidth-Current - Supply (Max)Sufface MountRatings-Anating TypeSufface MountProkage / CaseSufface MountProkage / Case0.07° L x 0.063° W (2.00mm x 1.60mm)Height0.031° (0.79mm)	Manufacturer Part Number	SIT1602BCE7-XXS
Programmable OscillatorsPackage4-SMD, No LeadSeriesSiT1602TypeMEMS (Silicon)Programmable TypeProgrammed as RequestAvailable Frequency Range3.57MHz ~ 77.76MHzFunctionStandby (Power Down)OutputLVCMOSVoltage - Supply2.5 V ~ 3.3 VFrequency Stability (Total)-Prequency Stability (Total)-Operating Temperature-0°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)Sufface MountRatings-Package / CaseSufface MountPreducting TypeSufface MountPackage / Case0.079° L x 0.063° W (2.00mm x 1.60mm)Height0.031" (0.79mm)	Manufacturer	SiTIME
Package4-SMD, No LeadSeriesSiT1602TypeMEMS (Silicon)Programmable TypeProgrammed as RequestAvailable Frequency Range3.57MHz ~ 77.76MHzFunctionStandby (Power Down)OutputLVCMOSVoltage - Supply2.5 V ~ 3.3 VFrequency Stability (Total)-20°C ~ 70°COperating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Ratings-Mounting TypeSufface MountPackage / Case4.SMD, No LeadSize / Dimension100°° L x 0.063° W (2.00mm x 1.60mm)Height0.31° (0.79mm)	Category	Crystals, Oscillators, Resonators
SeriesSiT1602TypeMEMS (Silicon)Programmable TypeProgrammed as RequestAvailable Frequency Range3.57MHz ~ 77.76MHzFunctionStandby (Power Down)OutputLVCMOSVoltage - Supply2.5 V ~ 3.3 VFrequency Stability-Frequency Stability (Total)2.0°C ~ 70°COperating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Ratings-Mounting TypeSurface MountPackage / Case4.SMD, No LeadSize / Dimension0.031" (0.79mm)		Programmable Oscillators
TypeMEMS (Silicon)Programmable TypeProgrammed as RequestAvailable Frequency Range3.57MHz ~ 77.76MHzFunctionStandby (Power Down)OutputLVCMOSVoltage - Supply2.5 V ~ 3.3 VFrequency Stability (Total)±20pm, ±25ppm, ±50ppmOperating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)4.5mARatings-Mounting TypeSurface MountPackage / Case4.5MD, No LeadSize / Dimension0.079" L x 0.063" W (2.00mm x 1.60mm)Height0.031" (0.79mm)	Package	4-SMD, No Lead
Programmable Type Programmed as Request Available Frequency Range 3.57MHz ~ 77.76MHz Function Standby (Power Down) Output LVCMOS Voltage - Supply 2.5 V ~ 3.3 V Frequency Stability - Frequency Stability (Total) ±20pm, ±25ppm, ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4.SMD, No Lead Size / Dimension 0.031" (0.79mm)	Series	SiT1602
Available Frequency Range3.57MHz ~ 77.76MHzFunctionStandby (Power Down)OutputLVCMOSVoltage - Supply2.5 V ~ 3.3 VFrequency Stability-Frequency Stability (Total)±20ppn, ±25ppn, ±50ppmOperating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)4.5mARatings-Mounting TypeSurface MountPackage / Case4.5MD, No LeadSize / Dimension0.079" L x 0.063" W (2.00mm x 1.60mm)Height0.031" (0.79mm)	Туре	MEMS (Silicon)
FunctionStandby (Power Down)OutputLVCMOSVoltage - Supply2.5 V ~ 3.3 VFrequency Stability-Frequency Stability (Total)±20pm, ±25ppm, ±50ppmOperating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)4.5mARatings-Mounting TypeSurface MountPackage / Case4.5MD, No LeadSize / Dimension0.079" L x 0.063" W (2.00mm x 1.60mm)Height0.031" (0.79mm)	Programmable Type	Programmed as Request
OutputLVCMOSVoltage - Supply2.5 V ~ 3.3 VFrequency Stability-Frequency Stability (Total)±20ppm, ±50ppmOperating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)4.5mARatings-Mounting TypeSurface MountPackage / Case4.SMD, No LeadSize / Dimension0.079" L x 0.063" W (2.00mm x 1.60mm)Height0.031" (0.79mm)	Available Frequency Range	3.57MHz ~ 77.76MHz
Yoltage - Supply 2.5 V ~ 3.3 V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4.5MD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height 0.031" (0.79mm)	Function	Standby (Power Down)
Frequency Stability-Frequency Stability (Total) $\pm 20ppn, \pm 50ppn$ Operating Temperature $-20^{\circ}C \sim 70^{\circ}C$ Spread Spectrum Bandwidth-Current - Supply (Max)4.5mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.079" L x 0.063" W (2.00mm x 1.60mm)Height0.031" (0.79mm)	Output	LVCMOS
Frequency Stability (Total)±20ppm, ±25ppm, ±50ppmOperating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)4.5mARatings-Mounting TypeSurface MountPackage / Case4.SMD, No LeadSize / Dimension0.079" L x 0.063" W (2.00mm x 1.60mm)Height0.031" (0.79mm)	Voltage - Supply	2.5 V ~ 3.3 V
Operating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)4.5mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.079" L x 0.063" W (2.00mm x 1.60mm)Height0.031" (0.79mm)	Frequency Stability	-
Spread Spectrum Bandwidth-Current - Supply (Max)4.5mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.079" L x 0.063" W (2.00mm x 1.60mm)Height0.031" (0.79mm)	Frequency Stability (Total)	±20ppm, ±25ppm, ±50ppm
Current - Supply (Max)4.5mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.079" L x 0.063" W (2.00mm x 1.60mm)Height0.031" (0.79mm)	Operating Temperature	-20°C ~ 70°C
Ratings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.079" L x 0.063" W (2.00mm x 1.60mm)Height0.031" (0.79mm)	Spread Spectrum Bandwidth	-
Nounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.079" L x 0.063" W (2.00mm x 1.60mm)Height0.031" (0.79mm)	Current - Supply (Max)	4.5mA
Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height 0.031" (0.79mm)	Ratings	-
Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height 0.031" (0.79mm)	Mounting Type	Surface Mount
Height 0.031" (0.79mm)	Package / Case	4-SMD, No Lead
-	Size / Dimension	0.079" L x 0.063" W (2.00mm x 1.60mm)
Report errors?	Height	0.031" (0.79mm)
		Report errors?

SIT1602BCE7-XXS Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SIT1602BCE7-XXS Payment Methods





If you have any question about SIT1602BCE7-XXS, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com