



SIT1602BIT8-30E Information



For Reference Only

Part Number SIT1602BIT8-30E

Manufacturer SiTIME

Category Crystals, Oscillators, Resonators

Programmable Oscillators

Description OSC PROG LVCMOS 3V EN/DS SMD

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SIT1602BIT8-30E Specifications

Manufacturer Part Number SIT1602BIT8-30E Manufacturer SiTIME Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series SiT1602 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 3.57MHz ~ 77.76MHz Function Enable/Disable Output LVCMOS Voltage - Supply 3V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature +40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)		
Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series SiT1602 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 3.57MHz ~ 77.76MHz Function Enable/Disable Output LVCMOS Voltage - Supply 3V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Manufacturer Part Number	SIT1602BIT8-30E
Package 4-SMD, No Lead Series SiT1602 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 3.57MHz ~ 77.76MHz Function Enable/Disable Output LVCMOS Voltage - Supply 3V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Manufacturer	SiTIME
Package 4-SMD, No Lead Series SiT1602 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 3.57MHz ~ 77.76MHz Function Enable/Disable Output LVCMOS Voltage - Supply 3V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Category	Crystals, Oscillators, Resonators
Series SiT1602 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 3.57MHz ~ 77.76MHz Function Enable/Disable Output LVCMOS Voltage - Supply 3V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)		Programmable Oscillators
TypeMEMS (Silicon)Programmable TypeProgrammed as RequestAvailable Frequency Range3.57MHz ~ 77.76MHzFunctionEnable/DisableOutputLVCMOSVoltage - Supply3VFrequency Stability-Frequency Stability (Total)±20ppm, ±25ppm, ±50ppmOperating Temperature-40°C ~ 85°CSpread Spectrum Bandwidth-Current - Supply (Max)4.5mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.276" L x 0.197" W (7.00mm x 5.00mm)Height0.039" (1.00mm)	Package	4-SMD, No Lead
Programmable Type Programmed as Request Available Frequency Range 3.57MHz ~ 77.76MHz Function Enable/Disable Output LVCMOS Voltage - Supply 3V Frequency Stability Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.00000000000000000000000000000000000	Series	SiT1602
Available Frequency Range 3.57MHz ~ 77.76MHz Function Enable/Disable Output LVCMOS Voltage - Supply 3V Frequency Stability	Туре	MEMS (Silicon)
Function Enable/Disable Output LVCMOS Voltage - Supply 3V Frequency Stability Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.009" (1.00mm)	Programmable Type	Programmed as Request
Output LVCMOS Voltage - Supply 3V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.009" (1.00mm)	Available Frequency Range	3.57MHz ~ 77.76MHz
Voltage - Supply Frequency Stability Frequency Stability (Total) Operating Temperature Spread Spectrum Bandwidth - Current - Supply (Max) Ratings Mounting Type Surface Mount Package / Case Size / Dimension Height ASW SUPPOM, ±25ppm, ±50ppm -40°C ~ 85°C -40°C ~ 85°C SPOM -40°C ~ 85°C Surface Mount -500000000000000000000000000000000000	Function	Enable/Disable
Frequency Stability (Total) Frequency Stability (Total) Departing Temperature -40°C ~ 85°C Spread Spectrum Bandwidth Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case Size / Dimension D.039" (1.00mm) +20ppm, ±25ppm, ±50ppm -40°C ~ 85°C -40°C	Output	LVCMOS
Frequency Stability (Total) ± 20 ppm, ± 25 ppm, ± 50 ppm Operating Temperature -40° C $\sim 85^{\circ}$ C Spread Spectrum Bandwidth $-$ Current - Supply (Max) 4.5 mA Ratings $-$ Mounting Type Surface Mount Package / Case $4-$ SMD, No Lead Size / Dimension 0.276° L x 0.197° W (7.00mm x 5.00 mm) Height 0.039° (1.00mm)	Voltage - Supply	3V
Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Frequency Stability	-
Spread Spectrum Bandwidth Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Frequency Stability (Total)	±20ppm, ±25ppm, ±50ppm
Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Operating Temperature	-40°C ~ 85°C
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Current - Supply (Max)	4.5mA
Package / Case 4-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Ratings	-
Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Mounting Type	Surface Mount
Height 0.039" (1.00mm)	Package / Case	4-SMD, No Lead
	Size / Dimension	0.276" L x 0.197" W (7.00mm x 5.00mm)
Report errors?	Height	0.039" (1.00mm)
		Report errors?

SIT1602BIT8-30E Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SIT1602BIT8-30E Payment Methods





















SIT1602BIT8-30E Shipping Methods













If you have any question about SIT1602BIT8-30E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com