



SIT1602BIU2-30E Information



For Reference Only

Part Number SIT1602BIU2-30E

Manufacturer SiTIME

Category Crystals, Oscillators, Resonators

Programmable Oscillators

Description OSC PROG LVCMOS 3V EN/DS SMD

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SIT1602BIU2-30E Specifications

Manufacturer Part Number STI 1602BIU2-30E Manufacturer STIME Category Crystals, Oscillators, Resonators Programmable Oscillators Programmable Oscillators Package 4-SMD, No Lead Series STI 1602 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 3.57MHz ~ 77.76MHz Function Enable/Disable Output LVCMOS Voltage - Supply - Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature ±40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.031" (0.79mm)		
Category Crystals, Oscillators, Resonators Programmable Oscillators Package 4-SMD, No Lead Series SiT1602 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 3.57MHz ~ 77.76MHz Function Enable/Disable Output LVCMOS Voltage - Supply 3V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.031" (0.79mm)	Manufacturer Part Number	SIT1602BIU2-30E
Package 4-SMD, No Lead Series SiT1602 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 3.57MHz ~ 77.76MHz Function Enable/Disable Output LVCMOS Voltage - Supply - Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.031" (0.79mm)	Manufacturer	SiTIME
Package 4-SMD, No Lead Series SiT1602 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 3.57MHz ~ 77.76MHz Function Enable/Disable Output LVCMOS Voltage - Supply 3V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.031" (0.79mm)	Category	Crystals, Oscillators, Resonators
Series SiT1602 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 3.57MHz ~ 77.76MHz Function Enable/Disable Output LVCMOS Voltage - Supply 3V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.031" (0.79mm)		Programmable Oscillators
Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 3.57MHz ~ 77.76MHz Function Enable/Disable Output LVCMOS Voltage - Supply 3V Frequency Stability Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.031" (0.79mm)	Package	4-SMD, No Lead
Programmable Type Programmed as Request Available Frequency Range 3.57MHz ~ 77.76MHz Function Enable/Disable Output LVCMOS Voltage - Supply 3V Frequency Stability Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.00000000000000000000000000000000000	Series	SiT1602
Available Frequency Range 3.57MHz ~ 77.76MHz Function Enable/Disable Output LVCMOS Voltage - Supply 3V Frequency Stability - Frequency Stability (Total) Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.031" (0.79mm)	Туре	MEMS (Silicon)
Function Enable/Disable Output LVCMOS Voltage - Supply 3V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.001" (0.79mm)	Programmable Type	Programmed as Request
Output LVCMOS Voltage - Supply 3V Frequency Stability Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.031" (0.79mm)	Available Frequency Range	3.57MHz ~ 77.76MHz
Voltage - Supply Frequency Stability Frequency Stability (Total) Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case Size / Dimension 0.031" (0.79mm) 3V 3V 3V 3V 3V 3V - Surface Mount +20ppm, ±25ppm, ±50ppm -40°C ~ 85°C -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA - Mounting Type Surface Mount 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height	Function	Enable/Disable
Frequency Stability (Total) Frequency Stability (Total) Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case Size / Dimension Outling Type Outling Type Outling Type Outling Type Surface Mount Outling Type Ou	Output	LVCMOS
Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height +20ppm, ±25ppm, ±50ppm -40°C ~ 85°C - Spread Spectrum Bandwidth - Current - Supply (Max) - Surface Mount 4-SMD, No Lead 0.126" L x 0.098" W (3.20mm x 2.50mm)	Voltage - Supply	3V
Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.031" (0.79mm)	Frequency Stability	-
Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.031" (0.79mm)	Frequency Stability (Total)	±20ppm, ±25ppm, ±50ppm
Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.031" (0.79mm)	Operating Temperature	-40°C ~ 85°C
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.031" (0.79mm)	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.031" (0.79mm)	Current - Supply (Max)	4.5mA
Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.031" (0.79mm)	Ratings	-
Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.031" (0.79mm)	Mounting Type	Surface Mount
Height 0.031" (0.79mm)	Package / Case	4-SMD, No Lead
	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
Report errors?	Height	0.031" (0.79mm)
		Report errors?

SIT1602BIU2-30E Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SIT1602BIU2-30E Payment Methods



















SIT1602BIU2-30E Shipping Methods













If you have any question about SIT1602BIU2-30E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com