

SIT2024BM-S2-XXX-000.FP0000G

SIT2024BM-S2-XXX-000.FP0000G Information



For Reference Only

Part Number SIT2024BM-S2-XXX-000.FP0000G

Manufacturer SiTIME

Category Crystals, Oscillators, Resonators

Programmable Oscillators

Description PROG OSC BLANK 1MHZ-110MHZ

Package SC-74A, SOT-753

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SIT2024BM-S2-XXX-000.FP0000G Specifications

Category Crystals, Oscillators, Resonators Programmable Oscillators Package SC-74A, SOT-753 Series SiT2024B Type MEMS (Silicon) Programmable Type Blank (User Must Program) Available Frequency Range 1MHz ~ 110MHz Function - Output LVCMOS Voltage - Supply 1.8V, 2.5 V ~ 3.3 V Frequency Stability ±25ppm Frequency Stability (Total) ±25ppm Operating Temperature -55°C ~ 125°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.8mA Ratings AEC-Q100 Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Size / Dimension 0.114" L x 0.063" W (2.90mm x 1.60mm)		
Category Crystals, Oscillators, Resonators Programmable Oscillators Package SC-74A, SOT-753 Series SiT2024B Type MEMS (Silicon) Programmable Type Blank (User Must Program) Available Frequency Range 1MHz ~ 110MHz Function - Output LVCMOS Voltage - Supply 1.8V, 2.5 V ~ 3.3 V Frequency Stability ±25ppm Frequency Stability (Total) ±25ppm Operating Temperature -55°C ~ 125°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.8mA Ratings AEC-Q100 Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Size / Dimension 0.114" L x 0.063" W (2.90mm x 1.60mm) Height 0.057" (1.45mm)	Manufacturer Part Number	SIT2024BM-S2-XXX-000.FP0000G
Package SC-74A, SOT-753 Series SiT2024B Type MEMS (Silicon) Programmable Type Blank (User Must Program) Available Frequency Range 1MHz ~ 110MHz Function - Output LVCMOS Voltage - Supply 1.8V, 2.5 V ~ 3.3 V Frequency Stability ±25ppm Frequency Stability (Total) ±25ppm Operating Temperature -55°C ~ 125°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.8mA Ratings AEC-Q100 Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Size / Dimension 0.114" L x 0.063" W (2.90mm x 1.60mm) Height 0.057" (1.45mm)	Manufacturer	SiTIME
Package SC-74A, SOT-753 Series SiT2024B Type MEMS (Silicon) Programmable Type Blank (User Must Program) Available Frequency Range 1MHz ~ 110MHz Function - Output LVCMOS Voltage - Supply 1.8V, 2.5 V ~ 3.3 V Frequency Stability ±25ppm Frequency Stability (Total) ±25ppm Operating Temperature -55°C ~ 125°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.8mA Ratings AEC-Q100 Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Size / Dimension 0.114" L x 0.063" W (2.90mm x 1.60mm) Height 0.057" (1.45mm)	Category	Crystals, Oscillators, Resonators
Series SiT2024B Type MEMS (Silicon) Programmable Type Blank (User Must Program) Available Frequency Range 1MHz ~ 110MHz Function - Output LVCMOS Voltage - Supply 1.8V, 2.5 V ~ 3.3 V Frequency Stability ±25ppm Frequency Stability (Total) ±25ppm Operating Temperature -55°C ~ 125°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.8mA Ratings AEC-Q100 Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Size / Dimension 0.114" L x 0.063" W (2.90mm x 1.60mm) Height 0.057" (1.45mm)		Programmable Oscillators
Type MEMS (Silicon) Programmable Type Blank (User Must Program) Available Frequency Range 1MHz ~ 110MHz Function - Output LVCMOS Voltage - Supply 1.8V, 2.5 V ~ 3.3 V Frequency Stability ±25ppm Frequency Stability (Total) ±25ppm Operating Temperature -55°C ~ 125°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.8mA Ratings AEC-Q100 Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Size / Dimension 0.114" L x 0.063" W (2.90mm x 1.60mm) Height 0.057" (1.45mm)	Package	SC-74A, SOT-753
Programmable Type Blank (User Must Program) Available Frequency Range 1MHz ~ 110MHz Function - Output LVCMOS Voltage - Supply 1.8V, 2.5 V ~ 3.3 V Frequency Stability ±25ppm Frequency Stability (Total) -55°C ~ 125°C Spread Spectrum Bandwidth - Current - Supply (Max) AEC-Q100 Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Size / Dimension 0.057" (1.45mm)	Series	SiT2024B
Available Frequency Range IMHz ~ 110MHz Function - Output LVCMOS Voltage - Supply 1.8V, 2.5 V ~ 3.3 V Frequency Stability Frequency Stability (Total) Operating Temperature -55°C ~ 125°C Spread Spectrum Bandwidth - Current - Supply (Max) ABMA Ratings AEC-Q100 Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Size / Dimension 0.114" L x 0.063" W (2.90mm x 1.60mm) Height	Туре	MEMS (Silicon)
Function - Coutput LVCMOS Voltage - Supply 1.8V, 2.5 V ~ 3.3 V Frequency Stability ±25ppm Frequency Stability (Total) ±25ppm Operating Temperature -55°C ~ 125°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.8mA Ratings AEC-Q100 Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Size / Dimension 0.114" L x 0.063" W (2.90mm x 1.60mm) Height 0.057" (1.45mm)	Programmable Type	Blank (User Must Program)
Output LVCMOS Voltage - Supply 1.8V, 2.5 V ~ 3.3 V Frequency Stability ±25ppm Frequency Stability (Total) ±25ppm Operating Temperature -55°C ~ 125°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.8mA Ratings AEC-Q100 Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Size / Dimension 0.114" L x 0.063" W (2.90mm x 1.60mm) Height 0.057" (1.45mm)	Available Frequency Range	1MHz ~ 110MHz
Voltage - Supply Frequency Stability £25ppm Frequency Stability (Total) Derating Temperature -55°C ~ 125°C Spread Spectrum Bandwidth - Current - Supply (Max) AEC-Q100 Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Size / Dimension Height Lave 0.063" W (2.90mm x 1.60mm) 0.057" (1.45mm)	Function	-
Frequency Stability (Total) ±25ppm Operating Temperature -55°C ~ 125°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.8mA Ratings AEC-Q100 Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Size / Dimension 0.114" L x 0.063" W (2.90mm x 1.60mm) Height +25ppm ±25ppm ±25ppm ±25ppm ±25ppm ±25ppm 50°C ~ 125°C ABC-Q100 50°C ~ 125°C 50°C ~	Output	LVCMOS
Frequency Stability (Total) ±25ppm Operating Temperature -55°C ~ 125°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.8mA Ratings AEC-Q100 Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Size / Dimension 0.114" L x 0.063" W (2.90mm x 1.60mm) Height 0.057" (1.45mm)	Voltage - Supply	1.8V, 2.5 V ~ 3.3 V
Operating Temperature -55°C ~ 125°C Spread Spectrum Bandwidth - Current - Supply (Max) AEC-Q100 Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Size / Dimension 0.114" L x 0.063" W (2.90mm x 1.60mm) Height 0.057" (1.45mm)	Frequency Stability	±25ppm
Spread Spectrum Bandwidth Current - Supply (Max) 4.8mA AEC-Q100 Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Size / Dimension 0.114" L x 0.063" W (2.90mm x 1.60mm) Height 0.057" (1.45mm)	Frequency Stability (Total)	±25ppm
Current - Supply (Max) 4.8mA Ratings AEC-Q100 Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Size / Dimension 0.114" L x 0.063" W (2.90mm x 1.60mm) Height 0.057" (1.45mm)	Operating Temperature	-55°C ~ 125°C
Ratings AEC-Q100 Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Size / Dimension 0.114" L x 0.063" W (2.90mm x 1.60mm) Height 0.057" (1.45mm)	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Size / Dimension 0.114" L x 0.063" W (2.90mm x 1.60mm) Height 0.057" (1.45mm)	Current - Supply (Max)	4.8mA
Package / Case SC-74A, SOT-753 Size / Dimension 0.114" L x 0.063" W (2.90mm x 1.60mm) Height 0.057" (1.45mm)	Ratings	AEC-Q100
Size / Dimension 0.114" L x 0.063" W (2.90mm x 1.60mm) Height 0.057" (1.45mm)	Mounting Type	Surface Mount
Height 0.057" (1.45mm)	Package / Case	SC-74A, SOT-753
	Size / Dimension	0.114" L x 0.063" W (2.90mm x 1.60mm)
Report errors?	Height	0.057" (1.45mm)
		Report errors?

SIT2024BM-S2-XXX-000.FP0000G Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SIT2024BM-S2-XXX-000.FP0000G Payment Methods



















SIT2024BM-S2-XXX-000.FP0000G Shipping Methods













If you have any question about SIT2024BM-S2-XXX-000.FP0000G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com