



### SIT3807AI-2-33SM Information



For Reference Only

Part Number SIT3807AI-2-33SM

Manufacturer SiTIME

Category Crystals, Oscillators, Resonators

**Programmable Oscillators** 

**Description** OSC PROG LVCMOS 3.3V STBY 25PPM

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## SIT3807AI-2-33SM Specifications

Manufacturer Part Number         SIT3807AI-2-33SM           Manufacturer         SiTIME           Category         Crystals, Oscillators, Resonators           Programmable Oscillators           Package         4-SMD, No Lead           Series         SiT3807           Type         MEMS VCXO           Programmable Type         Programmed as Request           Available Frequency Range         1.544MHz ~ 49.152MHz           Function         Standby           Output         LVCMOS, LVTTL           Voltage - Supply         3.3V           Frequency Stability         ±25ppm           Frequency Stability (Total)         -           Operating Temperature         40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         33mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.126" L x 0.098" W (3.20mm x 2.50mm)           Height         0.031" (0.79mm)		
Category         Crystals, Oscillators, Resonators           Package         4-SMD, No Lead           Series         SiT3807           Type         MEMS VCXO           Programmable Type         Programmed as Request           Available Frequency Range         1.544MHz ~ 49.152MHz           Function         Standby           Output         LVCMOS, LVTTL           Voltage - Supply         3.3V           Frequency Stability         ±25ppm           Frequency Stability (Total)         -           Operating Temperature         -40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         33mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.126" L x 0.098" W (3.20mm x 2.50mm)           Height         0.031" (0.79mm)	Manufacturer Part Number	SIT3807AI-2-33SM
Package         4-SMD, No Lead           Series         SiT3807           Type         MEMS VCXO           Programmable Type         Programmed as Request           Available Frequency Range         1.544MHz ~ 49.152MHz           Function         Standby           Output         LVCMOS, LVTTL           Voltage - Supply         3.3V           Frequency Stability         ±25ppm           Frequency Stability (Total)         -           Operating Temperature         -40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         33mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.126" L x 0.098" W (3.20mm x 2.50mm)           Height         0.031" (0.79mm)	Manufacturer	SiTIME
Package         4-SMD, No Lead           Series         SiT3807           Type         MEMS VCXO           Programmable Type         Programmed as Request           Available Frequency Range         1.544MHz ~ 49.152MHz           Function         Standby           Output         LVCMOS, LVTTL           Voltage - Supply         3.3V           Frequency Stability         ±25ppm           Frequency Stability (Total)         -           Operating Temperature         -40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         33mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.126" L x 0.098" W (3.20mm x 2.50mm)           Height         0.031" (0.79mm)	Category	Crystals, Oscillators, Resonators
Series         SiT3807           Type         MEMS VCXO           Programmable Type         Programmed as Request           Available Frequency Range         1.544MHz ~ 49.152MHz           Function         Standby           Output         LVCMOS, LVTTL           Voltage - Supply         3.3V           Frequency Stability         ±25ppm           Frequency Stability (Total)         -           Operating Temperature         -40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         33mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.126" L x 0.098" W (3.20mm x 2.50mm)           Height         0.031" (0.79mm)		Programmable Oscillators
Type MEMS VCXO  Programmable Type Programmed as Request  Available Frequency Range 1.544MHz ~ 49.152MHz  Function Standby  Output LVCMOS, LVTTL  Voltage - Supply 3.3V  Frequency Stability +25ppm  Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C  Spread Spectrum Bandwidth - Current - Supply (Max) 33mA  Ratings - Mounting Type Surface Mount  Package / Case 4-SMD, No Lead  Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm)  Height 0.031" (0.79mm)	Package	4-SMD, No Lead
Programmable Type Programmed as Request  Available Frequency Range 1.544MHz ~ 49.152MHz  Function Standby  Output LVCMOS, LVTTL  Voltage - Supply 3.3V  Frequency Stability ±25ppm  Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C  Spread Spectrum Bandwidth - Current - Supply (Max) 33mA  Ratings - Mounting Type Surface Mount  Package / Case 4-SMD, No Lead  Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm)  Height 0.00000000000000000000000000000000000	Series	SiT3807
Available Frequency Range  1.544MHz ~ 49.152MHz  Function  Standby  Output  LVCMOS, LVTTL  Voltage - Supply  3.3V  Frequency Stability  ±25ppm  Frequency Stability (Total)  - Operating Temperature  -40°C ~ 85°C  Spread Spectrum Bandwidth  - Current - Supply (Max)  33mA  Ratings  - Mounting Type  Surface Mount  Package / Case  4-SMD, No Lead  Size / Dimension  0.0126" L x 0.098" W (3.20mm x 2.50mm)  Height	Туре	MEMS VCXO
Function Standby Output LVCMOS, LVTTL Voltage - Supply 3.3V Frequency Stability ±25ppm Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 33mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.031" (0.79mm)	Programmable Type	Programmed as Request
Output LVCMOS, LVTTL  Voltage - Supply 3.3V  Frequency Stability ±25ppm  Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C  Spread Spectrum Bandwidth - Current - Supply (Max) 33mA  Ratings - Mounting Type Surface Mount  Package / Case 4-SMD, No Lead  Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm)  Height 0.031" (0.79mm)	Available Frequency Range	1.544MHz ~ 49.152MHz
Voltage - Supply  Frequency Stability  Frequency Stability (Total)  Operating Temperature  -40°C ~ 85°C  Spread Spectrum Bandwidth  - Current - Supply (Max)  Ratings  - Mounting Type  Surface Mount  Package / Case  4-SMD, No Lead  Size / Dimension  Height  3.3V  33V  33V  425ppm  -  40°C ~ 85°C  57  57  58  58  58  40°C ~ 85°C  58  40°C ~ 85°C  58  40°C ~ 85°C  58  40°C ~ 85°C  4	Function	Standby
Frequency Stability (Total)  Operating Temperature  Operating Sapectrum Bandwidth  Current - Supply (Max)  Ratings  -  Mounting Type  Surface Mount  Package / Case  Size / Dimension  Height  +25ppm  -  -40°C ~ 85°C  -40°C ~ 85°C  -  -40°C ~ 85°	Output	LVCMOS, LVTTL
Frequency Stability (Total)  Operating Temperature  -40°C ~ 85°C  Spread Spectrum Bandwidth  - Current - Supply (Max)  Ratings  - Mounting Type  Surface Mount  Package / Case  4-SMD, No Lead  Size / Dimension  0.126" L x 0.098" W (3.20mm x 2.50mm)  Height	Voltage - Supply	3.3V
Operating Temperature -40°C ~ 85°C  Spread Spectrum Bandwidth -  Current - Supply (Max) 33mA  Ratings -  Mounting Type Surface Mount  Package / Case 4-SMD, No Lead  Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm)  Height 0.031" (0.79mm)	Frequency Stability	±25ppm
Spread Spectrum Bandwidth - Current - Supply (Max) 33mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.031" (0.79mm)	Frequency Stability (Total)	-
Current - Supply (Max)  Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.031" (0.79mm)	Operating Temperature	-40°C ~ 85°C
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.031" (0.79mm)	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount  Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm)  Height 0.031" (0.79mm)	Current - Supply (Max)	33mA
Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.031" (0.79mm)	Ratings	-
Size / Dimension       0.126" L x 0.098" W (3.20mm x 2.50mm)         Height       0.031" (0.79mm)	Mounting Type	Surface Mount
Height 0.031" (0.79mm)	Package / Case	4-SMD, No Lead
	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
Report errors?	Height	0.031" (0.79mm)
		Report errors?

#### SIT3807AI-2-33SM Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### SIT3807AI-2-33SM Payment Methods





















## SIT3807AI-2-33SM Shipping Methods













If you have any question about SIT3807AI-2-33SM, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com