



### SIT3808AC-C-18EH Information



For Reference Only

Part Number SIT3808AC-C-18EH

**Manufacturer** SiTIME

Category Crystals, Oscillators, Resonators

**Programmable Oscillators** 

**Description** OSC PROG LVCMOS 1.8V EN/DS 10PPM

Package 6-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# SIT3808AC-C-18EH Specifications

Manufacturer Part Number         SIT3808AC-C-18EH           Manufacturer         SiTIME           Category         Crystals, Oscillators, Resonators           Package         6-SMD, No Lead           Series         SiT3808           Type         MEMS VCXO           Programmable Type         Programmed as Request           Available Frequency Range         1MHz ~ 80MHz           Function         Enable/Disable           Output         LVCMOS, LVTTL           Voltage - Supply         1.8V           Frequency Stability         ±10ppm           Frequency Stability (Total)         -           Operating Temperature         -20°C ~ 70°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         31mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         6-SMD, No Lead           Size / Dimension         0.197" L x 0.126" W (5.00mm x 3.20mm)           Height         0.031" (0.79mm)		
Category         Crystals, Oscillators, Resonators           Package         6-SMD, No Lead           Series         SiT3808           Type         MEMS VCXO           Programmable Type         Programmed as Request           Available Frequency Range         1MHz ~ 80MHz           Function         Enable/Disable           Output         LVCMOS, LVTTL           Voltage - Supply         1.8V           Frequency Stability (Total)         -           Operating Temperature         -20°C ~ 70°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         31mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         6-SMD, No Lead           Size / Dimension         0.197" L x 0.126" W (5.00mm x 3.20mm)           Height         0.031" (0.79mm)	Manufacturer Part Number	SIT3808AC-C-18EH
Package         6-SMD, No Lead           Series         SiT3808           Type         MEMS VCXO           Programmable Type         Programmed as Request           Available Frequency Range         1MHz ~ 80MHz           Function         Enable/Disable           Output         LVCMOS, LVTTL           Voltage - Supply         1.8V           Frequency Stability         ±10ppm           Frequency Stability (Total)         -           Operating Temperature         -20°C ~ 70°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         31mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         6-SMD, No Lead           Size / Dimension         0.197" L x 0.126" W (5.00mm x 3.20mm)           Height         0.031" (0.79mm)	Manufacturer	SiTIME
Package         6-SMD, No Lead           Series         SiT3808           Type         MEMS VCXO           Programmable Type         Programmed as Request           Available Frequency Range         1MHz ~ 80MHz           Function         Enable/Disable           Output         LVCMOS, LVTTL           Voltage - Supply         1.8V           Frequency Stability         ±10ppm           Frequency Stability (Total)         -           Operating Temperature         -20°C ~ 70°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         31mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         6-SMD, No Lead           Size / Dimension         0.197" L x 0.126" W (5.00mm x 3.20mm)           Height         0.031" (0.79mm)	Category	Crystals, Oscillators, Resonators
Series         SiT3808           Type         MEMS VCXO           Programmable Type         Programmed as Request           Available Frequency Range         1MHz ~ 80MHz           Function         Enable/Disable           Output         LVCMOS, LVTTL           Voltage - Supply         1.8V           Frequency Stability         ±10ppm           Frequency Stability (Total)         -           Operating Temperature         -20°C ~ 70°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         31mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         6-SMD, No Lead           Size / Dimension         0.197" L x 0.126" W (5.00mm x 3.20mm)           Height         0.031" (0.79mm)		Programmable Oscillators
TypeMEMS VCXOProgrammable TypeProgrammed as RequestAvailable Frequency Range1MHz ~ 80MHzFunctionEnable/DisableOutputLVCMOS, LVTTLVoltage - Supply1.8VFrequency Stability±10ppmFrequency Stability (Total)-Operating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)31mARatings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height0.031" (0.79mm)	Package	6-SMD, No Lead
Programmable Type Programmed as Request  Available Frequency Range 1MHz ~ 80MHz  Function Enable/Disable  Output LVCMOS, LVTTL  Voltage - Supply 1.8V  Frequency Stability ±10ppm  Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C  Spread Spectrum Bandwidth - Current - Supply (Max) 31mA  Ratings - Mounting Type Surface Mount  Package / Case 6-SMD, No Lead  Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm)  Height   MHz ~ 80MHz    IMHz ~ 80MHz    Frequency Stability (Total)    LVCMOS, LVTTL  LVCMOS, LVCMOS  LVCMOS, LVCTOS	Series	SiT3808
Available Frequency Range  Function  Enable/Disable  Output  LVCMOS, LVTTL  Voltage - Supply  1.8V  Frequency Stability  #10ppm  Frequency Stability (Total)  Operating Temperature  -20°C ~ 70°C  Spread Spectrum Bandwidth  - Current - Supply (Max)  Ratings  - Mounting Type  Surface Mount  Package / Case  6-SMD, No Lead  Size / Dimension  0.031" (0.79mm)	Туре	MEMS VCXO
Function Enable/Disable Output LVCMOS, LVTTL Voltage - Supply 1.8V Frequency Stability ±10ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 31mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Programmable Type	Programmed as Request
Output LVCMOS, LVTTL  Voltage - Supply 1.8V  Frequency Stability ±10ppm  Frequency Stability (Total) - Operating Temperature -20°C ~70°C  Spread Spectrum Bandwidth - Current - Supply (Max) 31mA  Ratings - Mounting Type Surface Mount  Package / Case 6-SMD, No Lead  Size / Dimension 0.031" (0.79mm)	Available Frequency Range	1MHz ~ 80MHz
Voltage - Supply Frequency Stability Frequency Stability (Total) Operating Temperature Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case Size / Dimension Height  1.8V  - 10ppm - 108V - 109pm - 108V - 108	Function	Enable/Disable
Frequency Stability (Total)	Output	LVCMOS, LVTTL
Frequency Stability (Total)  Operating Temperature  -20°C ~ 70°C  Spread Spectrum Bandwidth  - Current - Supply (Max)  Ratings  - Mounting Type  Surface Mount  Package / Case  6-SMD, No Lead  Size / Dimension  0.197" L x 0.126" W (5.00mm x 3.20mm)  Height	Voltage - Supply	1.8V
Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 31mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Frequency Stability	±10ppm
Spread Spectrum Bandwidth  Current - Supply (Max)  Ratings  - Mounting Type Surface Mount  Package / Case 6-SMD, No Lead  Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm)  Height 0.031" (0.79mm)	Frequency Stability (Total)	-
Current - Supply (Max)       31mA         Ratings       -         Mounting Type       Surface Mount         Package / Case       6-SMD, No Lead         Size / Dimension       0.197" L x 0.126" W (5.00mm x 3.20mm)         Height       0.031" (0.79mm)	Operating Temperature	-20°C ~ 70°C
Ratings -  Mounting Type Surface Mount  Package / Case 6-SMD, No Lead  Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm)  Height 0.031" (0.79mm)	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount  Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm)  Height 0.031" (0.79mm)	Current - Supply (Max)	31mA
Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Ratings	-
Size / Dimension       0.197" L x 0.126" W (5.00mm x 3.20mm)         Height       0.031" (0.79mm)	Mounting Type	Surface Mount
Height 0.031" (0.79mm)	Package / Case	6-SMD, No Lead
-	Size / Dimension	0.197" L x 0.126" W (5.00mm x 3.20mm)
Report errors?	Height	0.031" (0.79mm)
		Report errors?

#### SIT3808AC-C-18EH Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## SIT3808AC-C-18EH Payment Methods



















## SIT3808AC-C-18EH Shipping Methods













If you have any question about SIT3808AC-C-18EH, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com