



SIT3808AI-C-25EE Information



For Reference Only

Part Number SIT3808AI-C-25EE

Manufacturer SiTIME

Category Crystals, Oscillators, Resonators

Programmable Oscillators

Description OSC PROG LVCMOS 2.5V EN/DS 10PPM

Package 6-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SIT3808AI-C-25EE Specifications

Manufacturer Part Number SIT3808AI-C-25EE Manufacturer SiTIME Category Crystals, Oscillators, Resonators Programmable Oscillators Programmable Oscillators Package 6-SMD, No Lead Series SiT3808 Type MEMS VCXO Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 80MHz Function Enable/Disable Output LVCMOS, LVTTL Voltage - Supply 2.5V Frequency Stability +10ppm Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 33mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)		
Category Crystals, Oscillators, Resonators Package 6-SMD, No Lead Series SiT3808 Type MEMS VCXO Programmable Type Programmed as Request Available Frequency Range IMHz ~ 80MHz Function Enable/Disable Output LVCMOS, LVTTL Voltage - Supply 2.5V Frequency Stability ±10ppm Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 33mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Manufacturer Part Number	SIT3808AI-C-25EE
Package 6-SMD, No Lead Series SiT3808 Type MEMS VCXO Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 80MHz Function Enable/Disable Output LVCMOS, LVTTL Voltage - Supply 2.5V Frequency Stability ±10ppm Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 33mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Manufacturer	SiTIME
Package 6-SMD, No Lead Series SiT3808 Type MEMS VCXO Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 80MHz Function Enable/Disable Output LVCMOS, LVTTL Voltage - Supply 2.5V Frequency Stability ±10ppm Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 33mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Category	Crystals, Oscillators, Resonators
SeriesSiT3808TypeMEMS VCXOProgrammable TypeProgrammed as RequestAvailable Frequency Range1MHz ~ 80MHzFunctionEnable/DisableOutputLVCMOS, LVTTLVoltage - Supply2.5VFrequency Stability±10ppmFrequency Stability (Total)-Operating Temperature-40°C ~ 85°CSpread Spectrum Bandwidth-Current - Supply (Max)33mARatings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height0.031" (0.79mm)		Programmable Oscillators
Type MEMS VCXO Programmable Type Programmed as Request Available Frequency Range IMHz ~ 80MHz Function Enable/Disable Output LVCMOS, LVTTL Voltage - Supply 2.5V Frequency Stability Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 33mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.031" (0.79mm)	Package	6-SMD, No Lead
Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 80MHz Function Enable/Disable Output LVCMOS, LVTTL Voltage - Supply 2.5V Frequency Stability ±10ppm Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 33mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.00000000000000000000000000000000000	Series	SiT3808
Available Frequency Range IMHz ~ 80MHz Function Enable/Disable Output LVCMOS, LVTTL Voltage - Supply 2.5V Frequency Stability ±10ppm Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 33mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height	Туре	MEMS VCXO
Function Enable/Disable Output LVCMOS, LVTTL Voltage - Supply 2.5V Frequency Stability ±10ppm Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 33mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Programmable Type	Programmed as Request
Output LVCMOS, LVTTL Voltage - Supply 2.5V Frequency Stability ±10ppm Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 33mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.001" (0.79mm)	Available Frequency Range	1MHz ~ 80MHz
Voltage - Supply Frequency Stability Frequency Stability (Total) Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension Height 2.5V 2.5V 2.5V 5PO Surface Mount - 0.031" (0.79mm)	Function	Enable/Disable
Frequency Stability (Total)	Output	LVCMOS, LVTTL
Frequency Stability (Total) Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height	Voltage - Supply	2.5V
Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 33mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Frequency Stability	±10ppm
Spread Spectrum Bandwidth Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Frequency Stability (Total)	-
Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Operating Temperature	-40°C ~ 85°C
Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Current - Supply (Max)	33mA
Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Ratings	-
Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Mounting Type	Surface Mount
Height 0.031" (0.79mm)	Package / Case	6-SMD, No Lead
	Size / Dimension	0.197" L x 0.126" W (5.00mm x 3.20mm)
Report errors?	Height	0.031" (0.79mm)
		Report errors?

SIT3808AI-C-25EE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SIT3808AI-C-25EE Payment Methods





















SIT3808AI-C-25EE Shipping Methods













If you have any question about SIT3808AI-C-25EE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com