



SIT3809AC-G-18EX Information



For Reference Only

Part Number SIT3809AC-G-18EX

Manufacturer SiTIME

Category Crystals, Oscillators, Resonators

Programmable Oscillators

Description OSC PROG LVCMOS 1.8V EN/DS 10PPM

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SIT3809AC-G-18EX Specifications

Manufacturer Part Number SIT3809AC-G-18EX Manufacturer SiTIME Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series SiT3809 Type MEMS VCXO Programmable Type Programmed as Request Available Frequency Range 80MHz ~ 220MHz Function Enable/Disable Output LVCMOS, LVTTL Voltage - Supply ±10ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 33mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.106" L x 0.094" W (2.70mm x 2.40mm) Height 0.031" (0.79mm)		
Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series SiT3809 Type MEMS VCXO Programmable Type Programmed as Request Available Frequency Range 80MHz ~ 220MHz Function Enable/Disable Output LVCMOS, LVTTL Voltage - Supply 1.8V Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 33mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.106" L x 0.094" W (2.70mm x 2.40mm) Height 0.031" (0.79mm)	Manufacturer Part Number	SIT3809AC-G-18EX
Package 4-SMD, No Lead Series SiT3809 Type MEMS VCXO Programmable Type Programmed as Request Available Frequency Range 80MHz ~ 220MHz Function Enable/Disable Output LVCMOS, LVTTL Voltage - Supply 1.8V Frequency Stability ±10ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 33mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.106" L x 0.094" W (2.70mm x 2.40mm) Height 0.031" (0.79mm)	Manufacturer	SiTIME
Package 4-SMD, No Lead Series SiT3809 Type MEMS VCXO Programmable Type Programmed as Request Available Frequency Range 80MHz ~ 220MHz Function Enable/Disable Output LVCMOS, LVTTL Voltage - Supply 1.8V Frequency Stability ±10ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 33mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.106" L x 0.094" W (2.70mm x 2.40mm) Height 0.031" (0.79mm)	Category	Crystals, Oscillators, Resonators
Series SiT3809 Type MEMS VCXO Programmable Type Programmed as Request Available Frequency Range 80MHz ~ 220MHz Function Enable/Disable Output LVCMOS, LVTTL Voltage - Supply 1.8V Frequency Stability ±10ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 33mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.106" L x 0.094" W (2.70mm x 2.40mm) Height 0.031" (0.79mm)		Programmable Oscillators
TypeMEMS VCXOProgrammable TypeProgrammed as RequestAvailable Frequency Range80MHz ~ 220MHzFunctionEnable/DisableOutputLVCMOS, LVTTLVoltage - Supply1.8VFrequency Stability±10ppmFrequency Stability (Total)-Operating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)33mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.106" L x 0.094" W (2.70mm x 2.40mm)Height0.031" (0.79mm)	Package	4-SMD, No Lead
Programmable Type Programmed as Request Available Frequency Range 80MHz ~ 220MHz Function Enable/Disable Output LVCMOS, LVTTL Voltage - Supply 1.8V Frequency Stability ±10ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 33mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.106" L x 0.094" W (2.70mm x 2.40mm) Height 0.0000 1.000	Series	SiT3809
Available Frequency Range 80MHz ~ 220MHz Function Enable/Disable Output LVCMOS, LVTTL Voltage - Supply 1.8V Frequency Stability ±10ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 33mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.031" (0.79mm)	Туре	MEMS VCXO
Function Enable/Disable Output LVCMOS, LVTTL Voltage - Supply 1.8V Frequency Stability ±10ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 33mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.106" L x 0.094" W (2.70mm x 2.40mm) Height 0.031" (0.79mm)	Programmable Type	Programmed as Request
OutputLVCMOS, LVTTLVoltage - Supply1.8VFrequency Stability±10ppmFrequency Stability (Total)-Operating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)33mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.106" L x 0.094" W (2.70mm x 2.40mm)Height0.031" (0.79mm)	Available Frequency Range	80MHz ~ 220MHz
Voltage - Supply Frequency Stability Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension Height 1.8V - 109m -20°C ~ 70°C -20°C ~ 70°	Function	Enable/Disable
Frequency Stability (Total)	Output	LVCMOS, LVTTL
Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.106" L x 0.094" W (2.70mm x 2.40mm) Height - 0.031" (0.79mm)	Voltage - Supply	1.8V
Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 33mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.106" L x 0.094" W (2.70mm x 2.40mm) Height 0.031" (0.79mm)	Frequency Stability	±10ppm
Spread Spectrum Bandwidth Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.106" L x 0.094" W (2.70mm x 2.40mm) Height 0.031" (0.79mm)	Frequency Stability (Total)	-
Current - Supply (Max) 33mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.106" L x 0.094" W (2.70mm x 2.40mm) Height 0.031" (0.79mm)	Operating Temperature	-20°C ~ 70°C
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.106" L x 0.094" W (2.70mm x 2.40mm) Height 0.031" (0.79mm)	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.106" L x 0.094" W (2.70mm x 2.40mm) Height 0.031" (0.79mm)	Current - Supply (Max)	33mA
Package / Case 4-SMD, No Lead Size / Dimension 0.106" L x 0.094" W (2.70mm x 2.40mm) Height 0.031" (0.79mm)	Ratings	-
Size / Dimension 0.106" L x 0.094" W (2.70mm x 2.40mm) Height 0.031" (0.79mm)	Mounting Type	Surface Mount
Height 0.031" (0.79mm)	Package / Case	4-SMD, No Lead
-	Size / Dimension	0.106" L x 0.094" W (2.70mm x 2.40mm)
Report errors?	Height	0.031" (0.79mm)
		Report errors?

SIT3809AC-G-18EX Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SIT3809AC-G-18EX Payment Methods



















SIT3809AC-G-18EX Shipping Methods













If you have any question about SIT3809AC-G-18EX, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com