



## SIT3809AC-G-25NY Information



For Reference Only

Part Number SIT3809AC-G-25NY

**Manufacturer** SiTIME

Category Crystals, Oscillators, Resonators

**Programmable Oscillators** 

**Description** OSC PROG LVCMOS 2.5V 10PPM SMD

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## SIT3809AC-G-25NY Specifications

Manufacturer Part Number         SIT3809AC-G-25NY           Manufacturer         SiTIME           Category         Crystals, Oscillators, Resonators           Programmable Oscillators           Package         4-SMD, No Lead           Series         SiT3809           Type         MEMS VCXO           Programmable Type         Programmed as Request           Available Frequency Range         80MHz ~ 220MHz           Function         -           Output         LVCMOS, LVTTL           Voltage - Supply         2.5V           Frequency Stability         +10ppm           Frequency Stability (Total)         -           Operating Temperature         -20°C ~ 70°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         36mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.106" L x 0.094" W (2.70mm x 2.40mm)           Height         0.031" (0.79mm)		
Category         Crystals, Oscillators, Resonators           Programmable Oscillators           Package         4-SMD, No Lead           Series         SiT3809           Type         MEMS VCXO           Programmable Type         Programmed as Request           Available Frequency Range         80MHz ~ 220MHz           Function         -           Output         LVCMOS, LVTTL           Voltage - Supply         2.5V           Frequency Stability (Total)         -           Operating Temperature         -20°C ~ 70°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         36mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.106" L x 0.094" W (2.70mm x 2.40mm)           Height         0.031" (0.79mm)	Manufacturer Part Number	SIT3809AC-G-25NY
Package         4-SMD, No Lead           Series         SiT3809           Type         MEMS VCXO           Programmable Type         Programmed as Request           Available Frequency Range         80MHz ~ 220MHz           Function         -           Output         LVCMOS, LVTTL           Voltage - Supply         2.5V           Frequency Stability         ±10ppm           Frequency Stability (Total)         -           Operating Temperature         -20°C ~ 70°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         36mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.106" L x 0.094" W (2.70mm x 2.40mm)           Height         0.031" (0.79mm)	Manufacturer	SiTIME
Package         4-SMD, No Lead           Series         SiT3809           Type         MEMS VCXO           Programmable Type         Programmed as Request           Available Frequency Range         80MHz ~ 220MHz           Function         -           Output         LVCMOS, LVTTL           Voltage - Supply         2.5V           Frequency Stability         ±10ppm           Frequency Stability (Total)         -           Operating Temperature         -20°C ~ 70°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         36mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.106" L x 0.094" W (2.70mm x 2.40mm)           Height         0.031" (0.79mm)	Category	Crystals, Oscillators, Resonators
Series         SiT3809           Type         MEMS VCXO           Programmable Type         Programmed as Request           Available Frequency Range         80MHz ~ 220MHz           Function         -           Output         LVCMOS, LVTTL           Voltage - Supply         2.5V           Frequency Stability         ±10ppm           Frequency Stability (Total)         -           Operating Temperature         -20°C ~ 70°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         36mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.106" L x 0.094" W (2.70mm x 2.40mm)           Height         0.031" (0.79mm)		Programmable Oscillators
Type MEMS VCXO  Programmable Type Programmed as Request  Available Frequency Range 80MHz ~ 220MHz  Function -  Output LVCMOS, LVTTL  Voltage - Supply 2.5V  Frequency Stability + 10ppm  Frequency Stability (Total) -  Operating Temperature -20°C ~ 70°C  Spread Spectrum Bandwidth -  Current - Supply (Max) 36mA  Ratings -  Mounting Type Surface Mount  Package / Case 4-SMD, No Lead  Size / Dimension 0.106" L x 0.094" W (2.70mm x 2.40mm)  Height 0.031" (0.79mm)	Package	4-SMD, No Lead
Programmable Type Programmed as Request  Available Frequency Range 80MHz ~ 220MHz  Function - CUtput LVCMOS, LVTTL  Voltage - Supply 2.5V  Frequency Stability ±10ppm  Frequency Stability (Total) - COperating Temperature -20°C ~ 70°C  Spread Spectrum Bandwidth - Current - Supply (Max) 36mA  Ratings - Surface Mount  Package / Case 4-SMD, No Lead  Size / Dimension 0.106" L x 0.094" W (2.70mm x 2.40mm)  Height 0.00000000000000000000000000000000000	Series	SiT3809
Available Frequency Range  Function  Output  LVCMOS, LVTTL  Voltage - Supply  2.5V  Frequency Stability  †10ppm  Frequency Stability (Total)  Operating Temperature  -20°C ~ 70°C  Spread Spectrum Bandwidth  - Current - Supply (Max)  Ratings  Amale Surface Mount  Package / Case  4-SMD, No Lead  Size / Dimension  0.031" (0.79mm)	Туре	MEMS VCXO
Function - Coutput LVCMOS, LVTTL  Voltage - Supply 2.5V  Frequency Stability ±10ppm  Frequency Stability (Total) - Coperating Temperature -20°C ~ 70°C  Spread Spectrum Bandwidth - Current - Supply (Max) 36mA  Ratings - Surface Mount  Package / Case 4-SMD, No Lead  Size / Dimension 0.031" (0.79mm)	Programmable Type	Programmed as Request
OutputLVCMOS, LVTTLVoltage - Supply2.5VFrequency Stability±10ppmFrequency Stability (Total)-Operating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)36mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.106" L x 0.094" W (2.70mm x 2.40mm)Height0.031" (0.79mm)	Available Frequency Range	80MHz ~ 220MHz
Voltage - Supply  Frequency Stability  Frequency Stability (Total)  Operating Temperature  -20°C ~ 70°C  Spread Spectrum Bandwidth  - Current - Supply (Max)  SafmA  Ratings  - Mounting Type  Surface Mount  Package / Case  4-SMD, No Lead  Size / Dimension  Height  2.5V  2.5V  2.5V  500  \$\text{4.50}\$  \$\text{50}\$  \$\	Function	-
Frequency Stability (Total)	Output	LVCMOS, LVTTL
Frequency Stability (Total)  Operating Temperature  -20°C ~ 70°C  Spread Spectrum Bandwidth  - Current - Supply (Max)  Ratings  - Mounting Type  Surface Mount  Package / Case  4-SMD, No Lead  Size / Dimension  0.106" L x 0.094" W (2.70mm x 2.40mm)  Height  - 0.031" (0.79mm)	Voltage - Supply	2.5V
Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 36mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.106" L x 0.094" W (2.70mm x 2.40mm) Height 0.031" (0.79mm)	Frequency Stability	±10ppm
Spread Spectrum Bandwidth  Current - Supply (Max)  Ratings  - Mounting Type  Surface Mount  Package / Case  4-SMD, No Lead  Size / Dimension  0.106" L x 0.094" W (2.70mm x 2.40mm)  Height  0.031" (0.79mm)	Frequency Stability (Total)	-
Current - Supply (Max)  Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.106" L x 0.094" W (2.70mm x 2.40mm) Height 0.031" (0.79mm)	Operating Temperature	-20°C ~ 70°C
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.106" L x 0.094" W (2.70mm x 2.40mm) Height 0.031" (0.79mm)	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount  Package / Case 4-SMD, No Lead Size / Dimension 0.106" L x 0.094" W (2.70mm x 2.40mm)  Height 0.031" (0.79mm)	Current - Supply (Max)	36mA
Package / Case 4-SMD, No Lead Size / Dimension 0.106" L x 0.094" W (2.70mm x 2.40mm) Height 0.031" (0.79mm)	Ratings	-
Size / Dimension       0.106" L x 0.094" W (2.70mm x 2.40mm)         Height       0.031" (0.79mm)	Mounting Type	Surface Mount
Height 0.031" (0.79mm)	Package / Case	4-SMD, No Lead
	Size / Dimension	0.106" L x 0.094" W (2.70mm x 2.40mm)
Report errors?	Height	0.031" (0.79mm)
		Report errors?

#### SIT3809AC-G-25NY Guarantees



## **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

#### SIT3809AC-G-25NY Payment Methods





















## SIT3809AC-G-25NY Shipping Methods













If you have any question about SIT3809AC-G-25NY, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com