



SIT3822AC-2C-25NZ Information



For Reference Only

Part Number SIT3822AC-2C-25NZ

Manufacturer SiTIME

Category Crystals, Oscillators, Resonators

Programmable Oscillators

Description OSC PROG LVDS 2.5V 10PPM SMD

Package 6-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SIT3822AC-2C-25NZ Specifications

Manufacturer Part Number SIT3822AC-2C-25NZ Manufacturer SiTIME Category Crystals, Oscillators, Resonators Programmable Oscillators Package 6-SMD, No Lead Series SiT3822 Type MEMS VCXO Programmable Type Programmed as Request Available Frequency Range 220MHz ~ 625MHz Function - Output LVDS Voltage - Supply 2.5V Frequency Stability ±10ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)		
Category Crystals, Oscillators, Resonators Package 6-SMD, No Lead Series SiT3822 Type MEMS VCXO Programmable Type Programmed as Request Available Frequency Range 220MHz ~ 625MHz Function - Output LVDS Voltage - Supply 2.5V Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Manufacturer Part Number	SIT3822AC-2C-25NZ
Package 6-SMD, No Lead Series SiT3822 Type MEMS VCXO Programmable Type Programmed as Request Available Frequency Range 220MHz ~ 625MHz Function - Output LVDS Voltage - Supply 2.5V Frequency Stability ±10ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Manufacturer	SiTIME
Package 6-SMD, No Lead Series SiT3822 Type MEMS VCXO Programmable Type Programmed as Request Available Frequency Range 220MHz ~ 625MHz Function - Output LVDS Voltage - Supply 2.5V Frequency Stability ±10ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Category	Crystals, Oscillators, Resonators
Series SiT3822 Type MEMS VCXO Programmable Type Programmed as Request Available Frequency Range 220MHz ~ 625MHz Function - Output LVDS Voltage - Supply 2.5V Frequency Stability ±10ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)		Programmable Oscillators
Type MEMS VCXO Programmable Type Programmed as Request Available Frequency Range 220MHz ~ 625MHz Function - Output LVDS Voltage - Supply 2.5V Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.031" (0.79mm)	Package	6-SMD, No Lead
Programmable Type Programmed as Request Available Frequency Range 220MHz ~ 625MHz Function - Cutput LVDS Voltage - Supply 2.5V Frequency Stability ±10ppm Frequency Stability (Total) - Coperating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 55mA Ratings - Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.00000000000000000000000000000000000	Series	SiT3822
Available Frequency Range Function Output LVDS Voltage - Supply 2.5V Frequency Stability Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Stability Frequency Supply Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.031" (0.79mm)	Туре	MEMS VCXO
Function - Coutput LVDS Voltage - Supply 2.5V Frequency Stability ±10ppm Frequency Stability (Total) - Coperating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 55mA Ratings - Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.031" (0.79mm)	Programmable Type	Programmed as Request
OutputLVDSVoltage - Supply2.5VFrequency Stability±10ppmFrequency Stability (Total)-Operating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)55mARatings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height0.031" (0.79mm)	Available Frequency Range	220MHz ~ 625MHz
Voltage - Supply Frequency Stability Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Statings - Mounting Type Surface Mount Package / Case Size / Dimension Height 2.5V 2.5V 5100 Supply - Supply Surface Mount 6-SMD, No Lead Size / 0.197" L x 0.126" W (5.00mm x 3.20mm) 0.031" (0.79mm)	Function	-
Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth Current - Supply (Max) Stability - Mounting Type Surface Mount Package / Case Size / Dimension Height +10ppm - -20°C ~ 70°C -20°C ~ 70°C	Output	LVDS
Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) S55mA Ratings - Mounting Type Surface Mount Package / Case Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height - Operating Temperature -20°C ~ 70°C -20°C ~ 7	Voltage - Supply	2.5V
Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) S5mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Frequency Stability	±10ppm
Spread Spectrum Bandwidth - Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Frequency Stability (Total)	-
Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Operating Temperature	-20°C ~ 70°C
Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Current - Supply (Max)	55mA
Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Ratings	-
Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Mounting Type	Surface Mount
Height 0.031" (0.79mm)	Package / Case	6-SMD, No Lead
	Size / Dimension	0.197" L x 0.126" W (5.00mm x 3.20mm)
Report errors?	Height	0.031" (0.79mm)
		Report errors?

SIT3822AC-2C-25NZ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SIT3822AC-2C-25NZ Payment Methods



















SIT3822AC-2C-25NZ Shipping Methods













If you have any question about SIT3822AC-2C-25NZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com