



SIT8008AIA3-30E Information



For Reference Only

Part Number SIT8008AIA3-30E

Manufacturer SiTIME

Category Crystals, Oscillators, Resonators

Programmable Oscillators

Description OSC PROG LVCMOS 3V EN/DS 20PPM

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SIT8008AIA3-30E Specifications

Manufacturer Part Number SIT 8008AIA3-30E Manufacturer SiTIME Category Crystals, Oscillators, Resonators Programmable Oscillators Package 4-SMD, No Lead Series SiT8008 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 110MHz Function Enable/Disable Output HCMOS, LVCMOS Voltage - Supply 3V Frequency Stability ±20ppm Frequency Stability (Total) - Operating Temperature 40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)		
Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series SiT8008 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 110MHz Function Enable/Disable Output HCMOS, LVCMOS Voltage - Supply 3V Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Manufacturer Part Number	SIT8008AIA3-30E
Package 4-SMD, No Lead Series SiT8008 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 110MHz Function Enable/Disable Output HCMOS, LVCMOS Voltage - Supply ±20ppm Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Manufacturer	SiTIME
Package 4-SMD, No Lead Series SiT8008 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 110MHz Function Enable/Disable Output HCMOS, LVCMOS Voltage - Supply 3V Frequency Stability ±20ppm Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Category	Crystals, Oscillators, Resonators
Series SiT8008 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 110MHz Function Enable/Disable Output HCMOS, LVCMOS Voltage - Supply 3V Frequency Stability ±20ppm Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)		Programmable Oscillators
Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range IMHz ~ 110MHz Function Enable/Disable Output HCMOS, LVCMOS Voltage - Supply 3V Frequency Stability Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Memounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height MEMS (Silicon) IMEMS (Silicon) Programmed as Request Silicon) Silicon) Programmed as Request Silicon) Sili	Package	4-SMD, No Lead
Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 110MHz Function Enable/Disable Output HCMOS, LVCMOS Voltage - Supply 3V Frequency Stability ±20ppm Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.00000000000000000000000000000000000	Series	SiT8008
Available Frequency Range Function Enable/Disable Output HCMOS, LVCMOS Voltage - Supply 3V Frequency Stability Frequency Stability (Total) Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension Height 1MHz ~ 110MHz Enable/Disable Enable/Disable Enable/Disable 1APC 1A	Туре	MEMS (Silicon)
Function Enable/Disable Output HCMOS, LVCMOS Voltage - Supply 3V Frequency Stability ±20ppm Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Programmable Type	Programmed as Request
Output HCMOS, LVCMOS Voltage - Supply 3V Frequency Stability ±20ppm Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.001" (0.79mm)	Available Frequency Range	1MHz ~ 110MHz
Voltage - Supply Frequency Stability Frequency Stability (Total) Operating Temperature Operating Spectrum Bandwidth - Current - Supply (Max) Atings - Mounting Type Surface Mount Package / Case Size / Dimension One of the supply (Max) Operating Temperature 3V - 4.0°C ~ 85°C - 5.00	Function	Enable/Disable
Frequency Stability (Total)	Output	HCMOS, LVCMOS
Frequency Stability (Total) Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height	Voltage - Supply	3V
Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Frequency Stability	±20ppm
Spread Spectrum Bandwidth Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Frequency Stability (Total)	-
Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Operating Temperature	-40°C ~ 85°C
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Current - Supply (Max)	4.5mA
Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Ratings	-
Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Mounting Type	Surface Mount
Height 0.031" (0.79mm)	Package / Case	4-SMD, No Lead
	Size / Dimension	0.197" L x 0.126" W (5.00mm x 3.20mm)
Report errors?	Height	0.031" (0.79mm)
		Report errors?

SIT8008AIA3-30E Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SIT8008AIA3-30E Payment Methods



















SIT8008AIA3-30E Shipping Methods













If you have any question about SIT8008AIA3-30E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com