



#### SIT8008AIR3-XXS Information



For Reference Only

Part Number SIT8008AIR3-XXS

Manufacturer SiTIME

Category Crystals, Oscillators, Resonators

**Programmable Oscillators** 

**Description** OSC PROG LVCMOS 2.25V-3.63V

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## SIT8008AIR3-XXS Specifications

Manufacturer Part Number         SIT8008AIR3-XXS           Manufacturer         SiTIME           Category         Crystals, Oscillators, Resonators           Package         4-SMD, No Lead           Series         SiT8008           Type         MEMS (Silicon)           Programmable Type         Programmed as Request           Available Frequency Range         1MHz ~ 110MHz           Function         Standby           Output         HCMOS, LVCMOS           Voltage - Supply         ±20 pm           Frequency Stability         ±20 pm           Frequency Stability (Total)         -           Operating Temperature         +40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         4.5mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.197" L x 0.126" W (5.00mm x 3.20mm)           Height         0.031" (0.79mm)		
Category         Crystals, Oscillators, Resonators           Package         4-SMD, No Lead           Series         SiT8008           Type         MEMS (Silicon)           Programmable Type         Programmed as Request           Available Frequency Range         1MHz ~ 110MHz           Function         Standby           Output         HCMOS, LVCMOS           Voltage - Supply         £25 V ~ 3.63 V           Frequency Stability (Total)         -           Operating Temperature         40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         4.5mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.197" L x 0.126" W (5.00mm x 3.20mm)           Height         0.031" (0.79mm)	Manufacturer Part Number	SIT8008AIR3-XXS
Package         4-SMD, No Lead           Series         SiT8008           Type         MEMS (Silicon)           Programmable Type         Programmed as Request           Available Frequency Range         1MHz ~ 110MHz           Function         Standby           Output         HCMOS, LVCMOS           Voltage - Supply         2.25 V ~ 3.63 V           Frequency Stability         ±20ppm           Frequency Stability (Total)         -           Operating Temperature         -40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         4.5mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.197" L x 0.126" W (5.00mm x 3.20mm)           Height         0.031" (0.79mm)	Manufacturer	SiTIME
Package         4-SMD, No Lead           Series         SiT8008           Type         MEMS (Silicon)           Programmable Type         Programmed as Request           Available Frequency Range         1MHz ~ 110MHz           Function         Standby           Output         HCMOS, LVCMOS           Voltage - Supply         2.25 V ~ 3.63 V           Frequency Stability         ±20ppm           Frequency Stability (Total)         -           Operating Temperature         -40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         4.5mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.197" L x 0.126" W (5.00mm x 3.20mm)           Height         0.031" (0.79mm)	Category	Crystals, Oscillators, Resonators
Series         SiT8008           Type         MEMS (Silicon)           Programmable Type         Programmed as Request           Available Frequency Range         1MHz ~ 110MHz           Function         Standby           Output         HCMOS, LVCMOS           Voltage - Supply         2.25 V ~ 3.63 V           Frequency Stability         ±20ppm           Frequency Stability (Total)         -           Operating Temperature         -40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         4.5mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         4-SMD, No Lead           Size / Dimension         0.197" L x 0.126" W (5.00mm x 3.20mm)           Height         0.031" (0.79mm)		Programmable Oscillators
TypeMEMS (Silicon)Programmable TypeProgrammed as RequestAvailable Frequency Range1MHz ~ 110MHzFunctionStandbyOutputHCMOS, LVCMOSVoltage - Supply2.25 V ~ 3.63 VFrequency Stability±20ppmFrequency Stability (Total)-Operating Temperature-40°C ~ 85°CSpread Spectrum Bandwidth-Current - Supply (Max)4.5mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height0.031" (0.79mm)	Package	4-SMD, No Lead
Programmable Type Programmed as Request  Available Frequency Range 1MHz ~ 110MHz  Function Standby  Output HCMOS, LVCMOS  Voltage - Supply 2.2.5 V ~ 3.63 V  Frequency Stability ±20ppm  Frequency Stability (Total) - Operating Temperature 440°C ~ 85°C  Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA  Ratings - Mounting Type Surface Mount  Package / Case 4-SMD, No Lead  Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm)  Height 10.00000000000000000000000000000000000	Series	SiT8008
Available Frequency Range Function Standby Output HCMOS, LVCMOS  Voltage - Supply 2.25 V ~ 3.63 V  Frequency Stability Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C  Spread Spectrum Bandwidth - Current - Supply (Max)  Ratings - Mounting Type Surface Mount Package / Case Size / Dimension  0.031" (0.79mm)  Height	Туре	MEMS (Silicon)
Function Standby Output HCMOS, LVCMOS Voltage - Supply 2.25 V ~ 3.63 V Frequency Stability ±20ppm Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Programmable Type	Programmed as Request
Output HCMOS, LVCMOS  Voltage - Supply 2.25 V ~ 3.63 V  Frequency Stability ±20ppm  Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C  Spread Spectrum Bandwidth - Current - Supply (Max) 4.5mA  Ratings - Mounting Type Surface Mount  Package / Case 4-SMD, No Lead  Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm)  Height 0.0031" (0.79mm)	Available Frequency Range	1MHz ~ 110MHz
Voltage - Supply  Frequency Stability  Frequency Stability (Total)  Operating Temperature  -40°C ~ 85°C  Spread Spectrum Bandwidth  - Current - Supply (Max)  Ratings  - Mounting Type  Surface Mount  Package / Case  Size / Dimension  Height  2.25 V ~ 3.63 V  2.25 ppm  4-80 pm  -  Surface Mount  -  0.197" L x 0.126" W (5.00mm x 3.20mm)  0.031" (0.79mm)	Function	Standby
Frequency Stability (Total)	Output	HCMOS, LVCMOS
Frequency Stability (Total)  Operating Temperature  -40°C ~ 85°C  Spread Spectrum Bandwidth  - Current - Supply (Max)  Ratings  - Mounting Type  Surface Mount  Package / Case  4-SMD, No Lead  Size / Dimension  0.197" L x 0.126" W (5.00mm x 3.20mm)  Height	Voltage - Supply	2.25 V ~ 3.63 V
Operating Temperature -40°C ~ 85°C  Spread Spectrum Bandwidth -  Current - Supply (Max) 4.5mA  Ratings -  Mounting Type Surface Mount  Package / Case 4-SMD, No Lead  Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm)  Height 0.031" (0.79mm)	Frequency Stability	±20ppm
Spread Spectrum Bandwidth  Current - Supply (Max)  Ratings  - Mounting Type Surface Mount  Package / Case 4-SMD, No Lead  Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm)  Height 0.031" (0.79mm)	Frequency Stability (Total)	-
Current - Supply (Max)  Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Operating Temperature	-40°C ~ 85°C
Ratings -  Mounting Type Surface Mount  Package / Case 4-SMD, No Lead  Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm)  Height 0.031" (0.79mm)	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount  Package / Case 4-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm)  Height 0.031" (0.79mm)	Current - Supply (Max)	4.5mA
Package / Case       4-SMD, No Lead         Size / Dimension       0.197" L x 0.126" W (5.00mm x 3.20mm)         Height       0.031" (0.79mm)	Ratings	-
Size / Dimension       0.197" L x 0.126" W (5.00mm x 3.20mm)         Height       0.031" (0.79mm)	Mounting Type	Surface Mount
Height 0.031" (0.79mm)	Package / Case	4-SMD, No Lead
-	Size / Dimension	0.197" L x 0.126" W (5.00mm x 3.20mm)
Report errors?	Height	0.031" (0.79mm)
		Report errors?

#### SIT8008AIR3-XXS Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **SIT8008AIR3-XXS Payment Methods**





















### SIT8008AIR3-XXS Shipping Methods













If you have any question about SIT8008AIR3-XXS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com