



SIT8008BCU1-25E Information



For Reference Only

Part Number SIT8008BCU1-25E

Manufacturer SiTIME

Category Crystals, Oscillators, Resonators

Programmable Oscillators

Description OSC PROG LVCMOS 2.5V EN/DS 20PPM

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SIT8008BCU1-25E Specifications

Manufacturer Part Number SIT8008BCU1-25E Manufacturer SiTIME Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series SiT8008B Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 110MHz Function Enable/Disable Output LVCMOS Voltage - Supply 2.5V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.2mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.031" (0.79mm)		
Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series SiT8008B Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 110MHz Function Enable/Disable Output LVCMOS Voltage - Supply 2.5V Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.2mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.031" (0.79mm)	Manufacturer Part Number	SIT8008BCU1-25E
Package 4-SMD, No Lead Series SiT8008B Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 110MHz Function Enable/Disable Output LVCMOS Voltage - Supply 2.5 V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.2mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.031" (0.79mm)	Manufacturer	SiTIME
Package 4-SMD, No Lead Series SiT8008B Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 110MHz Function Enable/Disable Output LVCMOS Voltage - Supply 2.5V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.2mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.031" (0.79mm)	Category	Crystals, Oscillators, Resonators
Series SiT8008B Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 110MHz Function Enable/Disable Output LVCMOS Voltage - Supply 2.5V Frequency Stability - Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.2mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.031" (0.79mm)		Programmable Oscillators
TypeMEMS (Silicon)Programmable TypeProgrammed as RequestAvailable Frequency Range1MHz ~ 110MHzFunctionEnable/DisableOutputLVCMOSVoltage - Supply2.5VFrequency Stability-Frequency Stability (Total)±20ppm, ±25ppm, ±50ppmOperating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)4.2mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height0.031" (0.79mm)	Package	4-SMD, No Lead
Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 110MHz Function Enable/Disable Output LVCMOS Voltage - Supply 2.5V Frequency Stability Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.2mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.00000000000000000000000000000000000	Series	SiT8008B
Available Frequency Range Function Enable/Disable Output LVCMOS Voltage - Supply 2.5V Frequency Stability Frequency Stability (Total) Operating Temperature Spread Spectrum Bandwidth - Current - Supply (Max) Ratings Auma Mounting Type Surface Mount Package / Case Size / Dimension Mounting Tomers (D.098" L x 0.079" W (2.50mm x 2.00mm) Height Enable/Disable Enable/D	Туре	MEMS (Silicon)
Function Enable/Disable Output LVCMOS Voltage - Supply 2.5V Frequency Stability Frequency Stability (Total) ±20ppm, ±25ppm, ±50ppm Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.2mA Ratings - Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.031" (0.79mm)	Programmable Type	Programmed as Request
OutputLVCMOSVoltage - Supply2.5VFrequency Stability-Frequency Stability (Total)±20ppm, ±25ppm, ±50ppmOperating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)4.2mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.098" L x 0.079" W (2.50mm x 2.00mm)Height0.031" (0.79mm)	Available Frequency Range	1MHz ~ 110MHz
Voltage - Supply Frequency Stability Frequency Stability (Total) Operating Temperature Spread Spectrum Bandwidth - Current - Supply (Max) Ratings Mounting Type Surface Mount Package / Case Size / Dimension Height 2.5V 2.5V 2.5V 2.5V 2.5V 2.5V - Supply (Max) 4.20ppm, ±25ppm, ±50ppm -20°C ~ 70°C 5.20°C ~ 70°C 5.20	Function	Enable/Disable
Frequency Stability (Total) Frequency Stability (Total) Departing Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case Size / Dimension D.031" (0.79mm) +20ppm, ±25ppm, ±50ppm -20°C ~ 70°C -20°	Output	LVCMOS
Frequency Stability (Total) ± 20 ppm, ± 25 ppm, ± 50 ppm Operating Temperature -20° C $\sim 70^{\circ}$ C Spread Spectrum Bandwidth $-$ Current - Supply (Max) 4.2 mA Ratings $-$ Mounting Type Surface Mount Package / Case $4-$ SMD, No Lead Size / Dimension 0.098° L x 0.079° W $(2.50$ mm x 2.00 mm) Height 0.031° $(0.79$ mm)	Voltage - Supply	2.5V
Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 4.2mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.031" (0.79mm)	Frequency Stability	-
Spread Spectrum Bandwidth - Current - Supply (Max) 4.2mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.031" (0.79mm)	Frequency Stability (Total)	±20ppm, ±25ppm, ±50ppm
Current - Supply (Max) 4.2mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.031" (0.79mm)	Operating Temperature	-20°C ~ 70°C
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.031" (0.79mm)	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.031" (0.79mm)	Current - Supply (Max)	4.2mA
Package / Case 4-SMD, No Lead Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.031" (0.79mm)	Ratings	-
Size / Dimension 0.098" L x 0.079" W (2.50mm x 2.00mm) Height 0.031" (0.79mm)	Mounting Type	Surface Mount
Height 0.031" (0.79mm)	Package / Case	4-SMD, No Lead
-	Size / Dimension	0.098" L x 0.079" W (2.50mm x 2.00mm)
Report errors?	Height	0.031" (0.79mm)
		Report errors?

SIT8008BCU1-25E Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SIT8008BCU1-25E Payment Methods



















SIT8008BCU1-25E Shipping Methods













If you have any question about SIT8008BCU1-25E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com