



SIT9002AC-33H18DG Information



For Reference Only

Part Number SIT9002AC-33H18DG

Manufacturer SiTIME

Category Crystals, Oscillators, Resonators

Programmable Oscillators

Description OSC PROG CML 1.8V 25PPM SMD

Package 6-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SIT9002AC-33H18DG Specifications

Manufacturer Part Number SIT9002AC-33H18DG Manufacturer SiTIME Category Crystals, Oscillators, Resonators Package 6-SMD, No Lead Series SiT9002 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 220MHz Function - Output CML Voltage - Supply 1.8V Frequency Stability ±25ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) 51mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)		
Category Crystals, Oscillators, Resonators Package 6-SMD, No Lead Series SiT9002 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 220MHz Function - Output CML Voltage - Supply 1.8V Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) 51mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Manufacturer Part Number	SIT9002AC-33H18DG
Package 6-SMD, No Lead Series SiT9002 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 220MHz Function - Output CML Voltage - Supply ± 25 ppm Frequency Stability ± 25 ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ± 1.00%, Center Spread Current - Supply (Max) 51mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Manufacturer	SiTIME
Package 6-SMD, No Lead Series SiT9002 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 220MHz Function - Output CML Voltage - Supply 1.8V Frequency Stability ±25ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) 51mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Category	Crystals, Oscillators, Resonators
Series SiT9002 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 220MHz Function - Output CML Voltage - Supply 1.8V Frequency Stability ±25ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) 51mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)		Programmable Oscillators
TypeMEMS (Silicon)Programmable TypeProgrammed as RequestAvailable Frequency Range1MHz ~ 220MHzFunction-OutputCMLVoltage - Supply1.8VFrequency Stability±25ppmFrequency Stability (Total)-Operating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth±1.00%, Center SpreadCurrent - Supply (Max)51mARatings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height0.031" (0.79mm)	Package	6-SMD, No Lead
Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 220MHz Function - CML Voltage - Supply 1.8V Frequency Stability ±25ppm Frequency Stability (Total) - COME Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) 51mA Ratings - CME Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.00000000000000000000000000000000000	Series	SiT9002
Available Frequency Range Function - Output CML Voltage - Supply 1.8V Frequency Stability Frequency Stability (Total) Operating Temperature Operating Temperature Spread Spectrum Bandwidth Lurrent - Supply (Max) Fatings Autings Function Surface Mount Package / Case Size / Dimension 1.8V - CML - CML - CML - CMC - CMC - CMC - CO°C - C	Туре	MEMS (Silicon)
Function - CML Voltage - Supply 1.8V Frequency Stability ±25ppm Frequency Stability (Total) - COMC Operating Temperature -20°C ~70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) 51mA Ratings - Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.001 CML CML CML CML CML CML CML CML	Programmable Type	Programmed as Request
OutputCMLVoltage - Supply1.8VFrequency Stability±25ppmFrequency Stability (Total)-Operating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth±1.00%, Center SpreadCurrent - Supply (Max)51mARatings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.197" L x 0.126" W (5.00mm x 3.20mm)Height0.031" (0.79mm)	Available Frequency Range	1MHz ~ 220MHz
Voltage - Supply Frequency Stability Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) 51mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension Height 1.8V - 1.8V - 2.0°C ~ 70°C -20°C ~ 7	Function	-
Frequency Stability (Total)	Output	CML
Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) S1mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height	Voltage - Supply	1.8V
Operating Temperature $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Spread Spectrum Bandwidth $\pm 1.00\%$, Center SpreadCurrent - Supply (Max) 51mA Ratings-Mounting TypeSurface MountPackage / Case 6-SMD , No LeadSize / Dimension 0.197 " L x 0.126 " W (5.00mm x 3.20mm)Height 0.031 " (0.79mm)	Frequency Stability	±25ppm
Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) 51mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Frequency Stability (Total)	-
Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Operating Temperature	-20°C ~ 70°C
Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Spread Spectrum Bandwidth	±1.00%, Center Spread
Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Current - Supply (Max)	51mA
Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Ratings	-
Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Mounting Type	Surface Mount
Height 0.031" (0.79mm)	Package / Case	6-SMD, No Lead
*	Size / Dimension	0.197" L x 0.126" W (5.00mm x 3.20mm)
Report errors?	Height	0.031" (0.79mm)
		Report errors?

SIT9002AC-33H18DG Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SIT9002AC-33H18DG Payment Methods



















SIT9002AC-33H18DG Shipping Methods













If you have any question about SIT9002AC-33H18DG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com