



SIT9002AC-38H18SG Information



For Reference Only

Part Number SIT9002AC-38H18SG

Manufacturer SiTIME

Category Crystals, Oscillators, Resonators

Programmable Oscillators

Description OSC PROG CML 1.8V STBY 25PPM SMD

Package 6-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SIT9002AC-38H18SG Specifications

Manufacturer Part Number STT9002AC-38H18SG Manufacturer SiTIME Category Crystals, Oscillators, Resonators Package 6-SMD, No Lead Series SiT9002 Type MEMS (Silicon) Programmable Type MEMS (Silicon) Available Frequency Range IMHz ~ 220MHz Function Standby Output CML Voltage - Supply 1.8V Frequency Stability ±25ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) 51mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)		
Category Crystals, Oscillators, Resonators Programmable Oscillators Package 6-SMD, No Lead Series SiT9002 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 220MHz Function Standby Output CML Voltage - Supply 1.8V Frequency Stability (Total) - COPERATION CONCEST Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) 51mA Ratings - CML Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Manufacturer Part Number	SIT9002AC-38H18SG
Package 6-SMD, No Lead Series SiT9002 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 220MHz Function Standby Output CML Voltage - Supply 1.8V Frequency Stability ±25ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) 51mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Manufacturer	SiTIME
Package 6-SMD, No Lead Series SiT9002 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 220MHz Function Standby Output CML Voltage - Supply 1.8V Frequency Stability ±25ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) 51mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Category	Crystals, Oscillators, Resonators
SeriesSiT9002TypeMEMS (Silicon)Programmable TypeProgrammed as RequestAvailable Frequency Range1MHz ~ 220MHzFunctionStandbyOutputCMLVoltage - Supply1.8VFrequency Stability±25ppmFrequency Stability (Total)-Operating Temperature-20°C ~ 70°CSpread Spectrum Bandwidth±1.00%, Center SpreadCurrent - Supply (Max)51mARatings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.276" L x 0.197" W (7.00mm x 5.00mm)Height0.039" (1.00mm)		Programmable Oscillators
Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range IMHz ~ 220MHz Function Standby Output CML Voltage - Supply 1.8V Frequency Stability ±25ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) 51mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Package	6-SMD, No Lead
Programmable Type Available Frequency Range IMHz ~ 220MHz Function Standby Output CML Voltage - Supply 1.8V Frequency Stability † ±25ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.039" (1.00mm) Programmed as Request 1MHz ~ 220MHz 1MHz ~ 220MHz 20°C ~ 70°C Strand CML **Combana **	Series	SiT9002
Available Frequency Range Function Standby Output CML Voltage - Supply 1.8V Frequency Stability +25ppm Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) S1mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height	Туре	MEMS (Silicon)
Function Standby Output CML Voltage - Supply 1.8V Frequency Stability Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) S1mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.0276" L x 0.197" W (7.00mm x 5.00mm) Height	Programmable Type	Programmed as Request
Output CML Voltage - Supply 1.8V Frequency Stability £25ppm Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth £1.00%, Center Spread Current - Supply (Max) S1mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height	Available Frequency Range	1MHz ~ 220MHz
Voltage - Supply 1.8V Frequency Stability Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) S1mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height	Function	Standby
Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth £1.00%, Center Spread Current - Supply (Max) S1mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height £25ppm - 0.039" (1.00mm)	Output	CML
Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) S1mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Voltage - Supply	1.8V
Operating Temperature $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Spread Spectrum Bandwidth $\pm 1.00\%$, Center SpreadCurrent - Supply (Max) 51mA Ratings-Mounting TypeSurface MountPackage / Case 6-SMD , No LeadSize / Dimension $0.276^{\circ}\text{L x } 0.197^{\circ}\text{W } (7.00\text{mm x } 5.00\text{mm})$ Height 0.039° (1.00mm)	Frequency Stability	±25ppm
Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) 51mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Frequency Stability (Total)	-
Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Operating Temperature	-20°C ~ 70°C
Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Spread Spectrum Bandwidth	±1.00%, Center Spread
Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Current - Supply (Max)	51mA
Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Ratings	-
Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.039" (1.00mm)	Mounting Type	Surface Mount
Height 0.039" (1.00mm)	Package / Case	6-SMD, No Lead
	Size / Dimension	0.276" L x 0.197" W (7.00mm x 5.00mm)
Report errors?	Height	0.039" (1.00mm)
		Report errors?

SIT9002AC-38H18SG Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SIT9002AC-38H18SG Payment Methods



















SIT9002AC-38H18SG Shipping Methods













If you have any question about SIT9002AC-38H18SG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com