



SIT9002AC-43N33DG Information



For Reference Only

Part Number SIT9002AC-43N33DG

Manufacturer SiTIME

Category Crystals, Oscillators, Resonators

Programmable Oscillators

Description OSC PROG HCSL 3.3V 25PPM SMD

Package 6-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SIT9002AC-43N33DG Specifications

Manufacturer SiTIME Category Crystals, Oscillators, Resonators Programmable Oscillators Package 6-SMD, No Lead Series SiT9002 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 220MHz Function - Output HCSL Voltage - Supply 3.3V Frequency Stability ±25ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) 80mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm)		
Category Crystals, Oscillators, Resonators Programmable Oscillators Package 6-SMD, No Lead Series SiT9002 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 220MHz Function - Output HCSL Voltage - Supply 3.3V Frequency Stability ±25ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) 80mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Manufacturer Part Number	SIT9002AC-43N33DG
Package 6-SMD, No Lead Series SiT9002 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 220MHz Function - Output HCSL Voltage - Supply ±25ppm Frequency Stability (Total) - Operating Temperature −20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) 80mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Manufacturer	SiTIME
Package 6-SMD, No Lead Series SiT9002 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 220MHz Function - Output HCSL Voltage - Supply 3.3V Frequency Stability ±25ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) 80mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Category	Crystals, Oscillators, Resonators
Series SiT9002 Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 220MHz Function - Output HCSL Voltage - Supply 3.3V Frequency Stability ±25ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) 80mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height		Programmable Oscillators
Type MEMS (Silicon) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 220MHz Function - Output HCSL Voltage - Supply 3.3V Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) 80mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height (MAX)	Package	6-SMD, No Lead
Programmable Type Available Frequency Range IMHz ~ 220MHz Function Output HCSL Voltage - Supply Frequency Stability Frequency Stability (Total) Operating Temperature Spread Spectrum Bandwidth Current - Supply (Max) Ratings Mounting Type Surface Mount Package / Case Size / Dimension Height Programmed as Request IMHz ~ 220MHz Programmed as Request IMHz ~ 220MHz Frequency Curent - 20°C ~ 70°C Por C Spread - 20°C ~ 70°C Spread Surface Mount - 20°C ~ 70°C Spread - 20°C ~ 70°	Series	SiT9002
Available Frequency Range IMHz ~ 220MHz Function Output HCSL Voltage - Supply 3.3V Frequency Stability Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.031" (0.79mm)	Type	MEMS (Silicon)
Function - Coutput HCSL Voltage - Supply 3.3V Frequency Stability ±25ppm Frequency Stability (Total) - Coperating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) 80mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.001" (0.79mm)	Programmable Type	Programmed as Request
Output HCSL Voltage - Supply 3.3V Frequency Stability ±25ppm Frequency Stability (Total) - Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) 80mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Available Frequency Range	1MHz ~ 220MHz
Voltage - Supply Frequency Stability Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) 80mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.031" (0.79mm)	Function	-
Frequency Stability (Total) Operating Temperature Spread Spectrum Bandwidth Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case Size / Dimension Height +25ppm - -20°C ~ 70°C -	Output	HCSL
Frequency Stability (Total) Operating Temperature -20°C ~ 70°C Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) 80mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Voltage - Supply	3.3V
Operating Temperature $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Spread Spectrum Bandwidth $\pm 1.00\%$, Center Spread Current - Supply (Max) 80mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Frequency Stability	±25ppm
Spread Spectrum Bandwidth ±1.00%, Center Spread Current - Supply (Max) 80mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Frequency Stability (Total)	-
Current - Supply (Max) 80mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Operating Temperature	-20°C ~ 70°C
Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Spread Spectrum Bandwidth	±1.00%, Center Spread
Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Current - Supply (Max)	80mA
Package / Case 6-SMD, No Lead Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Ratings	-
Size / Dimension 0.197" L x 0.126" W (5.00mm x 3.20mm) Height 0.031" (0.79mm)	Mounting Type	Surface Mount
Height 0.031" (0.79mm)	Package / Case	6-SMD, No Lead
	Size / Dimension	0.197" L x 0.126" W (5.00mm x 3.20mm)
Report errors?	Height	0.031" (0.79mm)
		Report errors?

SIT9002AC-43N33DG Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SIT9002AC-43N33DG Payment Methods



















SIT9002AC-43N33DG Shipping Methods













If you have any question about SIT9002AC-43N33DG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com