



SJT00RT-16-8SA Information

Heisener.com

Part Number SJT00RT-16-8SA

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 8POS WALL MNT SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SJT00RT-16-8SA Specifications

Manufacturer Part NumberSJT00RT-16-8SAManufacturerAmphenol Aerospace OperationsCategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesMIL-DTL-38999 I & III, VG 96912, SJTConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert16-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationAIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-Report errors?		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Receptacle, Female Sockets Number of Positions 8 Shell Size - Insert 16-8 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Manufacturer Part Number	SJT00RT-16-8SA
Circular Connectors Package - Series MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Receptacle, Female Sockets Number of Positions 8 Shell Size - Insert 16-8 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Manufacturer	Amphenol Aerospace Operations
Package - MIL-DTL-38999 1 & III, VG 96912, SJT Connector Type Receptacle, Female Sockets Number of Positions 8 Shell Size - Insert 16-8 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Woltage - Rated 900VAC, 1250VDC Current Rating -	Category	Connectors, Interconnects
Series MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Receptacle, Female Sockets Number of Positions 8 Shell Size - Insert 16-8 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Voltage - Rated 900VAC, 1250VDC Current Rating		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert16-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationAIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Package	-
Number of Positions Shell Size - Insert 16-8 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Features Voltage - Rated 900VAC, 1250VDC Current Rating	Series	MIL-DTL-38999 I & III, VG 96912, SJT
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Voltage - Rated 900VAC, 1250VDC Current Rating -	Number of Positions	8
Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating	Shell Size - Insert	16-8
Termination Crimp Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Mounting Type	Panel Mount, Flange
Orientation A Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Termination	Crimp
Ingress Protection Shell Material, Finish Contact Finish Features Voltage - Rated Current Rating Environment Resistant Aluminum, Cadmium over Nickel Plated Gold - Voltage - Rated 900VAC, 1250VDC -	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Voltage - Rated Current Rating Aluminum, Cadmium over Nickel Plated Gold - Current Rating	Orientation	A
Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Ingress Protection	Environment Resistant
Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Material, Finish	Aluminum, Cadmium over Nickel Plated
Voltage - Rated 900VAC, 1250VDC Current Rating -	Contact Finish	Gold
Current Rating -	Features	-
·	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	-
		Report errors?

SJT00RT-16-8SA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SJT00RT-16-8SA Payment Methods



















SJT00RT-16-8SA Shipping Methods













If you have any question about SJT00RT-16-8SA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com