



SJT00RT-24-35S Information

Heisener.com

Part Number SJT00RT-24-35S

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 128POS WALL MNT SCKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SJT00RT-24-35S Specifications

Manufacturer Part Number SJT00RT-24-35S Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Receptacle, Female Sockets Number of Positions 128 Shell Size - Insert 24-35 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating - Report errors?		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Receptacle, Female Sockets Number of Positions 128 Shell Size - Insert 24-35 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Manufacturer Part Number	SJT00RT-24-35S
Package-SeriesMIL-DTL-38999 I & III, VG 96912, SJTConnector TypeReceptacle, Female SocketsNumber of Positions128Shell Size - Insert24-35Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 550VDCCurrent Rating-	Manufacturer	Amphenol Aerospace Operations
Package - MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Receptacle, Female Sockets Number of Positions 128 Shell Size - Insert 24-35 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Woltage - Rated 400VAC, 550VDC Current Rating	Category	Connectors, Interconnects
Series MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Receptacle, Female Sockets Number of Positions 128 Shell Size - Insert 24-35 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Voltage - Rated 400VAC, 550VDC Current Rating		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions128Shell Size - Insert24-35Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 550VDCCurrent Rating-	Package	-
Number of Positions128Shell Size - Insert24-35Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 550VDCCurrent Rating-	Series	MIL-DTL-38999 I & III, VG 96912, SJT
Shell Size - Insert 24-35 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Number of Positions	128
Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Shell Size - Insert	24-35
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Termination	Crimp
Ingress Protection Environment Resistant Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated Current Rating Environment Resistant Aluminum, Cadmium over Nickel Plated Gold -	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Cadmium over Nickel Plated Gold - - - - - - - - - - - - -	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Ingress Protection	Environment Resistant
Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Shell Material, Finish	Aluminum, Cadmium over Nickel Plated
Voltage - Rated 400VAC, 550VDC Current Rating -	Contact Finish	Gold
Current Rating -	Features	-
-	Voltage - Rated	400VAC, 550VDC
Report errors?	Current Rating	-
		Report errors?

SJT00RT-24-35S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SJT00RT-24-35S Payment Methods





















SJT00RT-24-35S Shipping Methods













If you have any question about SJT00RT-24-35S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com