



## SJT06RT-10-13S Information

Heisener.com

Part Number SJT06RT-10-13S

Manufacturer Amphenol Aerospace Operations

**Category** Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 13POS STRAIGHT SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# SJT06RT-10-13S Specifications

Manufacturer Part Number     SJT06RT-10-13S       Manufacturer     Amphenol Aerospace Operations       Category     Connectors, Interconnects       Package     -       Series     MIL-DTL-38999 I & III, VG 96912, SJT       Connector Type     Plug, Female Sockets       Number of Positions     13       Shell Size - Insert     10-13       Shell Size, MIL     -       Mounting Type     Free Hanging (In-Line)       Termination     Crimp       Fastening Type     Bayonet Lock       Orientation     N (Normal)       Ingress Protection     Environment Resistant       Shell Material, Finish     Aluminum, Cadmium over Nickel Plated       Contact Finish     Gold       Features     -       Voltage - Rated     400VAC, 550VDC       Current Rating     -       Report errors?		
Category Connectors, Interconnects Circular Connectors  Package - Series MIL-DTL-38999 I & III, VG 96912, SJT  Connector Type Plug, Female Sockets Number of Positions 13 Shell Size - Insert 10-13 Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Manufacturer Part Number	SJT06RT-10-13S
Package-SeriesMIL-DTL-38999 I & III, VG 96912, SJTConnector TypePlug, Female SocketsNumber of Positions13Shell Size - Insert10-13Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 550VDCCurrent Rating-	Manufacturer	Amphenol Aerospace Operations
Package - MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Plug, Female Sockets Number of Positions 13 Shell Size - Insert 10-13 Shell Size, MIL - Connector Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Contact Finish Gold Features - Contact Finish Gold Current Rating - Contact Finish - Contact Finish Gold Current Rating - Contact Finish Gold	Category	Connectors, Interconnects
Series MIL-DTL-38999 I & III, VG 96912, SJT  Connector Type Plug, Female Sockets  Number of Positions 13  Shell Size - Insert 10-13  Shell Size, MIL		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions13Shell Size - Insert10-13Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 550VDCCurrent Rating-	Package	-
Number of Positions  Shell Size - Insert  10-13  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Crimp  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Cadmium over Nickel Plated  Contact Finish  Gold  Features  -  Voltage - Rated  400VAC, 550VDC  Current Rating  -	Series	MIL-DTL-38999 I & III, VG 96912, SJT
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated  Contact Finish Features - Voltage - Rated A00VAC, 550VDC  Current Rating -	Number of Positions	13
Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold  Features - Voltage - Rated 400VAC, 550VDC  Current Rating -	Shell Size - Insert	10-13
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Shell Size, MIL	-
Fastening Type  Bayonet Lock Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Cadmium over Nickel Plated  Contact Finish  Gold  Features  -  Voltage - Rated  400VAC, 550VDC  Current Rating  -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Termination	Crimp
Ingress Protection  Environment Resistant  Aluminum, Cadmium over Nickel Plated  Contact Finish  Gold  Features  - Voltage - Rated  Current Rating  Environment Resistant  Aluminum, Cadmium over Nickel Plated  Gold  -	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  - Voltage - Rated  Current Rating  Aluminum, Cadmium over Nickel Plated  Gold  -  -  -  -  -  -  -  -  -  -  -  -  -	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Ingress Protection	Environment Resistant
Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Shell Material, Finish	Aluminum, Cadmium over Nickel Plated
Voltage - Rated 400VAC, 550VDC  Current Rating -	Contact Finish	Gold
Current Rating -	Features	-
-	Voltage - Rated	400VAC, 550VDC
Report errors?	Current Rating	-
		Report errors?

### SJT06RT-10-13S Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## SJT06RT-10-13S Payment Methods



















# SJT06RT-10-13S Shipping Methods













If you have any question about SJT06RT-10-13S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com