



SJT06RT-16-35S Information

Heisener.com

Part Number SJT06RT-16-35S

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 55POS STRAIGHT SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SJT06RT-16-35S Specifications

| Manufacturer Part Number SJT06RT-16-35S Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Plug, Female Sockets Number of Positions 55 Shell Size - Insert 16-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating - Report errors? | | |
|--|--------------------------|--------------------------------------|
| Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Plug, Female Sockets Number of Positions 55 Shell Size - Insert 16-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating - | Manufacturer Part Number | SJT06RT-16-35S |
| Package-SeriesMIL-DTL-38999 I & III, VG 96912, SJTConnector TypePlug, Female SocketsNumber of Positions55Shell Size - Insert16-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 550VDCCurrent Rating- | Manufacturer | Amphenol Aerospace Operations |
| Package - MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Plug, Female Sockets Number of Positions 55 Shell Size - Insert 16-35 Shell Size, MIL - Comment Type Free Hanging (In-Line) Termination Crimp Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Comment Retire Advocated | Category | Connectors, Interconnects |
| Series MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Plug, Female Sockets Number of Positions 55 Shell Size - Insert 16-35 Shell Size, MIL | | Circular Connectors |
| Connector TypePlug, Female SocketsNumber of Positions55Shell Size - Insert16-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 550VDCCurrent Rating- | Package | - |
| Number of Positions Shell Size - Insert 16-35 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating - | Series | MIL-DTL-38999 I & III, VG 96912, SJT |
| Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating - | Connector Type | Plug, Female Sockets |
| Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Features - Voltage - Rated A00VAC, 550VDC Current Rating - | Number of Positions | 55 |
| Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating - | Shell Size - Insert | 16-35 |
| Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating - | Shell Size, MIL | - |
| Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating - | Mounting Type | Free Hanging (In-Line) |
| Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating - | Termination | Crimp |
| Ingress Protection Environment Resistant Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated Current Rating Environment Resistant Aluminum, Cadmium over Nickel Plated Gold - | Fastening Type | Bayonet Lock |
| Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Cadmium over Nickel Plated Gold - - - - - - - - - - - - - | Orientation | N (Normal) |
| Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating - | Ingress Protection | Environment Resistant |
| Features - Voltage - Rated 400VAC, 550VDC Current Rating - | Shell Material, Finish | Aluminum, Cadmium over Nickel Plated |
| Voltage - Rated 400VAC, 550VDC Current Rating - | Contact Finish | Gold |
| Current Rating - | Features | - |
| - | Voltage - Rated | 400VAC, 550VDC |
| Report errors? | Current Rating | - |
| | | Report errors? |

SJT06RT-16-35S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SJT06RT-16-35S Payment Methods



















SJT06RT-16-35S Shipping Methods













If you have any question about SJT06RT-16-35S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com