



SJT06RT-16-42S(023) Information

Heisener.com

Part Number SJT06RT-16-42S(023)

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 42POS STRAIGHT SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SJT06RT-16-42S(023) Specifications

Manufacturer Part NumberSJT06RT-16-42S(023)ManufacturerAmphenol Aerospace OperationsCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-38999 I & III, VG 96912, SJTConnector TypePlug, Female SocketsNumber of Positions42Shell Size - Insert16-42Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated400VAC, 550VDCCurrent Rating-Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-38999 I & III, VG 96912, SJTConnector TypePlug, Female SocketsNumber of Positions42Shell Size - Insert16-42Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated400VAC, 550VDCCurrent Rating-	Manufacturer Part Number	SJT06RT-16-42S(023)
Package-SeriesMIL-DTL-38999 I & III, VG 96912, SJTConnector TypePlug, Female SocketsNumber of Positions42Shell Size - Insert16-42Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated400VAC, 550VDCCurrent Rating-	Manufacturer	Amphenol Aerospace Operations
Package - MIL-DTL-38999 1 & III, VG 96912, SJT Connector Type Plug, Female Sockets Number of Positions 42 Shell Size - Insert 16-42 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Current Rating - MIL-DTL-38999 1 & III, VG 96912, SJT MIL-DTL-38999 1 & III, VG 96912, SJT 42 Let The Sockets Let The Sockets Let The Sockets Let The Sockets MIL-DTL-38999 1 & III, VG 96912, SJT Let The Sockets Let The Sockets Let The Sockets Let The Sockets MIL-DTL-38999 1 & III, VG 96912, SJT Let The Sockets Let The Sockets Let The Sockets Let The Sockets MIL-DTL-38999 1 & III, VG 96912, SJT Let The Sockets Let The So	Category	Connectors, Interconnects
Series MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Plug, Female Sockets Number of Positions 42 Shell Size - Insert 16-42 Shell Size, MIL		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions42Shell Size - Insert16-42Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated400VAC, 550VDCCurrent Rating-	Package	-
Number of Positions Shell Size - Insert 16-42 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Voltage - Rated 400VAC, 550VDC Current Rating -	Series	MIL-DTL-38999 I & III, VG 96912, SJT
Shell Size - Insert16-42Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated400VAC, 550VDCCurrent Rating-	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Number of Positions	42
Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Shell Size - Insert	16-42
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Nickel Plated, Electroless Gold - - - - - - - - - - - - -	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Ingress Protection	Environment Resistant
Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Shell Material, Finish	Aluminum, Nickel Plated, Electroless
Voltage - Rated 400VAC, 550VDC Current Rating -	Contact Finish	Gold
Current Rating -	Features	-
	Voltage - Rated	400VAC, 550VDC
Report errors?	Current Rating	-
		Report errors?

SJT06RT-16-42S(023) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SJT06RT-16-42S(023) Payment Methods



















SJT06RT-16-42S(023) Shipping Methods













If you have any question about SJT06RT-16-42S(023), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com