



Heisener.com

### SJT07RT-12-35P(014) Information

Part Number SJT07RT-12-35P(014)

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 22POS JAM NUT PINS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## SJT07RT-12-35P(014) Specifications

Manufacturer Part Number       SJT07RT-12-35P(014)         Manufacturer       Amphenol Aerospace Operations         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-38999 I & III, VG 96912, SJT         Connector Type       Receptacle, Male Pins         Number of Positions       22         Shell Size - Insert       12-35         Shell Size, MIL       -         Mounting Type       Panel Mount, Bulkhead - Front Side Nut         Termination       Crimp         Fastening Type       Bayonet Lock         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum, Olive Drab Cadmium Plated         Contact Finish       Gold         Features       -         Voltage - Rated       400VAC, 550VDC         Current Rating       Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-38999 I & III, VG 96912, SJTConnector TypeReceptacle, Male PinsNumber of Positions22Shell Size - Insert12-35Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 550VDCCurrent Rating-	Manufacturer Part Number	SJT07RT-12-35P(014)
Package-SeriesMIL-DTL-38999 I & III, VG 96912, SJTConnector TypeReceptacle, Male PinsNumber of Positions22Shell Size - Insert12-35Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 550VDCCurrent Rating-	Manufacturer	Amphenol Aerospace Operations
Package - MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Receptacle, Male Pins Number of Positions 22 Shell Size - Insert 12-35 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating	Category	Connectors, Interconnects
Series MIL-DTL-38999 I & III, VG 96912, SJT  Connector Type Receptacle, Male Pins  Number of Positions 22  Shell Size - Insert 12-35  Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions22Shell Size - Insert12-35Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 550VDCCurrent Rating-	Package	-
Number of Positions  Shell Size - Insert  12-35  Shell Size, MIL  Mounting Type  Panel Mount, Bulkhead - Front Side Nut  Termination  Crimp  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum, Olive Drab Cadmium Plated  Contact Finish  Gold  Features  -  Voltage - Rated  400VAC, 550VDC  Current Rating  -	Series	MIL-DTL-38999 I & III, VG 96912, SJT
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Bulkhead - Front Side Nut  Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Number of Positions	22
Mounting Type Panel Mount, Bulkhead - Front Side Nut  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold  Features - Voltage - Rated 400VAC, 550VDC  Current Rating -	Shell Size - Insert	12-35
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Olive Drab Cadmium Plated  Contact Finish  Gold  Features  -  Voltage - Rated  400VAC, 550VDC  Current Rating  -	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Termination	Crimp
Ingress Protection  Environment Resistant  Aluminum, Olive Drab Cadmium Plated  Contact Finish  Gold  Features  - Voltage - Rated  Current Rating  Environment Resistant  Aluminum, Olive Drab Cadmium Plated  Gold	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  - Voltage - Rated  Current Rating  Aluminum, Olive Drab Cadmium Plated  Gold  -  -  -  -  -  -  -  -  -  -  -  -  -	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Ingress Protection	Environment Resistant
Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 400VAC, 550VDC  Current Rating -	Contact Finish	Gold
Current Rating -	Features	-
•	Voltage - Rated	400VAC, 550VDC
Report errors?	Current Rating	-
Report circles.		Report errors?

## SJT07RT-12-35P(014) Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### SJT07RT-12-35P(014) Payment Methods



















## SJT07RT-12-35P(014) Shipping Methods













If you have any question about SJT07RT-12-35P(014), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com