



## SJT07RT-14-97S Information

Heisener.com

Part Number SJT07RT-14-97S

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 12POS JAM NUT SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## SJT07RT-14-97S Specifications

Manufacturer Part NumberSJT07RT-14-97SManufacturerAmphenol Aerospace OperationsCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-38999 I & III, VG 96912, SJTConnector TypeReceptacle, Female SocketsNumber of Positions12Shell Size - Insert14-97Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating-Report errors?		
Category Connectors, Interconnects Circular Connectors  Package - Series MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Receptacle, Female Sockets Number of Positions 12 Shell Size - Insert 14-97 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Benvironment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating -	Manufacturer Part Number	SJT07RT-14-97S
Package-SeriesMIL-DTL-38999 I & III, VG 96912, SJTConnector TypeReceptacle, Female SocketsNumber of Positions12Shell Size - Insert14-97Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating-	Manufacturer	Amphenol Aerospace Operations
Package-SeriesMIL-DTL-38999 I & III, VG 96912, SJTConnector TypeReceptacle, Female SocketsNumber of Positions12Shell Size - Insert14-97Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated600 VAC, 850 VDCCurrent Rating-	Category	Connectors, Interconnects
Series MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Receptacle, Female Sockets Number of Positions 12 Shell Size - Insert 14-97 Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions12Shell Size - Insert14-97Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating-	Package	-
Number of Positions12Shell Size - Insert14-97Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated600VAC, 850VDCCurrent Rating-	Series	MIL-DTL-38999 I & III, VG 96912, SJT
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating -	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Bulkhead - Front Side Nut  Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Features - Voltage - Rated 600VAC, 850VDC Current Rating -	Number of Positions	12
Mounting Type Panel Mount, Bulkhead - Front Side Nut  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating -	Shell Size - Insert	14-97
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating -	Shell Size, MIL	-
Fastening Type  Bayonet Lock Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Cadmium over Nickel Plated  Contact Finish  Gold  Features  -  Voltage - Rated  600VAC, 850VDC  Current Rating  -	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating -	Termination	Crimp
Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Cadmium over Nickel Plated  Contact Finish Gold  Features -  Voltage - Rated 600VAC, 850VDC  Current Rating -	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  - Voltage - Rated  Current Rating  Aluminum, Cadmium over Nickel Plated  Gold  -  Current Rating	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC, 850VDC Current Rating -	Ingress Protection	Environment Resistant
Features - Voltage - Rated 600VAC, 850VDC Current Rating -	Shell Material, Finish	Aluminum, Cadmium over Nickel Plated
Voltage - Rated 600VAC, 850VDC  Current Rating -	Contact Finish	Gold
Current Rating -	Features	-
	Voltage - Rated	600VAC, 850VDC
Report errors?	Current Rating	-
		Report errors?

### SJT07RT-14-97S Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **SJT07RT-14-97S Payment Methods**





















### SJT07RT-14-97S Shipping Methods













If you have any question about SJT07RT-14-97S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com