



SJT07RT-20-75P Information

Heisener.com

Part Number SJT07RT-20-75P

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 4POS JAM NUT PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SJT07RT-20-75P Specifications

| Manufacturer Part NumberSJTO7RT-20-75PManufacturerAmphenol Aerospace OperationsCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-38999 I & III, VG 96912, SJTConnector TypeReceptacle, Male PinsNumber of Positions4Shell Size - Insert20-75Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 550VDC | | |
|--|--------------------------|--|
| Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Receptacle, Male Pins Number of Positions 4 Shell Size - Insert 20-75 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated Connectors, Interconnects Circular Connectors AllII, VG 96912, SJT Entity, VG 96912, SJT AllII, VG 96912, SJT AllIII, VG 96912, SJT AllIII, VG 96912, SJT AllIII, VG 96912, SJT Entity, VG 96912, SJT AllIII, VG 96912, SJT AllIIII, VG 96912, SJT AllIII, VG 96912, SJT AllIII, VG 96912, SJ | Manufacturer Part Number | SJT07RT-20-75P |
| Package-SeriesMIL-DTL-38999 I & III, VG 96912, SJTConnector TypeReceptacle, Male PinsNumber of Positions4Shell Size - Insert20-75Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 550VDC | Manufacturer | Amphenol Aerospace Operations |
| Package - Series MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Receptacle, Male Pins Number of Positions 4 Shell Size - Insert 20-75 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC | Category | Connectors, Interconnects |
| Series MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Receptacle, Male Pins Number of Positions 4 Shell Size - Insert 20-75 Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Voltage - Rated 400VAC, 550VDC | | Circular Connectors |
| Connector Type Receptacle, Male Pins Number of Positions 4 Shell Size - Insert 20-75 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Voltage - Rated 400VAC, 550VDC | Package | - |
| Number of Positions4Shell Size - Insert20-75Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 550VDC | Series | MIL-DTL-38999 I & III, VG 96912, SJT |
| Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Voltage - Rated 20-75 Annual Sulkhead - Front Side Nut Crimp Bayonet Lock N (Normal) Aluminum (Normal) Aluminum (Normal) Gold Features - Voltage - Rated | Connector Type | Receptacle, Male Pins |
| Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC | Number of Positions | 4 |
| Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 550VDC | Shell Size - Insert | 20-75 |
| Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC | Shell Size, MIL | - |
| Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC | Mounting Type | Panel Mount, Bulkhead - Front Side Nut |
| Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC | Termination | Crimp |
| Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC | Fastening Type | Bayonet Lock |
| Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Aluminum, Cadmium over Nickel Plated Gold 400VAC, 550VDC | Orientation | N (Normal) |
| Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC | Ingress Protection | Environment Resistant |
| Features - Voltage - Rated 400VAC, 550VDC | Shell Material, Finish | Aluminum, Cadmium over Nickel Plated |
| Voltage - Rated 400VAC, 550VDC | Contact Finish | Gold |
| | Features | - |
| | Voltage - Rated | 400VAC, 550VDC |
| Current Rating - | Current Rating | - |
| Report errors? | | Report errors? |

SJT07RT-20-75P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SJT07RT-20-75P Payment Methods



















SJT07RT-20-75P Shipping Methods













If you have any question about SJT07RT-20-75P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com