



### SJTG06RT-16-26P Information

Heisener.com

Part Number SJTG06RT-16-26P

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 26POS STRAIGHT PINS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **SJTG06RT-16-26P Specifications**

Manufacturer Part Number     SJTG06RT-16-26P       Manufacturer     Amphenol Aerospace Operations       Category     Connectors, Interconnects       Circular Connectors       Package     -       Series     MIL-DTL-38999 I & III, VG 96912, SJT       Connector Type     Plug, Male Pins       Number of Positions     26       Shell Size - Insert     16-26       Shell Size, MIL     -       Mounting Type     Free Hanging (In-Line)       Termination     Crimp       Fastening Type     Bayonet Lock       Orientation     N (Normal)       Ingress Protection     Environment Resistant       Shell Material, Finish     Aluminum, Cadmium over Nickel Plated       Contact Finish     Gold       Features     Shielded       Voltage - Rated     600VAC, 850VDC       Current Rating     -       Report errors?		
Category Connectors, Interconnects Circular Connectors  Package - Series MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Plug, Male Pins Number of Positions 26 Shell Size - Insert 16-26 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated Courrent Rating - Connectors, Interconnects Circular Connectors MIL-DTL-38999 I & III, VG 96912, SJT  Plug, Male Pins Plug, Mal	Manufacturer Part Number	SJTG06RT-16-26P
Package-SeriesMIL-DTL-38999 I & III, VG 96912, SJTConnector TypePlug, Male PinsNumber of Positions26Shell Size - Insert16-26Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated600VAC, 850VDCCurrent Rating-	Manufacturer	Amphenol Aerospace Operations
Package - MIL-DTL-389991 & III, VG 96912, SJT Connector Type Plug, Male Pins Number of Positions 26 Shell Size - Insert 16-26 Shell Size, MIL - Tremination Crimp Fastening Type Free Hanging (In-Line) Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC Current Rating	Category	Connectors, Interconnects
Series MIL-DTL-38999 I & III, VG 96912, SJT  Connector Type Plug, Male Pins  Number of Positions 26  Shell Size - Insert 16-26  Shell Size, MIL		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions26Shell Size - Insert16-26Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated600VAC, 850VDCCurrent Rating-	Package	-
Number of Positions  Shell Size - Insert  16-26  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Crimp  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Cadmium over Nickel Plated  Contact Finish  Gold  Features  Shielded  Voltage - Rated  600VAC, 850VDC  Current Rating  -	Series	MIL-DTL-38999 I & III, VG 96912, SJT
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC Current Rating -	Connector Type	Plug, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated  Contact Finish Features Shielded  Voltage - Rated Current Rating	Number of Positions	26
Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Cadmium over Nickel Plated  Contact Finish Gold  Features Shielded  Voltage - Rated 600VAC, 850VDC  Current Rating -	Shell Size - Insert	16-26
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC Current Rating -	Shell Size, MIL	-
Fastening Type  Bayonet Lock Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Cadmium over Nickel Plated  Contact Finish  Gold  Features  Shielded  Voltage - Rated  600VAC, 850VDC  Current Rating  -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC Current Rating -	Termination	Crimp
Ingress Protection  Environment Resistant  Aluminum, Cadmium over Nickel Plated  Contact Finish  Gold  Features  Shielded  Voltage - Rated  Current Rating	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  Shielded  Voltage - Rated  Current Rating  Aluminum, Cadmium over Nickel Plated  Gold  Shielded	Orientation	N (Normal)
Contact Finish Gold Features Shielded Voltage - Rated 600VAC, 850VDC Current Rating -	Ingress Protection	Environment Resistant
Features Shielded  Voltage - Rated 600VAC, 850VDC  Current Rating -	Shell Material, Finish	Aluminum, Cadmium over Nickel Plated
Voltage - Rated 600VAC, 850VDC  Current Rating -	Contact Finish	Gold
Current Rating -	Features	Shielded
-	Voltage - Rated	600VAC, 850VDC
Report errors?	Current Rating	-
		Report errors?

#### SJTG06RT-16-26P Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### SJTG06RT-16-26P Payment Methods



















## SJTG06RT-16-26P Shipping Methods













If you have any question about SJTG06RT-16-26P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com