



SJTG06RT-24-35SC Information

Heisener.com

Part Number SJTG06RT-24-35SC

Manufacturer Amphenol Aerospace Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 128POS STRAIGHT SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SJTG06RT-24-35SC Specifications

Manufacturer Part Number SJTG06RT-24-35SC Manufacturer Amphenol Aerospace Operations Category Connectors, Interconnects Package - Series MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Plug, Female Sockets Number of Positions 128 Shell Size - Insert 24-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 550VDC Current Rating - Report errors?		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Plug, Female Sockets Number of Positions 128 Shell Size - Insert 24-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Voltage - Rated Voltage - Rated Current Rating Connectors, Interconnects Circular Connectors MIL-DTL-38999 I & III, VG 96912, SJT Full, VG 96912, SJT Connector Type Plug, Female Sockets MIL-DTL-38999 I & III, VG 96912, SJT Environment Sockets Aluminum (In-Line) Corientation Corientation Collage - Rated 400VAC, 550VDC Current Rating	Manufacturer Part Number	SJTG06RT-24-35SC
Package-SeriesMIL-DTL-38999 I & III, VG 96912, SJTConnector TypePlug, Female SocketsNumber of Positions128Shell Size - Insert24-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationCIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated400VAC, 550VDCCurrent Rating-	Manufacturer	Amphenol Aerospace Operations
Package - MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Plug, Female Sockets Number of Positions 128 Shell Size - Insert 24-35 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 550VDC Current Rating -	Category	Connectors, Interconnects
Series MIL-DTL-38999 I & III, VG 96912, SJT Connector Type Plug, Female Sockets Number of Positions 128 Shell Size - Insert 24-35 Shell Size, MIL		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions128Shell Size - Insert24-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationCIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated400VAC, 550VDCCurrent Rating-	Package	-
Number of Positions128Shell Size - Insert24-35Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationCIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated400VAC, 550VDCCurrent Rating-	Series	MIL-DTL-38999 I & III, VG 96912, SJT
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 550VDC Current Rating -	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Features Shielded Voltage - Rated 400VAC, 550VDC Current Rating	Number of Positions	128
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationCIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Cadmium over Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated400VAC, 550VDCCurrent Rating-	Shell Size - Insert	24-35
Termination Crimp Fastening Type Bayonet Lock Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 550VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 550VDC Current Rating	Mounting Type	Free Hanging (In-Line)
Orientation C Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 550VDC Current Rating -	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Cadmium over Nickel Plated Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 550VDC Current Rating	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating	Orientation	С
Contact Finish Gold Features Shielded Voltage - Rated 400VAC, 550VDC Current Rating -	Ingress Protection	Environment Resistant
Features Shielded Voltage - Rated 400VAC, 550VDC Current Rating -	Shell Material, Finish	Aluminum, Cadmium over Nickel Plated
Voltage - Rated 400VAC, 550VDC Current Rating -	Contact Finish	Gold
Current Rating -	Features	Shielded
	Voltage - Rated	400VAC, 550VDC
Report errors?	Current Rating	-
		Report errors?

SJTG06RT-24-35SC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SJTG06RT-24-35SC Payment Methods



















SJTG06RT-24-35SC Shipping Methods













If you have any question about SJTG06RT-24-35SC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com