



Heisener.com

# SJTP00RT-24-35S(014) Information

Part Number SJTP00RT-24-35S(014)

Manufacturer Amphenol Aerospace Operations

Connectors, Interconnects Category

**Circular Connectors** 

CONN RCPT 128POS WALL MNT SCKT **Description** 

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# SJTP00RT-24-35S(014) Specifications

Manufacturer Part Number       SJTP00RT-24-35S(014)         Manufacturer       Amphenol Aerospace Operations         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-38999 I & III, VG 96912, SJT         Connector Type       Receptacle, Female Sockets         Number of Positions       128         Shell Size - Insert       24-35         Shell Size, MIL       -         Mounting Type       Panel Mount, Flange         Termination       Crimp         Fastening Type       Bayonet Lock         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum, Olive Drab Cadmium Plated         Contact Finish       Gold         Features       -         Voltage - Rated       400VAC, 550VDC         Current Rating       Panent arrors 2		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-38999 I & III, VG 96912, SJTConnector TypeReceptacle, Female SocketsNumber of Positions128Shell Size - Insert24-35Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 550VDCCurrent Rating-	Manufacturer Part Number	SJTP00RT-24-35S(014)
Package-SeriesMIL-DTL-38999 I & III, VG 96912, SJTConnector TypeReceptacle, Female SocketsNumber of Positions128Shell Size - Insert24-35Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 550VDCCurrent Rating-	Manufacturer	Amphenol Aerospace Operations
Package-SeriesMIL-DTL-38999 I & III, VG 96912, SJTConnector TypeReceptacle, Female SocketsNumber of Positions128Shell Size - Insert24-35Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated400 VAC, 550 VDCCurrent Rating-	Category	Connectors, Interconnects
Series MIL-DTL-38999 I & III, VG 96912, SJT  Connector Type Receptacle, Female Sockets  Number of Positions 128  Shell Size - Insert 24-35  Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Gold  Features  Voltage - Rated 400VAC, 550VDC  Current Rating		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions128Shell Size - Insert24-35Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 550VDCCurrent Rating-	Package	-
Number of Positions128Shell Size - Insert24-35Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 550VDCCurrent Rating-	Series	MIL-DTL-38999 I & III, VG 96912, SJT
Shell Size - Insert 24-35 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Features - Voltage - Rated 400VAC, 550VDC  Current Rating -	Number of Positions	128
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated400VAC, 550VDCCurrent Rating-	Shell Size - Insert	24-35
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Olive Drab Cadmium Plated  Contact Finish  Gold  Features  -  Voltage - Rated  400VAC, 550VDC  Current Rating  -	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  - Voltage - Rated  Current Rating  Aluminum, Olive Drab Cadmium Plated  Gold  -  -  -  -  -  -  -  -  -  -  -  -  -	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Ingress Protection	Environment Resistant
Features - Voltage - Rated 400VAC, 550VDC Current Rating -	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 400VAC, 550VDC  Current Rating -	Contact Finish	Gold
Current Rating -	Features	-
•	Voltage - Rated	400VAC, 550VDC
Poport arrays	Current Rating	-
Report errors?		Report errors?

## SJTP00RT-24-35S(014) Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## SJTP00RT-24-35S(014) Payment Methods



















# SJTP00RT-24-35S(014) Shipping Methods













If you have any question about SJTP00RT-24-35S(014), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com