

# SK010M200ST

## SK010M200ST Information

www.heiseher.com	Part Number	SK010M200ST	
	Manufacturer	Cornell Dubilier Electronics (CDE)	
	Category	Capacitors Aluminum Electrolytic Capacitors	1000
	Description	CAP ALUM 1UF 20% 200V RADIAL	
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# SK010M200ST Specifications

Manufacturer Cornell Dubilier Electronics (CDE)   Category Capacitors   Atuminum Electrolytic Capacitors Atuminum Electrolytic Capacitors   Package Radial, Can   Series SK   Capacitance 1µF   Tolerance ±20%   Voltage - Rated 200V   ESR (Equivalent Series Resistance) 199.04 Ohm @ 120Hz   Lifetime @ Temp. 2000 Hrs @ 85°C   Operating Temperature -25°C ~ 85°C   Polarization General Purpose   Applications General Purpose   Ripple Current - Low Frequency 23.8m A @ 1kHz   Impedance -   Lead Spacing 0.098" (2.50mm)   Size / Dimension 0.248" Dia (6.30mm)   Height - Seated (Max) 0.512" (13.00mm)   Surface Mount Land Size -   Mounting Type Through Hole		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesSKCapacitance1µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)199.04 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency17mA @ 120HzRipple Current - High Frequency23.8mA @ 1kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer Part Number	SK010M200ST
Auminum Electrolytic CapacitorsPackageRadial, CanSeriesSKCapacitanceIµFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)199.04 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency23.8mA @ 1kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Cornell Dubilier Electronics (CDE)
PackageRadial, CanSeriesSKCapacitanceIµFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)199.04 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency23.8mA @ 1kHzImpedance-Lad Spacing0.098° (2.50mm)Size / Dimension0.512° (13.00mm)Sirface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesSKCapacitance1µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)199.04 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency17mA @ 120HzRipple Current - High Frequency23.8mA @ 1kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeRadial, Can		Aluminum Electrolytic Capacitors
CapacitanceIµFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)199.04 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency23.8mA @ 1kHzImpedance-Lead Spacing0.098° (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)199.04 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency17mA @ 120HzBipple Current - High Frequency0.098" (2.50mm)Size / Dimension0.098" (2.50mm)Size / Dimension0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Series	SK
Voltage - Rated200VESR (Equivalent Series Resistance)199.04 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency17mA @ 120HzBipple Current - High Frequency23.8mA @ 1kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.512" (13.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Capacitance	1μF
For a start199.04 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency17mA @ 120HzBipple Current - High Frequency23.8mA @ 1kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.512" (13.00mm)Height - Seated (Max).512" (13.00mm)Surface Mount Land Size-Pockage / CaseRadial, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency17mA @ 120HzRipple Current - High Frequency23.8mA @ 1kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	200V
Operating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency17mA @ 120HzBipple Current - High Frequency23.8mA @ 1kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeRadial, Can	ESR (Equivalent Series Resistance)	199.04 Ohm @ 120Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency17mA @ 120HzRipple Current - High Frequency23.8mA @ 1kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HoleRadial, CanRadial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency17mA @ 120HzRipple Current - High Frequency23.8mA @ 1kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency17mA @ 120HzRipple Current - High Frequency23.8mA @ 1kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
InInRipple Current - High Frequency23.8mA @ 1kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	17mA @ 120Hz
Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	23.8mA @ 1kHz
Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.248" Dia (6.30mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.512" (13.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### **SK010M200ST Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### SK010M200ST Payment Methods





If you have any question about SK010M200ST, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com