



SK057C564KAR Information



For Reference Only

Part Number SK057C564KAR
Manufacturer AVX Corporation
Category Capacitors

Ceramic Capacitors

Description CAP CER 0.56UF 500V X7R RADIAL

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SW057C5CAWAD	Chasifications
SK057C564KAR	Specifications

Manufacturer Part Number \$K057C564KAR Manufacturer AVX Corporation Category Capacitors Package Radial Series \$K Capacitance 0.56µF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications SMPS Filtering Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) - Lead Spacing 0.402" (10.20mm) Lead Style Straight		
Category Capacitors Package Radial Series SK Capacitance 0.56μF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Applications SMPS Filtering Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) - Lead Spacing 0.402" (10.20mm) Lead Style Straight	Manufacturer Part Number	SK057C564KAR
Package Radial Series SK Capacitance 0.56μF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications SMPS Filtering Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) - Lead Spacing 0.402" (10.20mm) Lead Style Straight	Manufacturer	AVX Corporation
Package Radial Series SK Capacitance 0.56μF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications SMPS Filtering Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) - Lead Spacing 0.402" (10.20mm) Lead Style Straight	Category	Capacitors
Series SK Capacitance 0.56µF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications SMPS Filtering Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) - Lead Spacing 0.402" (10.20mm) Lead Style Straight		Ceramic Capacitors
Capacitance 0.56µF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications SMPS Filtering Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) - Lead Spacing 0.402" (10.20mm) Lead Style Straight	Package	Radial
Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Ratings Applications SMPS Filtering Failure Rate Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) Lead Spacing 0.402" (10.20mm) Lead Style Straight	Series	SK
Voltage - Rated500VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsSMPS FilteringFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.500" L x 0.200" W (12.70mm x 5.08mm)Height - Seated (Max)0.560" (14.22mm)Thickness (Max)-Lead Spacing0.402" (10.20mm)Lead StyleStraight	Capacitance	0.56μF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features - Ratings - Applications SMPS Filtering Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style X7R A7R A7R A7R	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsSMPS FilteringFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.500" L x 0.200" W (12.70mm x 5.08mm)Height - Seated (Max)0.560" (14.22mm)Thickness (Max)-Lead Spacing0.402" (10.20mm)Lead StyleStraight	Voltage - Rated	500V
Features Ratings - Applications SMPS Filtering Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) Lead Spacing 0.402" (10.20mm) Lead Style Straight	Temperature Coefficient	X7R
Ratings - SMPS Filtering - SMPS Filtering - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) - Lead Spacing 0.402" (10.20mm) Lead Style Straight	Operating Temperature	-55°C ~ 125°C
Applications SMPS Filtering Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) - Lead Spacing 0.402" (10.20mm) Lead Style Straight	Features	-
Failure Rate Mounting Type Through Hole Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) - Lead Spacing 0.402" (10.20mm) Lead Style Straight	Ratings	-
Mounting Type Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) - Lead Spacing 0.402" (10.20mm) Lead Style Straight	Applications	SMPS Filtering
Package / Case Radial Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) - Lead Spacing 0.402" (10.20mm) Lead Style Straight	Failure Rate	-
Size / Dimension 0.500" L x 0.200" W (12.70mm x 5.08mm) Height - Seated (Max) 0.560" (14.22mm) Thickness (Max) - Lead Spacing 0.402" (10.20mm) Lead Style Straight	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style O.560" (14.22mm) - U.402" (10.20mm) Straight	Package / Case	Radial
Thickness (Max) Lead Spacing 0.402" (10.20mm) Lead Style Straight	Size / Dimension	0.500" L x 0.200" W (12.70mm x 5.08mm)
Lead Spacing 0.402" (10.20mm) Lead Style Straight	Height - Seated (Max)	0.560" (14.22mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.402" (10.20mm)
Report errors?	Lead Style	Straight
		Report errors?

SK057C564KAR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SK057C564KAR Payment Methods



















SK057C564KAR Shipping Methods













If you have any question about SK057C564KAR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com