

SK100M450ST

SK100M450ST Information

	De 4 Marcher	SK100M450ST	
www.ine.sener.com	Part Number	SK100M450ST	
	Manufacturer	Cornell Dubilier Electronics (CDE)	
	Category	Capacitors Aluminum Electrolytic Capacitors	2000
	Description	CAP ALUM 10UF 20% 450V RADIAL	
	Package	Radial, Can	- 11 230.
		For the pricing/inventory/lead time, please contact	EL62774
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SK100M450ST Specifications

ManufacturerCornell Dubilier Electronics (CDE)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanStriesSKCapacitance10µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)26.54 OhmLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarization-ApplicationsGeneral PurposeRipple Current - High Frequency-Impedance0.197" (5.00mm)Size / Dimension0.512" Dia (13.00mm)Height - Seated (Max)0.906" (23.00mm)Surface Mount Land Size-Mounting TypeThrough Hole		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesSKCapacitance10µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)26.54 OhmLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.512" Dia (13.00mm)Height - Seated (Max)0.906" (23.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer Part Number	SK100M450ST
Auminum Electrolytic CapacitorsPackageRadial, CanSeriesSKCapacitance10μFTolerance±20%Voltage - Rated26.54 OhmESR (Equivalent Series Resistance)26.54 OhmLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lad Spacing0.197" (5.00mm)Size / Dimension0.512" Dia (13.00mm)Sirface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadial, Can	Manufacturer	Cornell Dubilier Electronics (CDE)
PackageRadial, CanSeriesSKCapacitance10μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)26.54 OhmLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarization-ApplicationsGeneral PurposeRipple Current - High Frequency-Impedance-Lad Spacing0.197" (5.00mm)Size / Dimension0.512" Dia (13.00mm)Size / Dimension-Surface Mount Land Size-Package / CaseRadial, Can	Category	Capacitors
SeriesSKCapacitance10µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)26.54 OhmLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency-Inpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.512" Dia (13.00mm)Birghe Seated (Max)0.906" (23.00mm)Surface Mount Land Size-Mounting TypeRadial, Can		Aluminum Electrolytic Capacitors
Capacitance10μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)26.54 OhmLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.512" Dia (13.00mm)Bight - Seated (Max)0.906" (23.00mm)Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadial, Can	Package	Radial, Can
Tolerance±0%Voltage - Rated450VESR (Equivalent Series Resistance)26.54 OhmLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.512" Dia (13.00mm)Height - Seated (Max)0.906" (23.00mm)Surface Mount Land Size-Package / CaseRatial, Can	Series	SK
Voltage - Rated450VESR (Equivalent Series Resistance)26.54 OhmLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.906" (23.00mm)Height - Seated (Max)0.906" (23.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Capacitance	10µF
ESR (Equivalent Series Resistance)26.54 OhmLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.512" Dia (13.00mm)Height - Seated (Max)0.906" (23.00mm)Surface Mount Land Size-Pockage / CaseRadial, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.512" Dia (13.00mm)Height - Seated (Max)0.906" (23.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	450V
Operating Temperature-25°C ~ 85°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.512" Dia (13.00mm)Height - Seated (Max)0.906" (23.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	26.54 Ohm
Polarization-ApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.512" Dia (13.00mm)Height - Seated (Max)0.906" (23.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.512" Dia (13.00mm)Height - Seated (Max)0.906" (23.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.512" Dia (13.00mm)Height - Seated (Max)0.906" (23.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	-
Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.512" Dia (13.00mm)Height - Seated (Max)0.906" (23.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.512" Dia (13.00mm)Height - Seated (Max)0.906" (23.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.197" (5.00mm)Size / Dimension0.512" Dia (13.00mm)Height - Seated (Max)0.906" (23.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension0.512" Dia (13.00mm)Height - Seated (Max)0.906" (23.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.906" (23.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.512" Dia (13.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.906" (23.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

SK100M450ST Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE UARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SK100M450ST Payment Methods





If you have any question about SK100M450ST, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com