

SLPX122M220E7P3

SLPX122M220E7P3 Information



Part Number	SLPX122M220E7P3	
Manufacturer	Cornell Dubilier Electronics (CDE)	
Category	Capacitors Aluminum Electrolytic Capacitors	
Description	CAP ALUM 1200UF 20% 220V SNAP	
Package	Radial, Can - Snap-In	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SLPX122M220E7P3 Specifications

Manufacturer Part Number SLPX122M220E7P3 Manufacturer Cornell Dubilier Electronics (CDE) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series SLPX Capacitance 1200µF Tolerance ±200µ Voltage - Rated 220V ESR (Equivalent Series Resistance) 166 mOhm @ 120Hz Lifetime @ Temp. 3000 Hrs @ 85°C Operating Temperature 40°C ~ 85°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency 3.54A @ 120Hz Ippedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Size / Dimension - Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesSLPXCapacitance1200µFTolerance±20%Voltage - Rated20VESR (Equivalent Series Resistance)166 mOhm @ 120HzLifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency5.2A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	SLPX122M220E7P3
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesSLPXCapacitance1200µFTolerance±20%Voltage - Rated220VESR (Equivalent Series Resistance)166 mOhm @ 120HzLifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsS.2A @ 20HzRipple Current - Low Frequency5.2A @ 20HzRipple Current - High Frequency0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension1.575" (40.00mm)Height - Seated (Max).Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer	Cornell Dubilier Electronics (CDE)
PackageRadial, Can - Snap-InSeriesSLPXCapacitance1200µFTolerance±20%Voltage - Rated220VESR (Equivalent Series Resistance)166 mOhm @ 120HzLifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency5.2A @ 20kHzRippe Current - High Frequency0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesSLPXCapacitance1200µFTolerance±20%Voltage - Rated220VESR (Equivalent Series Resistance)166 mOhm @ 120HzLifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.54A @ 120HzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.81" Dia (30.00mm)Height - Seated (Max)5.75" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance120μFTolerance±20%Voltage - Rated20VESR (Equivalent Series Resistance)166 mOhm @ 120HzESR (Equivalent Series Resistance)3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency5.2A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±0%Voltage - Rated20VESR (Equivalent Series Resistance)166 mOhm @ 120HzLifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.54A @ 120HzMippelance-Lead Spacing0.394" (10.00mm)Size / Dimension1.81" Dia (30.00mm)Bight - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatia, Can - Snap-In	Series	SLPX
Voltage - Rated200VESR (Equivalent Series Resistance)166 mOhm @ 120HzLifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.54A @ 120HzRipple Current - High Frequency5.2A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Capacitance	1200µF
ESR (Equivalent Series Resistance)166 mOhm @ 120HzLifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.54A @ 120HzMipedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension5.75" (40.00mm)Muring Type-Rounting TypeFrough HolePackage / CaseRidial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 85°CDeperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.54A @ 120HzRipple Current - High Frequency5.2A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)5.75" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	220V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.54A @ 120HzBipple Current - High Frequency5.2A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max).Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	166 mOhm @ 120Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.54A @ 120HzRipple Current - High Frequency5.2A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency3.54A @ 120HzRipple Current - High Frequency5.2A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency3.54A @ 120HzRipple Current - High Frequency5.2A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency5.2A @ 20kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	3.54A @ 120Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	5.2A @ 20kHz
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	-
Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.575" (40.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors ²	Package / Case	Radial, Can - Snap-In
•		Report errors?

SLPX122M220E7P3 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SLPX122M220E7P3 Payment Methods





If you have any question about SLPX122M220E7P3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com