

SLPX153M025C7P3

SLPX153M025C7P3 Information



Part Number	SLPX153M025C7P3	
Manufacturer	Cornell Dubilier Electronics (CDE)	
Category	Capacitors Aluminum Electrolytic Capacitors	
Description	CAP ALUM 15000UF 20% 25V SNAP	
Package	Radial, Can - Snap-In	
	For the pricing/inventory/lead time, please contact us	
	Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SLPX153M025C7P3 Specifications

Manufacturer Part Number SLPX153M025C7P3 Manufacturer Cornell Dubilier Electronics (CDE) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series SLPX Capacitance 15000µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 400 Mn Lifetime @ Temp. 3000 Hrs @ S°C Operating Temperature -40°C ~ S°C Polarization General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Mandacture - Lied Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Size / Dimension - Mounting Type - Mounting Type -		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesSLPXCapacitance15000µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)40 mOhmLifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	SLPX153M025C7P3
Automium Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesSLPXCapacitance15000µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)40 mOhmLifetime @ Temp.3000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Size / Dimension1.575" (40.00mm)Surface Mount Land Size-Mounting TypeTurough HolePackage / CaseRadial, Can - Snap-In	Manufacturer	Cornell Dubilier Electronics (CDE)
PackageRadial, Can - Snap-InSeriesSLPXCapacitance15000µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)40 mOhmLifetime @ Temp.3000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Size / Dimension0.984" Dia (25.00mm)Surface Mount Land Size-Mounting TypeFinough HolePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesSLPXCapacitance15000µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)40 m MmLifetime @ Temp.3000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Indedace.Star / Dimension0.394" (10.00mm)Size / Dimension.Height - Seated (Max).Surface Mount Land Size.Mounting Type.Package / Case.Rolange / Case.		Aluminum Electrolytic Capacitors
Capacitance1500µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)40 mOhmLifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Iszer J Dimension0.984" Dia (25.00mm)Sizer J Dimension0.984" Dia (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)40 mOhmLifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can - Snap-In	Series	SLPX
Voltage - Rated25VESR (Equivalent Series Resistance)40 mOhmLifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Inpedance0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Capacitance	15000µF
ESR (Equivalent Series Resistance)40 mOhmLifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Inpedance-Inpedance0394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max).575" (40.00mm)Surface Mount Land Size-Mounting TypeMounting TypePackage / CaseRadia, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Voltage - Rated	25V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	40 mOhm
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	-
Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	-
Height - Seated (Max)1.575" (40.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.575" (40.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report error	Package / Case	Radial, Can - Snap-In
Reporterior		Report errors?

SLPX153M025C7P3 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SLPX153M025C7P3 Payment Methods





If you have any question about SLPX153M025C7P3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com