



### **SLR-342DC3F Information**



For Reference Only

Part Number SLR-342DC3F

Manufacturer Rohm Semiconductor

**Category** Optoelectronics

LED Indication - Discrete

**Description** LED ORANGE CLEAR 3MM ROUND T/H

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **SLR-342DC3F Specifications**

Manufacturer Part Number         SLR-342DC3F           Manufacturer         Rohm Semiconductor           Category         Optoelectronics           LED Indication - Discrete           Package         Radial           Series         SLR-342           Color         Orange           Configuration         -           Lens Color         Orange           Lens Transparency         Clear           Millicandela Rating         25mcd           Lens Style/Size         Round with Domed Top, 3.10mm           Voltage - Forward (Vf) (Typ)         2V           Current - Test         10mA           Viewing Angle         40°           Mounting Type         Through Hole           Wavelength - Dominant         605mm           Wavelength - Peak         -           Features         -           Package / Case         Radial           Supplier Device Package         T-1           Size / Dimension         -           Height (Max)         5.40mm		
Category         Optoelectronics           Package         Radial           Series         SLR-342           Color         Orange           Configuration         -           Lens Color         Orange           Lens Transparency         Clear           Millicandela Rating         25mcd           Lens Style/Size         Round with Domed Top, 3.10mm           Voltage - Forward (Vf) (Typ)         2V           Current - Test         10mA           Viewing Angle         40°           Mounting Type         Through Hole           Wavelength - Dominant         605nm           Wavelength - Peak         -           Features         -           Package / Case         Radial           Supplier Device Package         T-1           Size / Dimension         -           Height (Max)         5.40mm	Manufacturer Part Number	SLR-342DC3F
Package         Radial           Series         SLR-342           Color         Orange           Configuration         -           Lens Color         Orange           Lens Transparency         Clear           Millicandela Rating         25mcd           Lens Style/Size         Round with Domed Top, 3.10mm           Voltage - Forward (Vf) (Typ)         2V           Current - Test         10mA           Viewing Angle         40°           Mounting Type         Through Hole           Wavelength - Dominant         605nm           Wavelength - Peak         -           Features         -           Package / Case         Radial           Supplier Device Package         T-1           Size / Dimension         -           Height (Max)         5.40mm	Manufacturer	Rohm Semiconductor
Package         Radial           Series         SLR-342           Color         Orange           Configuration         -           Lens Color         Orange           Lens Transparency         Clear           Millicandela Rating         25mcd           Lens Style/Size         Round with Domed Top, 3.10mm           Voltage - Forward (Vf) (Typ)         2V           Current - Test         10mA           Viewing Angle         40°           Mounting Type         Through Hole           Wavelength - Dominant         605nm           Wavelength - Peak         -           Features         -           Package / Case         Radial           Supplier Device Package         T-1           Size / Dimension         -           Height (Max)         5.40mm	Category	Optoelectronics
Series         SLR-342           Color         Orange           Configuration         -           Lens Color         Orange           Lens Transparency         Clear           Millicandela Rating         25mcd           Lens Style/Size         Round with Domed Top, 3.10mm           Voltage - Forward (Vf) (Typ)         2V           Current - Test         10mA           Viewing Angle         40°           Mounting Type         Through Hole           Wavelength - Dominant         605nm           Wavelength - Peak         -           Features         -           Package / Case         Radial           Supplier Device Package         T-1           Size / Dimension         -           Height (Max)         5.40mm		LED Indication - Discrete
Color         Orange           Configuration         -           Lens Color         Orange           Lens Transparency         Clear           Millicandela Rating         25mcd           Lens Style/Size         Round with Domed Top, 3.10mm           Voltage - Forward (Vf) (Typ)         2V           Current - Test         10mA           Viewing Angle         40°           Mounting Type         Through Hole           Wavelength - Dominant         605nm           Wavelength - Peak         -           Features         -           Package / Case         Radial           Supplier Device Package         T-1           Size / Dimension         -           Height (Max)         5.40mm	Package	Radial
Configuration         -           Lens Color         Orange           Lens Transparency         Clear           Millicandela Rating         25mcd           Lens Style/Size         Round with Domed Top, 3.10mm           Voltage - Forward (Vf) (Typ)         2V           Current - Test         10mA           Viewing Angle         40°           Mounting Type         Through Hole           Wavelength - Dominant         605nm           Wavelength - Peak         -           Features         -           Package / Case         Radial           Supplier Device Package         T-1           Size / Dimension         -           Height (Max)         5.40mm	Series	SLR-342
Lens ColorOrangeLens TransparencyClearMillicandela Rating25mcdLens Style/SizeRound with Domed Top, 3.10mmVoltage - Forward (Vf) (Typ)2VCurrent - Test10mAViewing Angle40°Mounting TypeThrough HoleWavelength - Dominant605nmWavelength - Peak-Features-Package / CaseRadialSupplier Device PackageT-1Size / Dimension-Height (Max)5.40mm	Color	Orange
Lens Transparency Millicandela Rating Lens Style/Size Round with Domed Top, 3.10mm Voltage - Forward (Vf) (Typ) 2V Current - Test 10mA Viewing Angle Mounting Type Through Hole Wavelength - Dominant 605nm Wavelength - Peak - Features - Package / Case Radial Supplier Device Package T-1 Size / Dimension - Height (Max) Style Clear Style Clear Style Clear Style Clear Control Clear Style Clear Round with Domed Top, 3.10mm  Tops  Round with Domed Top, 3.10mm   605nm  - Through Hole Throug	Configuration	-
Millicandela Rating  Lens Style/Size  Round with Domed Top, 3.10mm  Voltage - Forward (Vf) (Typ)  2V  Current - Test  10mA  Viewing Angle  40°  Mounting Type  Through Hole  Wavelength - Dominant  605nm  Wavelength - Peak  - Features  - Package / Case  Radial  Supplier Device Package  T-1  Size / Dimension  Height (Max)  25mcd  Round with Domed Top, 3.10mm  2V  Current - Top, 3.10mm  Aunual Top, 3.10mm  - Round with Domed Top, 3.10mm  2V  Round With Domed Top, 3.10mm  Analog Top, 3.10mm  - Through Hole  10mA  40°  - Through Hole  40°  Throu	Lens Color	Orange
Lens Style/SizeRound with Domed Top, 3.10mmVoltage - Forward (Vf) (Typ)2VCurrent - Test10mAViewing Angle40°Mounting TypeThrough HoleWavelength - Dominant605nmWavelength - Peak-Features-Package / CaseRadialSupplier Device PackageT-1Size / Dimension-Height (Max)5.40mm	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ)2VCurrent - Test10mAViewing Angle40°Mounting TypeThrough HoleWavelength - Dominant605nmWavelength - Peak-Features-Package / CaseRadialSupplier Device PackageT-1Size / Dimension-Height (Max)5.40mm	Millicandela Rating	25mcd
Current - Test 10mA  Viewing Angle 40°  Mounting Type Through Hole  Wavelength - Dominant 605nm  Wavelength - Peak - Features - Package / Case Radial  Supplier Device Package T-1  Size / Dimension - Height (Max) 5.40mm	Lens Style/Size	Round with Domed Top, 3.10mm
Viewing Angle40°Mounting TypeThrough HoleWavelength - Dominant605nmWavelength - Peak-Features-Package / CaseRadialSupplier Device PackageT-1Size / Dimension-Height (Max)5.40mm	Voltage - Forward (Vf) (Typ)	2V
Mounting Type Through Hole  Wavelength - Dominant 605nm  Wavelength - Peak - Features - Package / Case Radial  Supplier Device Package T-1  Size / Dimension - Height (Max) 5.40mm	Current - Test	10mA
Wavelength - Dominant  Wavelength - Peak  Features  - Package / Case  Radial  Supplier Device Package  T-1  Size / Dimension  - Height (Max)  605nm  605nm  -  Radial  -  8444  Features  -  8444  Features  Featu	Viewing Angle	40°
Wavelength - Peak - Case - Case Radial Supplier Device Package / Case T-1 Size / Dimension - Case Feight (Max) 5.40mm	Mounting Type	Through Hole
Features - Case Radial Supplier Device Package T-1 Size / Dimension - Height (Max) 5.40mm	Wavelength - Dominant	605nm
Package / Case Radial Supplier Device Package T-1 Size / Dimension - Height (Max) 5.40mm	Wavelength - Peak	-
Supplier Device Package T-1 Size / Dimension - Height (Max) 5.40mm	Features	-
Size / Dimension - Height (Max) 5.40mm	Package / Case	Radial
Height (Max) 5.40mm	Supplier Device Package	T-1
	Size / Dimension	-
Report errors?	Height (Max)	5.40mm
		Report errors?

#### **SLR-342DC3F Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **SLR-342DC3F Payment Methods**



















## **SLR-342DC3F Shipping Methods**













If you have any question about SLR-342DC3F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com