


SLW-114-01-G-S

SLW-114-01-G-S Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SLW-114-01-G-S Specifications

Manufacturer Part NumberSLW-114-01-G-SManufacturerSamtec Inc.CategoryConnectors. InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesSuffect Connectors - Headers, Receptacles, Female SocketsConnector TypeSeretacleContact TypeReceptacles, Temale SocketsStyleBoard Connector SuffectNumber of PositionsI4Number of Positions LoadedI1Number of Rows1Number of RowsINumber of RowsSolderTerminationSolderSteining TypeOido (S.Jum)Contact Finish - MatingGoldContact Finish - MatingGoldContact Finish - MatingGoldContact Finish - MatingIIContact Finish - MatingIII (S.Jum)Contact Finish - MatingIII (S.Jum)Contact Finish - MatingIII (S.Jum)Contact Finish - MatingIII (S.Jum)Contact Finish - MatingIIII (S.Jum)Contact Finish - MatingIIII (S.Jum)Contact Finish - MatingIIIIII (S.Jum)Contact Finish - MatingIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII			
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series SLW Connector Type Receptacle Contact Type Receptacle Contact Type Forked Style Board to Board Number of Positions 14 Number of Positions Loaded All Number of Rows 1 Resenting Type Phole Solder Solder Contact Finish - Mating Gold Contact Finish - Mating Quin (0.51µm) Insulation Color Black Insulation Height 0.180" (4.57mm) Contact Length - Post 0.115" (2.92mm)	Manufacturer Part Number	SLW-114-01-G-S	
ActionRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesSLWConnector TypeReceptacleContact TypeForkedStyleBoard to BoardNumber of Positions14Number of Positions LoadedNilPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypeOusl (0.51µm)Contact Finish - MatingOuju (0.51µm)Contact Finish Thickness - MatingOuju (0.51µm)Insulation ColorBlackInsulation Height0.180" (4.57mm)Contact Length - Post0.115" (2.92mm)Operating Temperature-55°C ~ 125°C	Manufacturer	Samtec Inc.	
Package-SeriesSLWConnector TypeReceptacleContact TypeForkedStyleBoard to BoardNumber of Positions14Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypeQuin (0.51µm)Contact Finish - MatingOldContact Finish Thickness - MatingQuin (0.51µm)Insulation ColorBlackInsulation Height0.180" (4.57mm)Contact Length - Post0.115" (2.92mm)Operating Temperature-55°C ~ 125°C	Category	Connectors, Interconnects	
SeriesSLWConnector TypeReceptacleContact TypeForkedStyleBoard to BoardNumber of Positions14Number of Positions LoadedAllNumber of Rows1Number of Rows1Number of Rows1Number of Rows1Number of Rows-Nourting TypeThrough HoleYourd LinkingSolderContact Finish - MatingGoldContact Finish - MatingGoldStateining TypeBiackInsulation ColorBiackInsulation Height0.108" (4.57mm)Contact Length - Post0.115" (2.92mm)Operating Temperature-55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets	
Connector TypeReceptacleConnector TypeForkedStyleBoard to BoardNumber of Positions14Number of Positions LoadedAllNumber of Positions Loaded0.100" (2.54mm)Number of Rows1Number of Rows.Number of Rows1Number of Rows.Number of RowsSolderStoring TypeSolderPortact Finish - MatingSolderContact Finish - MatingGoldStoract Finish - MatingBlackInsulation ColorBlackInsulation Height0.108" (4.57mm)Contact Length - Post0.115" (2.92mm)Operating Temperature.55°C ~ 125°C	Package	-	
Contact TypeForkedStyleBoard to BoardNumber of Positions14Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldStaltion ColorBlackInsulation Height0.180" (4.57mm)Contact Length - Post0.115" (2.92mm)Operating Temperature-55°C ~ 125°C	Series	SLW	
Style Board to Board Number of Positions 14 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type - Mounting Type Solder Fastening Type Push-Pull Contact Finish - Mating Gold Issulation Color Black Insulation Height 0.180" (4.57mm) Ontact Length - Post 0.115" (2.92mm) Operating Temperature -55°C ~ 125°C	Connector Type	Receptacle	
Number of Positions 14 Number of Positions Loaded All Number of Positions Loaded O.100" (2.54mm) Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Jupin (0.51µm) Insulation Color Black Insulation Height O.180" (4.57mm) Operating Temperature -55°C ~ 125°C	Contact Type	Forked	
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJupin (0.51µm)Insulation ColorBlackInsulation Height0.110" (2.92mm)Operating Temperature-55°C ~ 125°C	Style	Board to Board	
Pitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.180" (4.57mm)Contact Length - Post0.115" (2.92mm)Operating Temperature-55°C ~ 125°C	Number of Positions	14	
Number of Rows1Row Spacing - Mating-Row Spacing - MatingThrough HoleMounting TypeSolderTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.180" (4.57mm)Contact Length - Post0.115" (2.92mm)Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All	
Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.180" (4.57mm)Contact Length - Post0.115" (2.92mm)Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)	
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.180" (4.57mm)Contact Length - Post0.115" (2.92mm)Operating Temperature-55°C ~ 125°C	Number of Rows	1	
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.180" (4.57mm)Contact Length - Post0.115" (2.92mm)Operating Temperature-55°C ~ 125°C	Row Spacing - Mating	-	
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.180" (4.57mm)Contact Length - Post0.115" (2.92mm)Operating Temperature-55°C ~ 125°C	Mounting Type	Through Hole	
Contact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.180" (4.57mm)Contact Length - Post0.115" (2.92mm)Operating Temperature-55°C ~ 125°C	Termination	Solder	
Contact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.180" (4.57mm)Contact Length - Post0.115" (2.92mm)Operating Temperature-55°C ~ 125°C	Fastening Type	Push-Pull	
Insulation ColorBlackInsulation Height0.180" (4.57mm)Contact Length - Post0.115" (2.92mm)Operating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold	
Insulation Height 0.180" (4.57mm) Contact Length - Post 0.115" (2.92mm) Operating Temperature -55°C ~ 125°C	Contact Finish Thickness - Mating	20µin (0.51µm)	
Contact Length - Post0.115" (2.92mm)Operating Temperature-55°C ~ 125°C	Insulation Color	Black	
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.180" (4.57mm)	
	Contact Length - Post	0.115" (2.92mm)	
Material Flammability Rating -	Operating Temperature	-55°C ~ 125°C	
	Material Flammability Rating	-	

Contact Finish - Post	Gold	
Mated Stacking Heights	6.09mm	
Ingress Protection	-	
Features	-	
		Report errors?

SLW-114-01-G-S Guarantees



Quality Guarantees


We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SLW-114-01-G-S Payment Methods



If you have any question about SLW-114-01-G-S, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com