

SLW-128-01-G-S Information



For Reference Only

Part Number SLW-128-01-G-S

Manufacturer Samtec Inc.

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description CONN RCPT .100" 28POS SNGL GOLD

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SLW-128-01-G-S Specifications

Manufacturer Part Number SLW-128-01-G-S Manufacturer Samtec Inc. Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series SLW Connector Type Receptacle Contact Type Forked Style Board to Board Number of Positions 28 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 20µin (0.51µm) Insulation Color Black Insulation Height 0.180" (4.57mm) Contact Length - Post 0.115" (2.92mm)		
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series SLW Connector Type Receptacle Contact Type Forked Style Board to Board Number of Positions 28 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height Oneocitys, Interconnects Receptacles, Female Sockets Receptacles, Female Sockets Rectangular Connectors - Headers, Receptacles, Female Sockets Rectangular Connectors - Headers, Receptacles, Female Sockets - Receptacle	Manufacturer Part Number	SLW-128-01-G-S
Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series SLW Connector Type Receptacle Contact Type Forked Style Board to Board Number of Positions 28 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height Packed SLW Receptacles, Female Sockets 1 Recetangular Connectors - Headers, Receptacles, Female Sockets 1 Rectangular Connectors - Headers, Receptacles, Female Sockets 1 Sulw Sulw Forked 1 Sulw 1 Sulw Sulw	Manufacturer	Samtec Inc.
Package - Series SLW Connector Type Receptacle Contact Type Forked Style Board to Board Number of Positions 28 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 20μin (0.51μm) Insulation Color Black Insulation Height 0.180" (4.57mm)	Category	Connectors, Interconnects
Series SLW Connector Type Receptacle Contact Type Forked Style Board to Board Number of Positions 28 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 20µin (0.51µm) Insulation Color Black Insulation Height 0.180" (4.57mm)		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type Receptacle Contact Type Forked Style Board to Board Number of Positions 28 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 20µin (0.51µm) Insulation Color Black Insulation Height 0.180" (4.57mm)	Package	-
Contact TypeForkedStyleBoard to BoardNumber of Positions28Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20μin (0.51μm)Insulation ColorBlackInsulation Height0.180" (4.57mm)	Series	SLW
Style Board to Board Number of Positions 28 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 20µin (0.51µm) Insulation Color Black Insulation Height 0.180" (4.57mm)	Connector Type	Receptacle
Number of Positions 28 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.180" (4.57mm)	Contact Type	Forked
Number of Positions Loaded Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height All 0.100" (2.54mm) Through Hole Contact Finish Thickness - Mating Black Insulation Height All 0.180" (4.57mm)	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20μin (0.51μm)Insulation ColorBlackInsulation Height0.180" (4.57mm)	Number of Positions	28
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20μin (0.51μm)Insulation ColorBlackInsulation Height0.180" (4.57mm)	Number of Positions Loaded	All
Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20μin (0.51μm)Insulation ColorBlackInsulation Height0.180" (4.57mm)	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20μin (0.51μm)Insulation ColorBlackInsulation Height0.180" (4.57mm)	Number of Rows	1
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 20μin (0.51μm) Insulation Color Black Insulation Height 0.180" (4.57mm)	Row Spacing - Mating	-
Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.180" (4.57mm)	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating20μin (0.51μm)Insulation ColorBlackInsulation Height0.180" (4.57mm)	Termination	Solder
Contact Finish Thickness - Mating 20μin (0.51μm) Insulation Color Black Insulation Height 0.180" (4.57mm)	Fastening Type	Push-Pull
Insulation Color Black Insulation Height 0.180" (4.57mm)	Contact Finish - Mating	Gold
Insulation Height 0.180" (4.57mm)	Contact Finish Thickness - Mating	20μin (0.51μm)
-	Insulation Color	Black
Contact Length - Post 0.115" (2.92mm)	Insulation Height	0.180" (4.57mm)
	Contact Length - Post	0.115" (2.92mm)
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating -	Material Flammability Rating	-

Contact Finish - Post	Gold
Mated Stacking Heights	6.09mm
Ingress Protection	-
Features	-
	Report errors?

SLW-128-01-G-S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SLW-128-01-G-S Payment Methods



















SLW-128-01-G-S Shipping Methods













If you have any question about SLW-128-01-G-S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com