



SM4124BT1R00 Information

w.heisener.c

Part Number SM4124BT1R00

Manufacturer Stackpole Electronics Inc.

Category Resistors

Chip Resistor - Surface Mount

Description RES SMD 1 OHM 0.1% 2W 4124

Package 4124 J-Lead

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SM4124BT1R00 Specifications

Manufacturer Part NumberSM4124BT1R00ManufacturerStackpole Electronics Inc.CategoryResistorsChip Resistor - Surface MountPackage4124 J-LeadSeriesSMResistance1 OhmsTolerance±0.1%Power (Watts)2WCompositionWirewoundFeaturesMoisture Resistant, Pulse WithstandingTemperature Coefficient-Operating Temperature-55°C ~ 275°CPackage / Case4124 J-LeadSupplier Device Package4124Size / Dimension0.429" L x 0.240" W (10.90mm x 6.10mm)Height - Seated (Max)0.195" (4.95mm)Number of Terminations2Failure Rate-	•	
Category Resistors Chip Resistor - Surface Mount Package 4124 J-Lead Series SM Resistance 1 Ohms Tolerance ±0.1% Power (Watts) 2W Composition Wirewound Features Moisture Resistant, Pulse Withstanding Temperature Coefficient - Operating Temperature -55°C ~ 275°C Package / Case 4124 J-Lead Supplier Device Package 4124 Size / Dimension 0.429" L x 0.240" W (10.90mm x 6.10mm) Height - Seated (Max) 0.195" (4.95mm) Number of Terminations 2 Failure Rate -	Manufacturer Part Number	SM4124BT1R00
Chip Resistor - Surface Mount Package 4124 J-Lead Series SM Resistance 1 Ohms Tolerance ±0.1% Power (Watts) 2W Composition Wirewound Features Moisture Resistant, Pulse Withstanding Temperature Coefficient - Operating Temperature -55°C ~ 275°C Package / Case 4124 J-Lead Supplier Device Package 4124 Size / Dimension 0.429" L x 0.240" W (10.90mm x 6.10mm) Height - Seated (Max) 0.195" (4.95mm) Number of Terminations 2 Failure Rate -	Manufacturer	Stackpole Electronics Inc.
Package 4124 J-Lead Series SM Resistance 1 Ohms Tolerance ±0.1% Power (Watts) 2W Composition Wirewound Features Moisture Resistant, Pulse Withstanding Temperature Coefficient - Operating Temperature -55°C ~ 275°C Package / Case 4124 J-Lead Supplier Device Package 4124 Size / Dimension 0.429" L x 0.240" W (10.90mm x 6.10mm) Height - Seated (Max) 0.195" (4.95mm) Number of Terminations 2 Failure Rate -	Category	Resistors
Series SM Resistance 1 Ohms Tolerance ±0.1% Power (Watts) 2W Composition Wirewound Features Moisture Resistant, Pulse Withstanding Temperature Coefficient - Operating Temperature -55°C ~ 275°C Package / Case 4124 J-Lead Supplier Device Package 4124 Size / Dimension 0.429" L x 0.240" W (10.90mm x 6.10mm) Height - Seated (Max) 0.195" (4.95mm) Number of Terminations 2 Failure Rate -		Chip Resistor - Surface Mount
Resistance 1 Ohms Tolerance ±0.1% Power (Watts) 2W Composition Wirewound Features Moisture Resistant, Pulse Withstanding Temperature Coefficient - Operating Temperature -55°C ~ 275°C Package / Case 4124 J-Lead Supplier Device Package 4124 Size / Dimension 0.429" L x 0.240" W (10.90mm x 6.10mm) Height - Seated (Max) 0.195" (4.95mm) Number of Terminations 2 Failure Rate -	Package	4124 J-Lead
Tolerance ±0.1% Power (Watts) 2W Composition Wirewound Features Moisture Resistant, Pulse Withstanding Temperature Coefficient - Operating Temperature -55°C ~ 275°C Package / Case 4124 J-Lead Supplier Device Package 4124 Size / Dimension 0.429" L x 0.240" W (10.90mm x 6.10mm) Height - Seated (Max) 0.195" (4.95mm) Number of Terminations 2 Failure Rate -	Series	SM
Power (Watts) Composition Wirewound Features Moisture Resistant, Pulse Withstanding Temperature Coefficient Operating Temperature -55°C ~ 275°C Package / Case 4124 J-Lead Supplier Device Package Size / Dimension 0.429" L x 0.240" W (10.90mm x 6.10mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Resistance	1 Ohms
Composition Wirewound Features Moisture Resistant, Pulse Withstanding Temperature Coefficient Operating Temperature -55°C ~ 275°C Package / Case 4124 J-Lead Supplier Device Package 4124 Size / Dimension 0.429" L x 0.240" W (10.90mm x 6.10mm) Height - Seated (Max) 0.195" (4.95mm) Number of Terminations 2 Failure Rate -	Tolerance	±0.1%
Features Moisture Resistant, Pulse Withstanding Temperature Coefficient Operating Temperature -55°C ~ 275°C Package / Case 4124 J-Lead Supplier Device Package 4124 Size / Dimension 0.429" L x 0.240" W (10.90mm x 6.10mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Power (Watts)	2W
Temperature Coefficient Operating Temperature -55°C ~ 275°C Package / Case 4124 J-Lead Supplier Device Package 4124 Size / Dimension 0.429" L x 0.240" W (10.90mm x 6.10mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Composition	Wirewound
Operating Temperature -55°C ~ 275°C Package / Case 4124 J-Lead Supplier Device Package 4124 Size / Dimension 0.429" L x 0.240" W (10.90mm x 6.10mm) Height - Seated (Max) 0.195" (4.95mm) Number of Terminations 2 Failure Rate -	Features	Moisture Resistant, Pulse Withstanding
Package / Case 4124 J-Lead Supplier Device Package 4124 Size / Dimension 0.429" L x 0.240" W (10.90mm x 6.10mm) Height - Seated (Max) 0.195" (4.95mm) Number of Terminations 2 Failure Rate -	Temperature Coefficient	-
Supplier Device Package 4124 Size / Dimension 0.429" L x 0.240" W (10.90mm x 6.10mm) Height - Seated (Max) 0.195" (4.95mm) Number of Terminations 2 Failure Rate -	Operating Temperature	-55°C ~ 275°C
Size / Dimension 0.429" L x 0.240" W (10.90mm x 6.10mm) Height - Seated (Max) 0.195" (4.95mm) Number of Terminations 2 Failure Rate -	Package / Case	4124 J-Lead
Height - Seated (Max) 0.195" (4.95mm) Number of Terminations 2 Failure Rate -	Supplier Device Package	4124
Number of Terminations 2 Failure Rate -	Size / Dimension	0.429" L x 0.240" W (10.90mm x 6.10mm)
Failure Rate -	Height - Seated (Max)	0.195" (4.95mm)
	Number of Terminations	2
Report errors?	Failure Rate	-
		Report errors?

SM4124BT1R00 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SM4124BT1R00 Payment Methods



















SM4124BT1R00 Shipping Methods













If you have any question about SM4124BT1R00, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com