



#### SM6227FT143R Information

w.heisener.c

Part Number SM6227FT143R

Manufacturer Stackpole Electronics Inc.

**Category** Resistors

Chip Resistor - Surface Mount

**Description** RES SMD 143 OHM 1% 3W 6227

Package 6227 J-Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **SM6227FT143R Specifications**

Manufacturer Part NumberSM6227FT143RManufacturerStackpole Electronics Inc.CategoryResistorsChip Resistor - Surface MountPackage6227 J-LeadSeriesSMResistance143 OhmsTolerance±1%Power (Watts)3WCompositionWirewoundFeaturesMoisture Resistant, Pulse WithstandingTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CPackage / Case6227 J-LeadSupplier Device Package6227Size / Dimension0.646" L x 0.276" W (16.40mm x 7.00mm)Height - Seated (Max)0.265" (6.73mm)Number of Terminations2Failure Rate-	•	
Category         Resistors           Chip Resistor - Surface Mount           Package         6227 J-Lead           Series         SM           Resistance         143 Ohms           Tolerance         ±1%           Power (Watts)         3W           Composition         Wirewound           Features         Moisture Resistant, Pulse Withstanding           Temperature Coefficient         ±20ppm/°C           Operating Temperature         -55°C ~ 275°C           Package / Case         6227 J-Lead           Supplier Device Package         6227           Size / Dimension         0.646" L x 0.276" W (16.40mm x 7.00mm)           Height - Seated (Max)         0.265" (6.73mm)           Number of Terminations         2           Failure Rate         -	Manufacturer Part Number	SM6227FT143R
Chip Resistor - Surface Mount           Package         6227 J-Lead           Series         SM           Resistance         143 Ohms           Tolerance         ±1%           Power (Watts)         3W           Composition         Wirewound           Features         Moisture Resistant, Pulse Withstanding           Temperature Coefficient         ±20ppm/°C           Operating Temperature         -55°C ~ 275°C           Package / Case         6227 J-Lead           Supplier Device Package         6227           Size / Dimension         0.646" L x 0.276" W (16.40mm x 7.00mm)           Height - Seated (Max)         0.265" (6.73mm)           Number of Terminations         2           Failure Rate         -	Manufacturer	Stackpole Electronics Inc.
Package6227 J-LeadSeriesSMResistance143 OhmsTolerance±1%Power (Watts)3WCompositionWirewoundFeaturesMoisture Resistant, Pulse WithstandingTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CPackage / Case6227 J-LeadSupplier Device Package6227Size / Dimension0.646" L x 0.276" W (16.40mm x 7.00mm)Height - Seated (Max)0.265" (6.73mm)Number of Terminations2Failure Rate-	Category	Resistors
Series         SM           Resistance         143 Ohms           Tolerance         ±1%           Power (Watts)         3W           Composition         Wirewound           Features         Moisture Resistant, Pulse Withstanding           Temperature Coefficient         ±20ppm/°C           Operating Temperature         -55°C ~ 275°C           Package / Case         6227 J-Lead           Supplier Device Package         6227           Size / Dimension         0.646" L x 0.276" W (16.40mm x 7.00mm)           Height - Seated (Max)         0.265" (6.73mm)           Number of Terminations         2           Failure Rate         -		Chip Resistor - Surface Mount
Resistance 143 Ohms  Tolerance ±1%  Power (Watts) 3W  Composition Wirewound  Features Moisture Resistant, Pulse Withstanding  Temperature Coefficient ±20ppm/°C  Operating Temperature -55°C ~ 275°C  Package / Case 6227 J-Lead  Supplier Device Package 6227  Size / Dimension 0.646" L x 0.276" W (16.40mm x 7.00mm)  Height - Seated (Max) 0.265" (6.73mm)  Number of Terminations 2  Failure Rate -	Package	6227 J-Lead
Tolerance ±1%  Power (Watts) 3W  Composition Wirewound  Features Moisture Resistant, Pulse Withstanding  Temperature Coefficient ±20ppm/°C  Operating Temperature -55°C ~ 275°C  Package / Case 6227 J-Lead  Supplier Device Package 6227  Size / Dimension 0.646" L x 0.276" W (16.40mm x 7.00mm)  Height - Seated (Max) 0.265" (6.73mm)  Number of Terminations 2  Failure Rate -	Series	SM
Power (Watts)  Composition  Wirewound  Features  Moisture Resistant, Pulse Withstanding  Temperature Coefficient  ±20ppm/°C  Operating Temperature  -55°C ~ 275°C  Package / Case  6227 J-Lead  Supplier Device Package  Size / Dimension  0.646" L x 0.276" W (16.40mm x 7.00mm)  Height - Seated (Max)  Number of Terminations  2  Failure Rate  -	Resistance	143 Ohms
Composition  Wirewound  Features  Moisture Resistant, Pulse Withstanding  Temperature Coefficient  ±20ppm/°C  Operating Temperature  -55°C ~ 275°C  Package / Case  6227 J-Lead  Supplier Device Package  Size / Dimension  0.646" L x 0.276" W (16.40mm x 7.00mm)  Height - Seated (Max)  Number of Terminations  2  Failure Rate  -	Tolerance	±1%
Features  Moisture Resistant, Pulse Withstanding  Temperature Coefficient  ±20ppm/°C  Operating Temperature  -55°C ~ 275°C  Package / Case  6227 J-Lead  Supplier Device Package  6227  Size / Dimension  0.646" L x 0.276" W (16.40mm x 7.00mm)  Height - Seated (Max)  Number of Terminations  2  Failure Rate  -	Power (Watts)	3W
Temperature Coefficient ±20ppm/°C  Operating Temperature -55°C ~ 275°C  Package / Case 6227 J-Lead  Supplier Device Package 6227  Size / Dimension 0.646" L x 0.276" W (16.40mm x 7.00mm)  Height - Seated (Max) 0.265" (6.73mm)  Number of Terminations 2  Failure Rate -	Composition	Wirewound
Operating Temperature  -55°C ~ 275°C  Package / Case  6227 J-Lead  Supplier Device Package  6227  Size / Dimension  0.646" L x 0.276" W (16.40mm x 7.00mm)  Height - Seated (Max)  Number of Terminations  2  Failure Rate  -	Features	Moisture Resistant, Pulse Withstanding
Package / Case 6227 J-Lead  Supplier Device Package 6227  Size / Dimension 0.646" L x 0.276" W (16.40mm x 7.00mm)  Height - Seated (Max) 0.265" (6.73mm)  Number of Terminations 2  Failure Rate -	Temperature Coefficient	±20ppm/°C
Supplier Device Package 6227 Size / Dimension 0.646" L x 0.276" W (16.40mm x 7.00mm) Height - Seated (Max) 0.265" (6.73mm) Number of Terminations 2 Failure Rate -	Operating Temperature	-55°C ~ 275°C
Size / Dimension         0.646" L x 0.276" W (16.40mm x 7.00mm)           Height - Seated (Max)         0.265" (6.73mm)           Number of Terminations         2           Failure Rate         -	Package / Case	6227 J-Lead
Height - Seated (Max) 0.265" (6.73mm)  Number of Terminations 2  Failure Rate -	Supplier Device Package	6227
Number of Terminations 2 Failure Rate -	Size / Dimension	0.646" L x 0.276" W (16.40mm x 7.00mm)
Failure Rate -	Height - Seated (Max)	0.265" (6.73mm)
	Number of Terminations	2
Report errors?	Failure Rate	-
		Report errors?

#### SM6227FT143R Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### SM6227FT143R Payment Methods



















### SM6227FT143R Shipping Methods













If you have any question about SM6227FT143R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com