



SMAJ40A M2G Information

Heisener.com

For Reference Only

Part Number SMAJ40A M2G
Manufacturer TSC America Inc.
Category Circuit Protection
TVS - Diodes

Description DIODE, TVS, UNIDIRECTIONAL, 400W

Package DO-214AC, SMA

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SMAJ40A M2G Specifications

Manufacturer Part NumberSMAJ40A M2GManufacturerTSC America Inc.CategoryCircuit ProtectionTVS - DiodesPackageDO-214AC, SMASeriesSMAJTypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)40VVoltage - Breakdown (Min)44.4VVoltage - Clamping (Max) @ Ipp64.5VCurrent - Peak Pulse (10/1000μs)6.2APower - Peak Pulse400WPower Line ProtectionNo
Category Circuit Protection TVS - Diodes Package DO-214AC, SMA Series SMAJ Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 40V Voltage - Breakdown (Min) 44.4V Voltage - Clamping (Max) @ Ipp 64.5V Current - Peak Pulse (10/1000μs) 6.2A Power - Peak Pulse 400W
TVS - Diodes Package DO-214AC, SMA Series SMAJ Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 40V Voltage - Breakdown (Min) 44.4V Voltage - Clamping (Max) @ Ipp 64.5V Current - Peak Pulse (10/1000μs) 6.2A Power - Peak Pulse 400W
Package DO-214AC, SMA Series SMAJ Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 40V Voltage - Breakdown (Min) 44.4V Voltage - Clamping (Max) @ Ipp 64.5V Current - Peak Pulse (10/1000μs) 6.2A Power - Peak Pulse 400W
Series SMAJ Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 40V Voltage - Breakdown (Min) 44.4V Voltage - Clamping (Max) @ Ipp 64.5V Current - Peak Pulse (10/1000μs) 6.2A Power - Peak Pulse 400W
Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 40V Voltage - Breakdown (Min) 44.4V Voltage - Clamping (Max) @ Ipp 64.5V Current - Peak Pulse (10/1000μs) 6.2A Power - Peak Pulse 400W
Unidirectional Channels Bidirectional Channels - Voltage - Reverse Standoff (Typ) 40V Voltage - Breakdown (Min) 44.4V Voltage - Clamping (Max) @ Ipp 64.5V Current - Peak Pulse (10/1000µs) Power - Peak Pulse 400W
Bidirectional Channels Voltage - Reverse Standoff (Typ) Voltage - Breakdown (Min) Voltage - Clamping (Max) @ Ipp 64.5V Current - Peak Pulse (10/1000μs) Power - Peak Pulse 400W
Voltage - Reverse Standoff (Typ) Voltage - Breakdown (Min) Voltage - Clamping (Max) @ Ipp 64.5V Current - Peak Pulse (10/1000μs) Power - Peak Pulse 400W
Voltage - Breakdown (Min) Voltage - Clamping (Max) @ Ipp 64.5V Current - Peak Pulse (10/1000μs) 6.2A Power - Peak Pulse 400W
Voltage - Clamping (Max) @ Ipp 64.5V Current - Peak Pulse (10/1000μs) 6.2A Power - Peak Pulse 400W
Current - Peak Pulse (10/1000µs) 6.2A Power - Peak Pulse 400W
Power - Peak Pulse 400W
Power Line Protection
1 Ower Enic Frocedion
Applications General Purpose
Capacitance @ Frequency -
Operating Temperature $-55^{\circ}\text{C} \sim 150^{\circ}\text{C} \text{ (TJ)}$
Mounting Type Surface Mount
Package / Case DO-214AC, SMA
Supplier Device Package DO-214AC (SMA)
Report errors

SMAJ40A M2G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SMAJ40A M2G Payment Methods



















SMAJ40A M2G Shipping Methods













If you have any question about SMAJ40A M2G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com