



SMAJ8.5A-TP Information



For Reference Only

Part Number SMAJ8.5A-TP

Manufacturer Micro Commercial Co
Category Circuit Protection
TVS - Diodes

Description TVS DIODE 8.5VWM 14.4VC SMA

Package DO-214AC, SMA

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SMAJ8.5A-TP Specifications

Manufacturer Part Number SMAJ8.5A-TP Manufacturer Micro Commercial Co Category Circuit Protection TVS - Diodes Package DO-214AC, SMA Series - Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 8.5V Voltage - Breakdown (Min) 9.44V Voltage - Clamping (Max) @ Ipp 14.4V Current - Peak Pulse (10/1000µs) 27.7A Power - Peak Pulse 400W Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -55°C ~ 175°C (TA) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package DO-214AC (SMA)	•	
Category Circuit Protection TVS - Diodes Package DO-214AC, SMA Series - Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 8.5V Voltage - Breakdown (Min) 9.44V Voltage - Clamping (Max) @ Ipp 14.4V Current - Peak Pulse (10/1000μs) 27.7A Power - Peak Pulse 400W Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -55°C ~ 175°C (TA) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package DO-214AC (SMA)	Manufacturer Part Number	SMAJ8.5A-TP
Package DO-214AC, SMA Series - Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 8.5V Voltage - Breakdown (Min) 9.44V Voltage - Clamping (Max) @ Ipp 14.4V Current - Peak Pulse (10/1000μs) 27.7A Power - Peak Pulse 400W Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -55°C ~ 175°C (TA) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package DO-214AC (SMA)	Manufacturer	Micro Commercial Co
PackageDO-214AC, SMASeries-TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)8.5VVoltage - Breakdown (Min)9.44VVoltage - Clamping (Max) @ Ipp14.4VCurrent - Peak Pulse (10/1000μs)27.7APower - Peak Pulse400WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TA)Mounting TypeSurface MountPackage / CaseDO-214AC, SMASupplier Device PackageDO-214AC (SMA)	Category	Circuit Protection
Series-TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)8.5VVoltage - Breakdown (Min)9.44VVoltage - Clamping (Max) @ Ipp14.4VCurrent - Peak Pulse (10/1000μs)27.7APower - Peak Pulse400WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TA)Mounting TypeSurface MountPackage / CaseDO-214AC, SMASupplier Device PackageDO-214AC (SMA)		TVS - Diodes
Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 8.5V Voltage - Breakdown (Min) 9.44V Voltage - Clamping (Max) @ Ipp 14.4V Current - Peak Pulse (10/1000µs) 27.7A Power - Peak Pulse 400W Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -55°C ~ 175°C (TA) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package	Package	DO-214AC, SMA
Unidirectional Channels Bidirectional Channels Voltage - Reverse Standoff (Typ) Voltage - Breakdown (Min) Voltage - Clamping (Max) @ Ipp 14.4V Current - Peak Pulse (10/1000µs) Power - Peak Pulse 400W Power Line Protection Applications General Purpose Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TA) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package	Series	-
Bidirectional Channels Voltage - Reverse Standoff (Typ) 8.5V Voltage - Breakdown (Min) 9.44V Voltage - Clamping (Max) @ Ipp 14.4V Current - Peak Pulse (10/1000μs) 27.7A Power - Peak Pulse 400W Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TA) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package	Туре	Zener
Voltage - Reverse Standoff (Typ) Voltage - Breakdown (Min) 9.44V Voltage - Clamping (Max) @ Ipp 14.4V Current - Peak Pulse (10/1000µs) Power - Peak Pulse 400W Power Line Protection Applications General Purpose Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TA) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package	Unidirectional Channels	1
Voltage - Breakdown (Min) Voltage - Clamping (Max) @ Ipp 14.4V Current - Peak Pulse (10/1000μs) Power - Peak Pulse 400W Power Line Protection Applications General Purpose Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TA) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package	Bidirectional Channels	-
Voltage - Clamping (Max) @ Ipp 14.4V Current - Peak Pulse (10/1000μs) 27.7A Power - Peak Pulse 400W Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TA) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package	Voltage - Reverse Standoff (Typ)	8.5V
Current - Peak Pulse (10/1000μs)27.7APower - Peak Pulse400WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TA)Mounting TypeSurface MountPackage / CaseDO-214AC, SMASupplier Device PackageDO-214AC (SMA)	Voltage - Breakdown (Min)	9.44V
Power - Peak Pulse 400W Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -55°C ~ 175°C (TA) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package DO-214AC (SMA)	Voltage - Clamping (Max) @ Ipp	14.4V
Power Line Protection Applications General Purpose Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TA) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package DO-214AC (SMA)	Current - Peak Pulse (10/1000µs)	27.7A
Applications Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TA) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package DO-214AC (SMA)	Power - Peak Pulse	400W
Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TA) Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package DO-214AC (SMA)	Power Line Protection	No
Operating Temperature-55°C ~ 175°C (TA)Mounting TypeSurface MountPackage / CaseDO-214AC, SMASupplier Device PackageDO-214AC (SMA)	Applications	General Purpose
Mounting Type Surface Mount Package / Case DO-214AC, SMA Supplier Device Package DO-214AC (SMA)	Capacitance @ Frequency	-
Package / Case DO-214AC, SMA Supplier Device Package DO-214AC (SMA)	Operating Temperature	-55°C ~ 175°C (TA)
Supplier Device Package DO-214AC (SMA)	Mounting Type	Surface Mount
••	Package / Case	DO-214AC, SMA
Report errors?	Supplier Device Package	DO-214AC (SMA)
		Report errors?

SMAJ8.5A-TP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SMAJ8.5A-TP Payment Methods





















SMAJ8.5A-TP Shipping Methods













If you have any question about SMAJ8.5A-TP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com