

SMBD7000E6327HTSA1

SMBD7000E6327HTSA1 Information



For Reference Only

Part Number	SMBD7000E6327HTSA1	
Manufacturer	Infineon Technologies	
Category	Discrete Semiconductor Products Diodes - Rectifiers - Arrays	
Description	DIODE ARRAY GP 100V 200MA SOT23	
Package	TO-236-3, SC-59, SOT-23-3	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SMBD7000E6327HTSA1 Specifications

Manufacturer Part NumberSMBD7000E6327HTSA1ManufacturerInfineon TechnologiesCategoryDiscrete Semiconductor ProductsDodes - Rectifiers - ArraysDodes - Rectifiers - ArraysPackageTO-236-3, SC-59, SOT-23-3Series-Diode Configuration1 Pair Series ConnectionDiode Configuration100VCurrent - Average Rectified (Io) (per Diode)200mA (DC)Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any SpeedReverse Recovery Time (trr)4nsOperating Temperature - Junction150°C (Max)Mounting TypeSurface MountPackage / CaseCorcas.Package / CaseCorcas. <th></th> <th></th>		
CategoryDiscrete Semiconductor ProductsPackageDiodes - Rectifiers - ArraysPackageTO-236-3, SC-59, SOT-23-3Series-Diode Configuration1 Pair Series ConnectionDiode TypeStandardVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io) (per Diode)200mA (DC)Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any Speed	Manufacturer Part Number	SMBD7000E6327HTSA1
Diodes - Rectifiers - ArraysPackageTO-236-3, SC-59, SOT-23-3Series-Diode Configuration1 Pair Series ConnectionDiode TypeStandardVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io) (per Diode)200mA (DC)Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any Speed	Manufacturer	Infineon Technologies
PackageTO-236-3, SC-59, SOT-23-3Series-Diode Configuration1 Pair Series ConnectionDiode TypeStandardVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io) (per Diode)200mA (DC)Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any Speed	Category	Discrete Semiconductor Products
Series-Diode Configuration1 Pair Series ConnectionDiode TypeStandardVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io) (per Diode)200mA (DC)Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any Speed		Diodes - Rectifiers - Arrays
Diode Configuration1 Pair Series ConnectionDiode TypeStandardVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io) (per Diode)200mA (DC)Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any Speed	Package	TO-236-3, SC-59, SOT-23-3
Diode Type Standard Diode Type Standard Voltage - DC Reverse (Vr) (Max) 100V Current - Average Rectified (Io) (per Diode) 200mA (DC) Voltage - Forward (Vf) (Max) @ If 1.25V @ 150mA Speed Small Signal =< 200mA (Io), Any Speed	Series	-
Voltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io) (per Diode)200mA (DC)Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any Speed	Diode Configuration	1 Pair Series Connection
Current - Average Rectified (Io) (per Diode)200mA (DC)Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any Speed	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If1.25V @ 150mASpeedSmall Signal =< 200mA (Io), Any Speed	Voltage - DC Reverse (Vr) (Max)	100V
SpeedSmall Signal =< 200mA (Io), Any SpeedReverse Recovery Time (trr)4nsCurrent - Reverse Leakage @ Vr500nA @ 100VOperating Temperature - Junction150°C (Max)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackagePG-SOT23-3	Current - Average Rectified (Io) (per Diode)	200mA (DC)
Reverse Recovery Time (trr)4nsCurrent - Reverse Leakage @ Vr500nA @ 100VOperating Temperature - Junction150°C (Max)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackagePG-SOT23-3	Voltage - Forward (Vf) (Max) @ If	1.25V @ 150mA
Current - Reverse Leakage @ Vr500nA @ 100VOperating Temperature - Junction150°C (Max)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackagePG-SOT23-3	Speed	Small Signal =< 200mA (Io), Any Speed
Operating Temperature - Junction150°C (Max)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackagePG-SOT23-3	Reverse Recovery Time (trr)	4ns
Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackagePG-SOT23-3	Current - Reverse Leakage @ Vr	500nA @ 100V
Package / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackagePG-SOT23-3	Operating Temperature - Junction	150°C (Max)
Supplier Device Package PG-SOT23-3	Mounting Type	Surface Mount
	Package / Case	TO-236-3, SC-59, SOT-23-3
Depart emers	Supplier Device Package	PG-SOT23-3
Keport errors		Report errors?

SMBD7000E6327HTSA1 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SMBD7000E6327HTSA1 Payment Methods



If you have any question about SMBD7000E6327HTSA1, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com