



SMBJ9.0CA-TP Information



For Reference Only

Part Number SMBJ9.0CA-TP

ManufacturerMicro Commercial CoCategoryCircuit Protection

TVS - Diodes

Description TVS DIODE 9VWM 15.4VC SMB

Package DO-214AA, SMB

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SMBJ9.0CA-TP Specifications

Manufacturer Part Number SMBJ9.0CA-TP Manufacturer Micro Commercial Co Category Circuit Protection TVS - Diodes Package DO-214AA, SMB Series - Type Zener Unidirectional Channels - Bidirectional Channels 1 Voltage - Reverse Standoff (Typ) 9V Voltage - Breakdown (Min) 10V Voltage - Clamping (Max) @ Ipp 15.4V Current - Peak Pulse (10/1000µs) 39A Power - Peak Pulse 600W Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Surface Mount Package / Case DO-214AA, SMB Supplier Device Package DO-214AA (SMB)	•	
Category Circuit Protection TVS - Diodes Package DO-214AA, SMB Series - Type Zener Unidirectional Channels Indirectional Channels Indire	Manufacturer Part Number	SMBJ9.0CA-TP
Package DO-214AA, SMB Series - Type Zener Unidirectional Channels - Bidirectional Channels 1 Voltage - Reverse Standoff (Typ) 9V Voltage - Breakdown (Min) 10V Voltage - Clamping (Max) @ Ipp 15.4V Current - Peak Pulse (10/1000μs) 39A Power - Peak Pulse 600W Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Surface Mount Package / Case DO-214AA, SMB Supplier Device Package DO-214AA (SMB)	Manufacturer	Micro Commercial Co
PackageDO-214AA, SMBSeries-TypeZenerUnidirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)9VVoltage - Breakdown (Min)10VVoltage - Clamping (Max) @ Ipp15.4VCurrent - Peak Pulse (10/1000μs)39APower - Peak Pulse600WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)	Category	Circuit Protection
Series-TypeZenerUnidirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)9VVoltage - Breakdown (Min)10VVoltage - Clamping (Max) @ Ipp15.4VCurrent - Peak Pulse (10/1000μs)39APower - Peak Pulse600WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)		TVS - Diodes
TypeZenerUnidirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)9VVoltage - Breakdown (Min)10VVoltage - Clamping (Max) @ Ipp15.4VCurrent - Peak Pulse (10/1000μs)39APower - Peak Pulse600WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)	Package	DO-214AA, SMB
Unidirectional Channels Bidirectional Channels 1 Voltage - Reverse Standoff (Typ) 9V Voltage - Breakdown (Min) 10V Voltage - Clamping (Max) @ Ipp 15.4V Current - Peak Pulse (10/1000µs) 39A Power - Peak Pulse 600W Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Surface Mount Package / Case DO-214AA, SMB Supplier Device Package	Series	-
Bidirectional Channels1Voltage - Reverse Standoff (Typ)9VVoltage - Breakdown (Min)10VVoltage - Clamping (Max) @ Ipp15.4VCurrent - Peak Pulse (10/1000μs)39APower - Peak Pulse600WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)	Туре	Zener
Voltage - Reverse Standoff (Typ) Voltage - Breakdown (Min) 10V Voltage - Clamping (Max) @ Ipp 15.4V Current - Peak Pulse (10/1000µs) Power - Peak Pulse 600W Power Line Protection Applications General Purpose Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Surface Mount Package / Case DO-214AA, SMB Supplier Device Package	Unidirectional Channels	-
Voltage - Breakdown (Min) Voltage - Clamping (Max) @ Ipp 15.4V Current - Peak Pulse (10/1000μs) Power - Peak Pulse 600W Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Surface Mount Package / Case DO-214AA, SMB Supplier Device Package	Bidirectional Channels	1
Voltage - Clamping (Max) @ Ipp Current - Peak Pulse (10/1000μs) Power - Peak Pulse 600W Power Line Protection Applications Capacitance @ Frequency Operating Temperature Mounting Type Surface Mount Package / Case Supplier Device Package 15.4V 15.4V 16.4V	Voltage - Reverse Standoff (Typ)	9V
Current - Peak Pulse (10/1000µs) Power - Peak Pulse 600W Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Surface Mount Package / Case DO-214AA, SMB Supplier Device Package	Voltage - Breakdown (Min)	10V
Power - Peak Pulse 600W Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Surface Mount Package / Case DO-214AA, SMB Supplier Device Package DO-214AA (SMB)	Voltage - Clamping (Max) @ Ipp	15.4V
Power Line Protection Applications General Purpose Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Surface Mount Package / Case DO-214AA, SMB Supplier Device Package DO-214AA (SMB)	Current - Peak Pulse (10/1000µs)	39A
Applications Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Surface Mount Package / Case DO-214AA, SMB Supplier Device Package DO-214AA (SMB)	Power - Peak Pulse	600W
Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Surface Mount Package / Case DO-214AA, SMB Supplier Device Package DO-214AA (SMB)	Power Line Protection	No
Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Surface Mount Package / Case DO-214AA, SMB Supplier Device Package DO-214AA (SMB)	Applications	General Purpose
Mounting TypeSurface MountPackage / CaseDO-214AA, SMBSupplier Device PackageDO-214AA (SMB)	Capacitance @ Frequency	-
Package / Case DO-214AA, SMB Supplier Device Package DO-214AA (SMB)	Operating Temperature	-55°C ~ 175°C (TJ)
Supplier Device Package DO-214AA (SMB)	Mounting Type	Surface Mount
••	Package / Case	DO-214AA, SMB
Report errors?	Supplier Device Package	DO-214AA (SMB)
		Report errors?

SMBJ9.0CA-TP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SMBJ9.0CA-TP Payment Methods



















SMBJ9.0CA-TP Shipping Methods













If you have any question about SMBJ9.0CA-TP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com