

SMD1210P005TSA

SMD1210P005TSA Information

Heisener.com	Part Number Manufacturer Category Description Package	SMD1210P005TSA Littelfuse Inc. Circuit Protection PTC Resettable Fuses FUSE RESETTABLE 50MA 30V 1210 1210 (3225 Metric), Concave For the pricing/inventory/lead time, please contact		
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Qu	iote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SMD1210P005TSA Specifications

ManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackage1210 (3225 Metric), ConcavePackagePOLY-FUSE?, SMD1210StriesPOLY-FUSE?, SMD1210TypePolymericVoltage - Max30VCurrent - Max10ACurrent - Hold (Ih) (Max)50mACurrent - Trip (It)150mATime to Trip1.5sResistance - Post Trip (R1) (Max)50 OhmsResistance - 25°C (Typ)-Operating Temperature40°C ~ 85°CRatings-Mounting TypeSurface MountPackage / Case1210 (3225 Metric), ConcaveSize / Dimension0.127" L x 0.102" W (3.22mm x 2.58mm)Height - Seated (Max)-Lead Spacing-Lead Spacing-		
CategoryCircuit ProtectionPCR Resettable FusesPackage1210 (3225 Metric), ConcaveSeriesPOLY-FUSE?, SMD1210TypePolymericVoltage - Max30VCurrent - Max10ACurrent - Hold (lh) (Max)50mACurrent - Trip (lt)150mATime to Trip1.5sResistance - Initial (Ri) (Min)36 OhmsResistance - Post Trip (R1) (Max)50 OhmsOperating Temperature-Adorc ~ 85°C-Ratings-Mounting TypeSurface MountPackage / Case1210 (3225 Metric), ConcaveSize / Dimension0.127" L x 0.102" W (3.22mm x 2.58mm)Height - Seated (Max)-Thickness (Max)0.039" (1.00mm)Lead Spacing-	Manufacturer Part Number	SMD1210P005TSA
PTC Resettable Fuses Package 1210 (3225 Metric), Concave Series POLY-FUSE?, SMD1210 Type Polymeric Voltage - Max 30V Current - Max 10A Current - Hold (Ih) (Max) 50mA Current - Trip (It) 150mA Time to Trip 1.5s Resistance - Initial (Ri) (Min) 36 Ohms Resistance - Post Trip (R1) (Max) 50 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1210 (3225 Metric), Concave Size / Dimension 0.127" L x 0.102" W (3.22mm x 2.58mm) Height - Seated (Max) - Thickness (Max) 0.39" (1.00mm)	Manufacturer	Littelfuse Inc.
Package1210 (3225 Metric), ConcaveSeriesPOLY-FUSE?, SMD1210TypePolymericVoltage - Max30VCurrent - Max10ACurrent - Max10ACurrent - Trip (It)50mACurrent - Trip (It)150mAResistance - Initial (Ri) (Min)36 OhmsResistance - Post Trip (R1) (Max)50 OhmsResistance - 25°C (Typ)-Operating Temperature-Nounting TypeSurface MountPackage / Case1210 (3225 Metric), ConcaveSize / Dimension0.127" L x 0.102" W (3.22mm x 2.58mm)Height - Seated (Max)-Thickness (Max)0.039" (1.00mm)Lead Spacing-	Category	Circuit Protection
Norm POLY-FUSE?, SMD1210 Type Polymeric Voltage - Max 30V Current - Max 10A Current - Mol (Ih) (Max) 50mA Current - Trip (It) 150mA Time to Trip 1.5s Resistance - Initial (Ri) (Min) 3.6 Ohms Resistance - Post Trip (R1) (Max) 50 Ohms Operating Temperature -40°C ~ 85°C Ratings - Nounting Type Surface Mount Package / Case 1210 (3225 Metric), Concave Size / Dimension 0.127" L x 0.102" W (3.22mm x 2.58mm) Height - Seated (Max) - Height - Seated (Max) - Lead Spacing -		PTC Resettable Fuses
Type Polymeric Voltage - Max 30V Current - Max 10A Current - Mol (lh) (Max) 50mA Current - Trip (It) 150mA Time to Trip 1.5s Resistance - Initial (Ri) (Min) 3.6 Ohms Resistance - Post Trip (R1) (Max) 50 Ohms Resistance - So ^o (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Nounting Type Surface Mount Package / Case 1210 (3225 Metric), Concave Size / Dimension 0.127" L x 0.102" W (3.22mm x 2.58mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm)	Package	1210 (3225 Metric), Concave
Voltage - Max 30V Current - Max 10A Current - Hold (Ih) (Max) 50mA Current - Trip (It) 150mA Time to Trip 1.5s Resistance - Initial (Ri) (Min) 3.6 Ohms Resistance - Post Trip (R1) (Max) 50 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1210 (3225 Metric), Concave Size / Dimension 0.127" L x 0.102" W (3.22mm x 2.58mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm)	Series	POLY-FUSE?, SMD1210
Current - Max 10A Current - Hold (Ih) (Max) 50mA Current - Trip (It) 150mA Time to Trip 1.5s Resistance - Initial (Ri) (Min) 3.6 Ohms Resistance - Post Trip (R1) (Max) 50 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1210 (3225 Metric), Concave Size / Dimension 0.127" L x 0.102" W (3.22mm x 2.58mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm)	Туре	Polymeric
Current - Hold (lh) (Max)50mACurrent - Trip (It)150mATime to Trip1.5sResistance - Initial (Ri) (Min)3.6 OhmsResistance - Post Trip (R1) (Max)50 OhmsResistance - 25°C (Typ)-Operating Temperature-40°C ~ 85°CRatings-Mounting TypeSurface MountPackage / Case1210 (3225 Metric), ConcaveSize / Dimension0.127" L x 0.102" W (3.22mm x 2.58mm)Height - Seated (Max)-Lead Spacing-	Voltage - Max	30V
Current - Trip (It)150mATime to Trip1.5sResistance - Initial (Ri) (Min)3.6 OhmsResistance - Post Trip (R1) (Max)50 OhmsResistance - 25°C (Typ)-Operating Temperature-40°C ~ 85°CRatings-Mounting TypeSurface MountPackage / Case1210 (3225 Metric), ConcaveSize / Dimension0.127" L x 0.102" W (3.22mm x 2.58mm)Height - Seated (Max)-Thickness (Max)0.039" (1.00mm)Lead Spacing-	Current - Max	10A
Time to Trip1.5sResistance - Initial (Ri) (Min)3.6 OhmsResistance - Post Trip (R1) (Max)50 OhmsResistance - 25°C (Typ)-Operating Temperature-40°C ~ 85°CRatings-Mounting TypeSurface MountPackage / Case1210 (3225 Metric), ConcaveSize / Dimension0.127" L x 0.102" W (3.22mm x 2.58mm)Height - Seated (Max)-Thickness (Max)0.039" (1.00mm)Lead Spacing-	Current - Hold (Ih) (Max)	50mA
Resistance - Initial (Ri) (Min)3.6 OhmsResistance - Post Trip (R1) (Max)50 OhmsResistance - 25°C (Typ)-Operating Temperature-40°C ~ 85°CRatings-Mounting TypeSurface MountPackage / Case1210 (3225 Metric), ConcaveSize / Dimension0.127" L x 0.102" W (3.22mm x 2.58mm)Height - Seated (Max)-Thickness (Max)0.039" (1.00mm)Lead Spacing-	Current - Trip (It)	150mA
Resistance - Post Trip (R1) (Max)50 OhmsResistance - 25°C (Typ)-Operating Temperature-40°C ~ 85°CRatings-Mounting TypeSurface MountPackage / Case1210 (3225 Metric), ConcaveSize / Dimension0.127" L x 0.102" W (3.22mm x 2.58mm)Height - Seated (Max)-Thickness (Max)0.039" (1.00mm)Lead Spacing-	Time to Trip	1.5s
Resistance - 25°C (Typ)-Operating Temperature-40°C ~ 85°CRatings-Mounting TypeSurface MountPackage / Case1210 (3225 Metric), ConcaveSize / Dimension0.127" L x 0.102" W (3.22mm x 2.58mm)Height - Seated (Max)-Thickness (Max)0.039" (1.00mm)Lead Spacing-	Resistance - Initial (Ri) (Min)	3.6 Ohms
Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1210 (3225 Metric), Concave Size / Dimension 0.127" L x 0.102" W (3.22mm x 2.58mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Resistance - Post Trip (R1) (Max)	50 Ohms
Ratings-Mounting TypeSurface MountPackage / Case1210 (3225 Metric), ConcaveSize / Dimension0.127" L x 0.102" W (3.22mm x 2.58mm)Height - Seated (Max)-Thickness (Max)0.039" (1.00mm)Lead Spacing-	Resistance - 25°C (Typ)	-
Mounting TypeSurface MountPackage / Case1210 (3225 Metric), ConcaveSize / Dimension0.127" L x 0.102" W (3.22mm x 2.58mm)Height - Seated (Max)-Thickness (Max)0.039" (1.00mm)Lead Spacing-	Operating Temperature	-40°C ~ 85°C
Package / Case 1210 (3225 Metric), Concave Size / Dimension 0.127" L x 0.102" W (3.22mm x 2.58mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Ratings	-
Size / Dimension 0.127" L x 0.102" W (3.22mm x 2.58mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Mounting Type	Surface Mount
Height - Seated (Max)-Thickness (Max)0.039" (1.00mm)Lead Spacing-	Package / Case	1210 (3225 Metric), Concave
Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Size / Dimension	0.127" L x 0.102" W (3.22mm x 2.58mm)
Lead Spacing -	Height - Seated (Max)	-
	Thickness (Max)	0.039" (1.00mm)
	Lead Spacing	-
Report errors?		Report error

SMD1210P005TSA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SMD1210P005TSA Payment Methods





If you have any question about SMD1210P005TSA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com