



SMD7FRA121 Information

Heisener.com

Part Number SMD7FRA121 Manufacturer Switchcraft Inc.

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 7POS TH RA SKT MIN DIN

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SMD7FRA121 Specifications

Manufacturer Part NumberSMD7FRA121ManufacturerSwitchcraft Inc.CategoryConnectors, InterconnectsPackage-SeriesSMDConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - InsertMini DINShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishCopper, Nickel PlatedContact FinishSilverFeaturesShieldedVoltage - Rated100VAC, 12VDCCurrent Rating1A, 2AReport errors?		
CategoryConnectors, InterconnectsPackage-SeriesSMDConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - InsertMini DINShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishCopper, Nickel PlatedContact FinishSilverFeaturesShieldedVoltage - Rated100VAC, 12VDCCurrent Rating1A, 2A	Manufacturer Part Number	SMD7FRA121
PackageCircular ConnectorsSeriesSMDConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - InsertMini DINShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishCopper, Nickel PlatedContact FinishSilverFeaturesShieldedVoltage - Rated100VAC, 12VDCCurrent Rating1A, 2A	Manufacturer	Switchcraft Inc.
Package-SeriesSMDConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - InsertMini DINShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishCopper, Nickel PlatedContact FinishSilverFeaturesShieldedVoltage - Rated100VAC, 12VDCCurrent Rating1A, 2A	Category	Connectors, Interconnects
SeriesSMDConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - InsertMini DINShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishCopper, Nickel PlatedContact FinishSilverFeaturesShieldedVoltage - Rated100VAC, 12VDCCurrent Rating1A, 2A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - InsertMini DINShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishCopper, Nickel PlatedContact FinishSilverFeaturesShieldedVoltage - Rated100VAC, 12VDCCurrent Rating1A, 2A	Package	-
Number of Positions7Shell Size - InsertMini DINShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishCopper, Nickel PlatedContact FinishSilverFeaturesShieldedVoltage - Rated100VAC, 12VDCCurrent Rating1A, 2A	Series	SMD
Shell Size - Insert Shell Size, MIL	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection - Shell Material, Finish Copper, Nickel Plated Contact Finish Silver Features Shielded Voltage - Rated 100VAC, 12VDC Current Rating 1 A 2A	Number of Positions	7
Mounting Type Termination Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection Shell Material, Finish Contact Finish Silver Features Shielded Voltage - Rated Ingress Attention Ingress Protection Shell Material Shielded Voltage - Rated Ingress Protection Shielded Ingress Protection Silver Shielded	Shell Size - Insert	Mini DIN
Termination Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection - Shell Material, Finish Copper, Nickel Plated Contact Finish Silver Features Shielded Voltage - Rated 100VAC, 12VDC Current Rating 1A, 2A	Shell Size, MIL	-
Fastening Type Push-Pull Orientation Keyed Ingress Protection - Shell Material, Finish Copper, Nickel Plated Contact Finish Silver Features Shielded Voltage - Rated 100VAC, 12VDC Current Rating 1A, 2A	Mounting Type	Through Hole, Right Angle
Orientation Keyed Ingress Protection - Shell Material, Finish Copper, Nickel Plated Contact Finish Silver Features Shielded Voltage - Rated 100VAC, 12VDC Current Rating 1A, 2A	Termination	Solder
Ingress Protection - Shell Material, Finish Copper, Nickel Plated Contact Finish Silver Features Shielded Voltage - Rated 100VAC, 12VDC Current Rating 1A, 2A	Fastening Type	Push-Pull
Shell Material, Finish Copper, Nickel Plated Contact Finish Silver Features Shielded Voltage - Rated 100VAC, 12VDC Current Rating 1A, 2A	Orientation	Keyed
Contact Finish Silver Features Shielded Voltage - Rated 100VAC, 12VDC Current Rating 1A, 2A	Ingress Protection	-
Features Shielded Voltage - Rated 100VAC, 12VDC Current Rating 1A, 2A	Shell Material, Finish	Copper, Nickel Plated
Voltage - Rated 100VAC, 12VDC Current Rating 1A, 2A	Contact Finish	Silver
Current Rating 1A, 2A	Features	Shielded
	Voltage - Rated	100VAC, 12VDC
Report errors?	Current Rating	1A, 2A
		Report errors?

SMD7FRA121 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SMD7FRA121 Payment Methods





















SMD7FRA121 Shipping Methods













If you have any question about SMD7FRA121, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com