

SMDJ30

SMDJ30 Information



Part Number	SMDJ30
Manufacturer	Littelfuse Inc.
Category	Circuit Protection TVS - Diodes
Description	TVS DIODE 30VWM 50.82VC SMD
Package	DO-214AB, SMC
	For the pricing/inventory/lead time, please contact
	us
	Website: https://www.heisener.com
	E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality


Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SMDJ30 Specifications

Manufacturer Part NumberSMD30ManufacturerLittelfuse Inc.CategoryCircuit ProtectionTVS - DiodesTVS - DiodesPackageDO-214AB, SMCSeriesSMDJTypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)30VVoltage - Breakdown (Min)31.55VVoltage - Clamping (Max) @ Ipp50.82VCurrent - Peak Pulse (10/1000µs)3000W (3kW)
CategoryCircuit ProtectionTVS - DiodesPackageDO-214AB, SMCSeriesSMDJTypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)30VVoltage - Breakdown (Min)31.55VVoltage - Clamping (Max) @ Ipp50.82VCurrent - Peak Pulse (10/100µs)62A
TVS - DiodesPackageDO-214AB, SMCSeriesSMDJTypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)30VVoltage - Breakdown (Min)50.82VVoltage - Clamping (Max) @ Ipp62A
PackageDO-214AB, SMCSeriesSMDJTypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)30VVoltage - Breakdown (Min)51.55VVoltage - Clamping (Max) @ Ipp50.82VCurrent - Peak Pulse (10/100µs)62A
SeriesSMDJTypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)30VVoltage - Breakdown (Min)31.55VVoltage - Clamping (Max) @ Ipp50.82VCurrent - Peak Pulse (10/1000µs)62A
TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)30VVoltage - Breakdown (Min)31.55VVoltage - Clamping (Max) @ Ipp50.82VCurrent - Peak Pulse (10/100µs)62A
MIUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)30VVoltage - Breakdown (Min)31.55VVoltage - Clamping (Max) @ Ipp50.82VCurrent - Peak Pulse (10/1000µs)62A
Bidirectional Channels-Voltage - Reverse Standoff (Typ)30VVoltage - Breakdown (Min)31.55VVoltage - Clamping (Max) @ Ipp50.82VCurrent - Peak Pulse (10/1000µs)62A
Voltage - Reverse Standoff (Typ)30VVoltage - Breakdown (Min)31.55VVoltage - Clamping (Max) @ Ipp50.82VCurrent - Peak Pulse (10/1000µs)62A
Voltage - Breakdown (Min)31.55VVoltage - Clamping (Max) @ Ipp50.82VCurrent - Peak Pulse (10/1000µs)62A
Voltage - Clamping (Max) @ Ipp 50.82V Current - Peak Pulse (10/1000µs) 62A
Current - Peak Pulse (10/1000µs) 62A
Power - Peak Pulse 3000W (3kW)
Power Line Protection No
Applications General Purpose
Capacitance @ Frequency -
Operating Temperature $-65^{\circ}C \sim 150^{\circ}C (TJ)$
Mounting Type Surface Mount
Package / Case DO-214AB, SMC
Supplier Device Package DO-214AB (SMCJ)
Report er

SMDJ30 Guarantees





If you have any question about SMDJ30, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com