

SMF15A-TP

SMF15A-TP Information





Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SMF15A-TP Specifications

Manufacturer Part NumberSMF15A-TPManufacturerMicro Commercial CoCategoryCircuit ProtectionTVS - DiodesPackageSOD-123FSeries-TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)15VVoltage - Clamping (Max) @ Ipp34.4VVoltage - Clamping (Max) @ Ipp200WPower - Peak Pulse (10/1000µs)8.2APower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature65°C ~ 175°C (TA)Mounting TypeSuD-123F	
CategoryCircuit ProtectionCategoryTVS - DiodesPackageSOD-123FPackage-Series-TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)15VVoltage - Breakdown (Min)16.7VVoltage - Clamping (Max) @ Ipp24.4VCurrent - Peak Pulse (10/1000µs)8.2APower - Peak Pulse200WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-<	
TVS - DiodesPackageSOD-123FSeries-TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)15VVoltage - Breakdown (Min)16.7VVoltage - Clamping (Max) @ Ipp24.4VCurrent - Peak Pulse (10/100µs)8.2APower - Peak Pulse200WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature.5°C ~ 175°C (TA)Mounting TypeSurface Mout	
PackageSOD-123FSeries-TypeZenerUndirectional Channels1Bidrectional Channels-Voltage - Reverse Standoff (Typ)5VVoltage - Breakdown (Min)16.7VVoltage - Clamping (Max) @ Ipp24.4VPower - Peak Pulse200WPower Jenek PulseSonApplicationsGeneral PurposeApplications-Operating Temperature-Mounting TypeSuface Mount	
Series - Stripe Zener Type I Undirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 55V Voltage - Breakdown (Min) 16.7V Voltage - Clamping (Max) @ Ipp 24.4V Current - Peak Pulse (10/100µs) 8.2A Power - Peak Pulse 200W Applications General Purpose Applications General Purpose Operating Temperature - Mounting Type Sufface Mount	
TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)15VVoltage - Breakdown (Min)16.7VVoltage - Clamping (Max) @ Ipp24.4VCurrent - Peak Pulse (10/1000µs)8.2APower - Peak Pulse00WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Type65°C ~ 175°C (TA)Mounting TypeSurface Mount	
Image: Antiperiod of the section of	
Bidirectional Channels-Bidirectional Channels-Voltage - Reverse Standoff (Typ)15VVoltage - Breakdown (Min)16.7VVoltage - Clamping (Max) @ Ipp24.4VCurrent - Peak Pulse (10/100µs)8.2APower - Peak Pulse200WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature65°C ~ 175°C (TA)Mounting TypeSurface Mont	
Voltage - Reverse Standoff (Typ)15VVoltage - Breakdown (Min)16.7VVoltage - Clamping (Max) @ Ipp24.4VCurrent - Peak Pulse (10/1000µs)8.2APower - Peak Pulse (10/1000µs)200WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature65°C ~ 175°C (TA)Mounting TypeSurface Mount	
Voltage - Breakdown (Min)16.7VVoltage - Clamping (Max) @ Ipp24.4VCurrent - Peak Pulse (10/1000µs)8.2APower - Peak Pulse200WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~175°C (TA)Mounting TypeSurface Mount	
Voltage - Clamping (Max) @ Ipp 24.4V Current - Peak Pulse (10/1000µs) 8.2A Power - Peak Pulse 200W Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -65°C ~175°C (TA) Mounting Type Surface Mount	
Current - Peak Pulse (10/1000µs)8.2APower - Peak Pulse200WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TA)Mounting TypeSurface Mount	
Power - Peak Pulse200WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~175°C (TA)Mounting TypeSurface Mount	
Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TA)Mounting TypeSurface Mount	
ApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TA)Mounting TypeSurface Mount	
Capacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TA)Mounting TypeSurface Mount	
Operating Temperature-65°C ~ 175°C (TA)Mounting TypeSurface Mount	
Mounting Type Surface Mount	
Package / Case SOD-123F	
Supplier Device Package SOD-123FL	
Report	rt errors?

SMF15A-TP Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE TARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SMF15A-TP Payment Methods Image: Im

If you have any question about SMF15A-TP, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com