



SMI18-24-B-ST Information

Heisener.com

Part Number SMI18-24-B-ST

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SMI18-24-B-ST Specifications

Manufacturer Part NumberSM118-24-B-STManufacturerCUI Inc.CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesSMI18Region UtilizedUnited KingdomFormWall MountInput TypeMulti-Blade (Included)Voltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)800mAPower (Watts)19.2WNo Load Power Consumption100mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature0°C ~ 40°COutput ConnectorStripped, Tinned Wire LeadsSize / Dimension2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)			
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series SMI18 Region Utilized United Kingdom Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 800mA Power (Watts) 19.2W No Load Power Consumption 100mW (Max) Polarization - Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Stripped, Tinned Wire Leads Size / Dimension Package - SMI18 Region (Off-Board) Adapters - ACD C Desktop, Wall Adapters - ACD C Desktop - ACD C Desktop	Manufacturer Part Number	SMI18-24-B-ST	
Package - Series SMI18 Region Utilized United Kingdom Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 800mA Power (Watts) 19.2W No Load Power Consumption 100mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Stripped, Tinned Wire Leads Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Manufacturer	CUI Inc.	
Package - Series SMI18 Region Utilized United Kingdom Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 800mA Power (Watts) 19.2W No Load Power Consumption 100mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Stripped, Tinned Wire Leads Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Category	Power Supplies - External/Internal (Off-Board)	
SeriesSMI18Region UtilizedUnited KingdomFormWall MountInput TypeMulti-Blade (Included)Voltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)800mAPower (Watts)19.2WNo Load Power Consumption100mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature0°C ~ 40°COutput ConnectorStripped, Tinned Wire LeadsSize / Dimension2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)		AC DC Desktop, Wall Adapters	
Region Utilized Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 800mA Power (Watts) 19.2W No Load Power Consumption 100mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Stripped, Tinned Wire Leads Size / Dimension United Kingdom Wall Mount 100mW Multi-Blade (Included) 90 ~ 264 VAC 40 VAC Current - Output (Max) 19.2W 100mW 1	Package	-	
Form Wall Mount Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 800mA Power (Watts) 19.2W No Load Power Consumption 100mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Stripped, Tinned Wire Leads Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Series	SMI18	
Input Type Multi-Blade (Included) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 800mA Power (Watts) 19.2W No Load Power Consumption 100mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Stripped, Tinned Wire Leads Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Region Utilized	United Kingdom	
Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 800mA Power (Watts) 19.2W No Load Power Consumption 100mW (Max) Polarization - Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Stripped, Tinned Wire Leads Size / Dimension 90 ~ 264 VAC 24V 24V Current - Output (Max) 19.2W 100mW (Max) - Commercial) Level VI, CoC Tier 2 0°C ~ 40°C Output Connector Stripped, Tinned Wire Leads Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Form	Wall Mount	
Voltage - Output (Max) 800mA Power (Watts) 19.2W No Load Power Consumption 100mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Stripped, Tinned Wire Leads Size / Dimension 2.4V 800mA 19.2W 100mW (Max) 100m	Input Type	Multi-Blade (Included)	
Current - Output (Max) Power (Watts) 19.2W No Load Power Consumption 100mW (Max) Polarization Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Stripped, Tinned Wire Leads Size / Dimension 800mA 100mW 10	Voltage - Input	90 ~ 264 VAC	
Power (Watts) 19.2W No Load Power Consumption 100mW (Max) Polarization Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Stripped, Tinned Wire Leads Size / Dimension 19.2W 100mW (Max)	Voltage - Output	24V	
No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature O°C ~ 40°C Output Connector Stripped, Tinned Wire Leads Size / Dimension 100mW (Max) Loud Max Fix (Commercial) Level VI, CoC Tier 2 O°C ~ 40°C Output Connector Stripped, Tinned Wire Leads Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Current - Output (Max)	800mA	
Polarization - Applications ITE (Commercial) Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 40°C Output Connector Stripped, Tinned Wire Leads Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Power (Watts)	19.2W	
ApplicationsITE (Commercial)EfficiencyLevel VI, CoC Tier 2Operating Temperature 0° C $\sim 40^{\circ}$ COutput ConnectorStripped, Tinned Wire LeadsSize / Dimension 2.95 " L x 1.41 " W x 2.58 " H (75.0 mm x 35.8 mm x 65.6 mm)	No Load Power Consumption	100mW (Max)	
Efficiency Level VI, CoC Tier 2 Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Stripped, Tinned Wire Leads Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Polarization	-	
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorStripped, Tinned Wire LeadsSize / Dimension 2.95 " L x 1.41 " W x 2.58 " H (75.0 mm x 35.8 mm x 65.6 mm)	Applications	ITE (Commercial)	
Output Connector Stripped, Tinned Wire Leads Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Efficiency	Level VI, CoC Tier 2	
Size / Dimension 2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	Operating Temperature	0°C ~ 40°C	
	Output Connector	Stripped, Tinned Wire Leads	
	Size / Dimension	2.95" L x 1.41" W x 2.58" H (75.0mm x 35.8mm x 65.6mm)	
Report errors?			Report errors?

SMI18-24-B-ST Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SMI18-24-B-ST Payment Methods



















SMI18-24-B-ST Shipping Methods













If you have any question about SMI18-24-B-ST, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com