

SML-LX1110UPGC-ATR

SML-LX1110UPGC-ATR Information



For Reference Only

Part Number SML-LX1110UPGC-ATR
Manufacturer Lumex Opto/Components Inc.

Category Optoelectronics LED Lighting - Color

Description LED 525NM ULT GREEN CLEAR 4PLCC

Package 4-SMD, J-Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SML-LX1110UPGC-ATR Specifications

Manufacturer Part Number SML-LX1110UPGC-ATR Manufacturer Lumex Opto/Components Inc. Category Optoelectronics LED Lighting - Color Package 4-SMD, J-Lead Series TitanBrite? Color Green Wavelength 525nm (Typ) Current - Test 350mA Voltage - Forward (Vf) (Typ) 3.5V Lumens/Watt @ Current - Test 51 lm/W Current - Max 350mA Flux @ Current/Temperature - Test 63 lm (Typ) Temperature - Test 25°C Viewing Angle 120° Mounting Type Surface Mount Package / Case 4-SMD, J-Lead Supplier Device Package 4-PLCC Size / Dimension 0.394" L x 0.394" W (10.00mm x 10.00mm) Height - Seated (Max) 0.173" (4.40mm)		
Category Optoelectronics LED Lighting - Color Package 4-SMD, J-Lead Series TitanBrite? Color Green Wavelength 525nm (Typ) Current - Test 350mA Voltage - Forward (Vf) (Typ) 3.5V Lumens/Watt @ Current - Test 51 lm/W Current - Max 350mA Flux @ Current/Temperature - Test 63 lm (Typ) Temperature - Test 25°C Viewing Angle 120° Mounting Type Surface Mount Package / Case 4-SMD, J-Lead Supplier Device Package 4-PLCC Size / Dimension 0.394" L x 0.394" W (10.00mm x 10.00mm) Height - Seated (Max) 0.173" (4.40mm)	Manufacturer Part Number	SML-LX1110UPGC-ATR
Package 4-SMD, J-Lead Series TitanBrite? Color Green Wavelength 525nm (Typ) Current - Test 350mA Voltage - Forward (Vf) (Typ) 3.5V Lumens/Watt @ Current - Test 51 lm/W Current - Max 350mA Flux @ Current/Temperature - Test 63 lm (Typ) Temperature - Test 25°C Viewing Angle 120° Mounting Type Surface Mount Package / Case 4-SMD, J-Lead Supplier Device Package 4-PLCC Size / Dimension 0.394" L x 0.394" W (10.00mm x 10.00mm) Height - Seated (Max) 0.173" (4.40mm)	Manufacturer	Lumex Opto/Components Inc.
Package 4-SMD, J-Lead Series TitanBrite? Color Green Wavelength 525nm (Typ) Current - Test 350mA Voltage - Forward (Vf) (Typ) 3.5V Lumens/Watt @ Current - Test 51 lm/W Current - Max 350mA Flux @ Current/Temperature - Test 63 lm (Typ) Temperature - Test 25°C Viewing Angle 120° Mounting Type Surface Mount Package / Case 4-SMD, J-Lead Supplier Device Package 4-PLCC Size / Dimension 0.394" L x 0.394" W (10.00mm x 10.00mm) Height - Seated (Max) 0.173" (4.40mm)	Category	Optoelectronics
Series TitanBrite? Color Green Wavelength 525nm (Typ) Current - Test 350mA Voltage - Forward (Vf) (Typ) 3.5V Lumens/Watt @ Current - Test 51 lm/W Current - Max 350mA Flux @ Current/Temperature - Test 63 lm (Typ) Temperature - Test 25°C Viewing Angle 120° Mounting Type Surface Mount Package / Case 4-SMD, J-Lead Supplier Device Package 4-PLCC Size / Dimension 0.394" L x 0.394" W (10.00mm x 10.00mm) Height - Seated (Max) 0.173" (4.40mm)		LED Lighting - Color
Color Green Wavelength 525nm (Typ) Current - Test 350mA Voltage - Forward (Vf) (Typ) 3.5V Lumens/Watt @ Current - Test 51 lm/W Current - Max 350mA Flux @ Current/Temperature - Test 63 lm (Typ) Temperature - Test 25°C Viewing Angle 120° Mounting Type Surface Mount Package / Case 4-SMD, J-Lead Supplier Device Package 4-PLCC Size / Dimension 0.394" L x 0.394" W (10.00mm x 10.00mm) Height - Seated (Max) 0.173" (4.40mm)	Package	4-SMD, J-Lead
Wavelength Current - Test 350mA Voltage - Forward (Vf) (Typ) 3.5V Lumens/Watt @ Current - Test 51 lm/W Current - Max 350mA Flux @ Current/Temperature - Test 63 lm (Typ) Temperature - Test 25°C Viewing Angle 120° Mounting Type Surface Mount Package / Case 4-SMD, J-Lead Supplier Device Package Supplier Device Package 4-PLCC Size / Dimension 0.394" L x 0.394" W (10.00mm x 10.00mm) Height - Seated (Max) 0.173" (4.40mm)	Series	TitanBrite?
Current - Test 350mA Voltage - Forward (Vf) (Typ) 3.5V Lumens/Watt @ Current - Test 51 lm/W Current - Max 350mA Flux @ Current/Temperature - Test 63 lm (Typ) Temperature - Test 25°C Viewing Angle 120° Mounting Type Surface Mount Package / Case 4-SMD, J-Lead Supplier Device Package 4-PLCC Size / Dimension 0.394" L x 0.394" W (10.00mm x 10.00mm) Height - Seated (Max) 0.173" (4.40mm)	Color	Green
Voltage - Forward (Vf) (Typ) Lumens/Watt @ Current - Test 51 lm/W Current - Max 350mA Flux @ Current/Temperature - Test 63 lm (Typ) Temperature - Test 25°C Viewing Angle 120° Mounting Type Surface Mount Package / Case 4-SMD, J-Lead Supplier Device Package Size / Dimension 0.394" L x 0.394" W (10.00mm x 10.00mm) Height - Seated (Max) 0.173" (4.40mm)	Wavelength	525nm (Typ)
Lumens/Watt @ Current - Test51 lm/WCurrent - Max350mAFlux @ Current/Temperature - Test63 lm (Typ)Temperature - Test25°CViewing Angle120°Mounting TypeSurface MountPackage / Case4-SMD, J-LeadSupplier Device Package4-PLCCSize / Dimension0.394" L x 0.394" W (10.00mm x 10.00mm)Height - Seated (Max)0.173" (4.40mm)	Current - Test	350mA
Current - Max Flux @ Current/Temperature - Test 63 lm (Typ) Temperature - Test 25°C Viewing Angle 120° Mounting Type Surface Mount Package / Case 4-SMD, J-Lead Supplier Device Package 4-PLCC Size / Dimension 0.394" L x 0.394" W (10.00mm x 10.00mm) Height - Seated (Max) 0.173" (4.40mm)	Voltage - Forward (Vf) (Typ)	3.5V
Flux @ Current/Temperature - Test Control Temperature - Test Control Type Surface Mount Package / Case Control Type Surface Mount A-SMD, J-Lead Supplier Device Package Control Type Surface Mount A-SMD, J-Lead Control Type Control Type Surface Mount Control Type Control Type Surface Mount Control Type Surface Mount Control Type Surface Mount Control Type Control Type Surface Mount Control Type Control Type	Lumens/Watt @ Current - Test	51 lm/W
Temperature - Test Viewing Angle 120° Mounting Type Surface Mount Package / Case 4-SMD, J-Lead Supplier Device Package 4-PLCC Size / Dimension 0.394" L x 0.394" W (10.00mm x 10.00mm) Height - Seated (Max) 0.173" (4.40mm)	Current - Max	350mA
Viewing Angle 120° Mounting Type Surface Mount Package / Case 4-SMD, J-Lead Supplier Device Package 4-PLCC Size / Dimension 0.394" L x 0.394" W (10.00mm x 10.00mm) Height - Seated (Max) 0.173" (4.40mm)	Flux @ Current/Temperature - Test	63 lm (Typ)
Mounting Type Surface Mount Package / Case 4-SMD, J-Lead Supplier Device Package 4-PLCC Size / Dimension 0.394" L x 0.394" W (10.00mm x 10.00mm) Height - Seated (Max) 0.173" (4.40mm)	Temperature - Test	25°C
Package / Case 4-SMD, J-Lead Supplier Device Package 4-PLCC Size / Dimension 0.394" L x 0.394" W (10.00mm x 10.00mm) Height - Seated (Max) 0.173" (4.40mm)	Viewing Angle	120°
Supplier Device Package 4-PLCC Size / Dimension 0.394" L x 0.394" W (10.00mm x 10.00mm) Height - Seated (Max) 0.173" (4.40mm)	Mounting Type	Surface Mount
Size / Dimension 0.394" L x 0.394" W (10.00mm x 10.00mm) Height - Seated (Max) 0.173" (4.40mm)	Package / Case	4-SMD, J-Lead
Height - Seated (Max) 0.173" (4.40mm)	Supplier Device Package	4-PLCC
	Size / Dimension	0.394" L x 0.394" W (10.00mm x 10.00mm)
Report errors?	Height - Seated (Max)	0.173" (4.40mm)
		Report errors?

SML-LX1110UPGC-ATR Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SML-LX1110UPGC-ATR Payment Methods



















SML-LX1110UPGC-ATR Shipping Methods













If you have any question about SML-LX1110UPGC-ATR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com